

# ROITHNER LASERTECHNIK

A-1040 VIENNA, SCHOENBRUNNER STRASSE 7, AUSTRIA

TEL: +43 -1- 586 52 43-0 FAX: +43 -1- 586 52 43-44

e-mail: office@roithner-laser.com http://www.roithner-laser.com

## RLT6615G TECHNICAL DATA



### High Power Visible Wavelength Laserdiode

Structure: **AlGaInP**, index guided

Lasing wavelength: **660 nm typ.**

Max. optical power: **15 mW**


Package: **9 mm**

**NOTE!**


LASERDIODE  
MUST BE COOLED!



### PIN CONNECTION:



- 1) Laser diode cathode
- 2) Laser diode anode and photodiode cathode
- 3) Photodiode anode



### Absolute Maximum Ratings (Tc=25°C)

CHARACTERISTIC	SYMBOL	RATING	UNIT
Optical Output Power	$P_o$	15	mW
LD Reverse Voltage	$V_{R(LD)}$	2	V
PD Reverse Voltage	$V_{R(PD)}$	30	V
Operation Case Temperature	$T_C$	-10 .. +50	°C
Storage Temperature	$T_{STG}$	-40 .. +85	°C

### Optical-Electrical Characteristics (Tc = 25°C)

CHARACTERISTIC	SYMBOL	TEST CONDITION	MIN	TYP	MAX	UNIT
Threshold Current	$I_{th}$		25	40	60	mA
Operation Current	$I_{op}$	$P_o = 15 \text{ mW}$		50	70	mA
Operating Voltage	$V_{op}$	$P_o = 15 \text{ mW}$		2.5	2.6	V
Lasing Wavelength	$\lambda_p$	$P_o = 15 \text{ mW}$		660	670	nm
Beam Divergence	$\theta_{//}$	$P_o = 15 \text{ mW}$	6	9	16	°
Beam Divergence	$\theta_{\perp}$	$P_o = 15 \text{ mW}$		30		°
Monitor Current	$I_m$	$P_o = 15 \text{ mW}$		100		µA
Astigmatism	$A_s$	$P_o = 15 \text{ mW}$		11		µm