


# ROITHNER LASERTECHNIK

SCHOENBRUNNER STRASSE 7, VIENNA, AUSTRIA

TEL: +43 -1- 586 52 43-0 FAX: +43 -1- 586 52 43-44

office@roithner-laser.com www.roithner-laser.com

## RLT905-500G TECHNICAL DATA



### High Power Infrared Laser Diode

Lasing mode structure: **multi mode**

Lasing wavelength: **typ. 905 nm**

Optical cw power: **500 mW**


Package: **9 mm (SOT-148)**

**NOTE!**


LASERDIODE  
MUST BE COOLED!



### PIN CONNECTION:



- 1) Laser diode cathode
- 2) Laser diode anode and photodiode cathode
- 3) Photodiode anode



### Absolute Maximum Ratings (T<sub>c</sub> = 25°C)

CHARACTERISTIC	SYMBOL	RATING	UNIT
Optical Output Power	P <sub>o</sub>	600	mW
LD Reverse Voltage	V <sub>R(LD)</sub>	1.5	V
PD Reverse Voltage	V <sub>R(PD)</sub>	10	V
Operating Temperature	T <sub>C</sub>	-20 .. +40	°C
Storage Temperature	T <sub>STG</sub>	-40 .. +70	°C

### Optical-Electrical Characteristics (T<sub>c</sub> = 25°C)

CHARACTERISTIC	SYMBOL	TEST CONDITION	MIN	TYP	MAX	UNIT
Emitting Aperture	A	cw		1 x 50		μm <sup>2</sup>
Optical Output Power	P <sub>o</sub>	cw		500		mW
Threshold Current	I <sub>th</sub>	cw	90	100	110	mA
Operation Current	I <sub>op</sub>	P <sub>o</sub> = 500 mW	650	670	690	mA
Forward Voltage	U <sub>f</sub>	P <sub>o</sub> = 500 mW	1.70	1.75	1.85	V
Lasing Wavelength	λ <sub>p</sub>	P <sub>o</sub> = 500 mW	900	905	910	nm
Spectral Width FWHM	Δλ	P <sub>o</sub> = 500 mW	1.5	2.5	10	nm
Beam Divergence	θ <sub>∥</sub>	P <sub>o</sub> = 500 mW		25		°
Beam Divergence	θ <sub>⊥</sub>	P <sub>o</sub> = 500 mW		40		°
Monitor Current	I <sub>m</sub>	P <sub>o</sub> = 500 mW	100	500	1500	μA