

REALTEK

RTL8763B Series

RTL8763BM, RTL8763BF, RTL8763BFR, RTL8763BS, RTL8763BA

BLUETOOTH 5 DUAL MODE SOC

PRELIMINARY DATASHEET (CONFIDENTIAL: Development Partners Only)

Rev. 0.93
7th, December 2017
Track ID: JATR-8275-15



Realtek Semiconductor Corp.

No. 2, Innovation Road II, Hsinchu Science Park, Hsinchu 300, Taiwan

Tel.: +886-3-578-0211. Fax: +886-3-577-6047

www.realtek.com

1. General Description

The RTL8763B series are single-chip Bluetooth ROM audio solutions for mono (RTL8763BM) and stereo (RTL8763BF/BFR, RTL8763BS, RTL8763BA) applications. The RTL8763B is composed of an ARM core and an ultra-low power DSP core with high efficiency computing power, high performance audio codec, power management unit, ADC, ultra-low current RF transceiver, and smart I/O distribution controller.

The parameter configuration tools, the EVB kits, and the MP kits, including controller hardware and software, provide a simple and flexible procedure for customers to quickly design and proceed to mass production with Realtek's new generation of audio solutions. These complete total solutions provide a fast and highly reliable development path with a very competitive R-BOM.

2. Features

General Features

- Bluetooth 5 specification compliant
- Supports HFP 1.7, HSP 1.2, A2DP 1.3, AVRCP 1.6, SPP 1.2 and PBAP 1.0
- Single-end RF radio output with high performance 10dBm of transmitter power and -94dBm 2M EDR receiver sensitivity
- Supports Bluetooth classic (BDR/EDR)
- Supports Bluetooth Low Energy (BLE)
 - ◆ Generic access service
 - ◆ Device information service
 - ◆ Proprietary services for data communication
 - ◆ Apple Notification Center Service (ANCS)
- Real Wireless Stereo (RWS)
- Supports USB type-C audio
- Supports iAP2
- Realtek's latest RCV (Real Clear Voice) technology for narrowband and wideband voice connection, including wind noise reduction
- Supports high resolution audio codec up to 24bits, 192kHz audio data format
- Supports dual analog and digital MIC, AUX-IN, I2S digital audio, analog output
- Supports high speed UART, I2C, SPI and USB2.0 compatible interface
- Supports high resolution 12-bits multi-channel ADC
- Supports PWM I/O and smart LED controller
- Supports USB BC1.2 battery charging
- Smart I/O distribution scheme with MUX
- Built-in 8Mbits FLASH memory (RTL8763BF/RTL8763BFR)

- Integrated dual switch mode power regulator, linear regulators, and battery charger; charging current up to 400mA
- Built-in battery voltage monitoring and thermal protection scheme with external thermal resistor
- SBC, AAC decoder support
- Package: 5x5mm² QFN40 (RTL8763BM, RTL8763BF, RTL8763BFR), 6x6mm² QFN48 (RTL8763BS) and 8x8mm² QFN68 (RTL8763BA) with 0.4mm pitch
- Supports OTA and USB firmware upgrade
- GSM 217Hz interference block out design
- Low BOM cost
- Green (RoHS compliant and no antimony or halogenated flame retardants)
- Supports PTA (Packet Traffic Arbiter) when co-existing with Wi-Fi

Baseband Features

- 40MHz main clock
- Supports serial flash for FW storage and parameter upgrade
- Adaptive Frequency Hopping (AFH)
- Multi-link support
- Supports Serial Copy Management System (SCMS-T) content protection

RAM and ROM Size

- ROM size 768KB
- MCU RAM size 16KB x 8 Data RAM + 8KB X 2 cache RAM
- DSP RAM 8KB x 22

RF

- Supports TX +10dBm (typ.) maximum output power for Bluetooth classic
- Supports TX +10dBm (typ.) maximum output power for Bluetooth BLE
- Supports TX +4dBm (typ.) maximum output power for Bluetooth BLE low power TPM mode
- Receive sensitivity: -94dBm (2Mbps EDR)
- Receive sensitivity: -97dBm (BLE)
- Receiver sensitivity: -106.5dBm (125K BLE long range)
- Single-end TX/RX RF port without matching component required (when TX power is below +4dBm and using PIFA type PCB antenna)
- Crystal oscillator with built-in integrated capacitor for clock offset digital tuning (0~20pF), could save 2-compensation CL cap following Realtek design guidelines

MCU

- 32-bit ARM Cortex-M4F Processor
- Supports hardware Floating Point Unit (FPU)
- Supports Memory Protect Unit (MPU)
- Supports SWD debug interface
- Executed external SPI flash
- 4-way association cache controller

DSP Audio Processing

- Enhanced Tensilica Hi-Fi-mini compatible 24-bit DSP core
- 2 single-cycle MACs: 24 x 24-bit multiplier and 56-bit accumulator
- Supports G.711 A-Law, μ -Law, continuous-variable-slope-delta (CVSD) and mSBC voice codecs
- Supports 8/16 kHz 1/2-mic noise suppression and echo cancellation

- Packet Loss Concealment (PLC) for voice processing
- SBC, and AAC-LC audio codecs supported for BT audio streaming

Audio Codec

- Dual operation voltage range 2.8V and 1.8V
- Supports cap-less, single-ended, and differential mode at the DAC path
- Supports 16ohm and 32ohm speaker loading
- Stereo 24-bit digital-to-analog (DAC) with 102dBA SNR
- Stereo 24-bit analog-to-digital (ADC) with 97dBA SNR
- 5-band configurable EQ at both DAC/ADC paths
- Sampling rates of 8, 16, 32, 44.1, 48, 88.2, and 96kHz are supported.
- Built-in MIC bias generator

Digital Audio Interface

- Supports two PDM digital MIC inputs
- Supports 24-bit, 192kHz on I2S digital audio
- Sampling frequency 8/16/32/44.1/48/88.2/96/176.4/192kHz

Radio

- Compliant with Bluetooth Core Specification including BR/EDR/LE-1M/LE-2M/LE-Coded (LongRange)
- Fully integrated balun and synthesizer minimizes external components.
- RF circuit design minimizes power-consumption while keeping excellent performance

PMU

- Highly integrated PMU design for the system application

- Dual switching mode regulator for digital core, radio and audio codec respectively
- Built-in LDO for the I/O and FLASH memory
- Built-in Li-Ion battery charger with up to 400mA charger current capability
- Supports ambient thermal detection to detect the battery temperature
- Built-in OVP, OCP, UVP protection to protect the system.

Operating Condition

- Operating voltage: 2.8V to 4.35V (VBAT)
- Temperature range: -40°C to +85°C

Package

- 5mmx5mm, QFN40 package (RTL8763BM)
- 5mmx5mm, QFN40 package (RTL8763BF/BFR)
- 6mmx6mm, QFN48 package (RTL8763BS)
- 8mmx8mm, QFN68 package (RTL8763BA)

3. System Applications

- Mono headset
- Stereo headset
- Real Wireless Stereo (RWS) headset
- Mono speaker
- Stereo speaker

Realtek RTL8763B
Bluetooth RF Test Tool
RTLBTAPP
User Manual

Draft v0.2

2017/08/8

Revision History

Date	Version	
2017/07/11	Draft v0.1	Initial
2017/08/08	Draft v0.1	Add BLE DTM Test

Catalog

Revision History 2

Figure List 4

- 1. Overview 5
- 2. Files 6
- 3. Hardware environment 6
- 4. Open RTLBTAPP 7
- 5. DUT (Link) Test Mode 9
- 6. LE DUT TX/RX Test(MP) 10
- 7. BLE Direct Test Mode 11
- 8. Appendix :FCC /IC /NCC Statement

Figure List

Figure 1 File List	6
Figure 2 Open BTLBTAPP	7
Figure 3 Check COM port number	8
Figure 4 Device opens successfully	8
Figure 5 Enter link test mode	9
Figure 6 LE Test.....	10
Figure 7 Reference EVB board define	11
Figure 8 Connect to instrument by uart interface.....	11
Figure 9 Connect to instrument for RS232 interface.....	12
Figure 10 Connect to instrument for usb to uart converter boar	12

1. Overview

This document is used to introduce RF test tool “RTLBTAPP” for Realtek Bluetooth chip RTL8763B series. Customers should comply with the steps and requirements under this document. Contact Realtek Bluetooth FAE if any problem arises in RF test flow.

2. Files

MP tool package is provided to customers in binary format:

RTLBTAPP.exe	MP executable file
RtlBluetoothMP.dll	MP dll library



Figure 1 File List

Double click “RTLBTAPP.exe” to open this tool. However, please use “Run Administrator” to open it in Vista/Windows7 or higher.

3. Hardware environment

Before use this tool, PC should direct connected UART port. The connection between Bluetooth and HOST chip must be cut off.

4. Open RTLBTAPP




Figure 2 Open BTLBTAPP

Step 1: Select correct interface.

- UART:

If the module interface is UART, please select “UART” and check COM port number in Device Manager.




Figure 3 Check COM port number

Step 2: Click “Open”.

After clicking “Open” button, the up left corner changes to green means it is successful to open BT Device.




Figure 4 Device opens successfully

5. DUT (Link) Test Mode




Figure 5 Enter link test mode

Enter link test mode, please follow the below operations.

- **Step 1:** Click “HCI Reset” button to reset.
- **Step 2:** Click “Test Mode” button to enter DUT Test Mode (link test mode).
- **Step 3:** After testing, click “HCI Reset” button to exit DUT Test Mode

6. LE DUT TX/RX Test(MP)




Figure 6 LE Test


- **Step 1:** Choose “LE Test”.
- **Step 2:** Choose “LE PKT TX” or “LE PKT RX”
- **Step 3:** Choose LE Test Parameters :
 - (a) Channel :0~39.
 - (b) Data length:0~0xFF
 - (c) PayType: PRBS9, 1111_0000, 1010, PRBS15, ALL1, ALL0, 0000_1111, 0101
 - (d) PHY: LE 1M PHY, LE 2M PHY, LE Coded PHY with S=8, LE Coded PHY with S=2
- **Step 4:** Click “Start” button and start to test. After testing, click “Stop” button. The green rectangle shows received LE Rx Packets in LE PKT RX mode.

7. BLE Direct Test Mode

This section describes the direct test mode mechanisms for testing Bluetooth Low Energy devices and explains how the direct test mode connection is established.

This Direct Test Mode MODE requires a direct connection to the Bluetooth measurement instrument. The Realtek Bluetooth Device uses the HCI UART interface to connect to the Bluetooth measurement instrument.

Realtek defines the uart pin as shown in the table below:

PIN Name	Interface
S06	UART RX
S07	UART TX
EVB	 <p style="text-align: center;">Figure 7 Reference EVB board define</p> <p>Note: Reference EVB board define as(This version may change)</p>

- If if Bluetooth measurement instrument interface is hci uart or 2 wire:




Figure 8 Connect to instrument by uart interface

- if Bluetooth measurement instrument interface is RS232, Level shift is required also .




Figure 9 Connect to instrument for RS232 interface

- if Bluetooth measurement instrument interface has support USB converter UART board, such as FTDI USB converter board.




Figure 10 Connect to instrument for usb to uart converter board

- **Configuration test environment step by step :**
 1. Connect an RF cable between the antenna connector on the EUT and Bluetooth measurement equipment.
 2. Connect the HCI UART(RS232) TX to UART RX of Bluetooth measurement equipment (level shift or usb converter board).
 3. Connect the HCI UART(RS232) RX to UART TX of Bluetooth measurement equipment (level shift or usb converter board).
 4. Connect GND between the EUT and Bluetooth measurement equipment or connect USB Cable to Tester.
 5. Push HW Reset pin and to begin test..

8. Appendix

FCC Statement:

This device complies with part 15 of the FCC Rules. Operation is subject to the following two conditions:

- (1) This device may not cause harmful interference, and
- (2) this device must accept any interference received, including interference that may cause undesired operation.

NOTE: This equipment has been tested and found to comply with the limits for a Class B digital device, pursuant to part 15 of the FCC Rules. These limits are designed to provide reasonable protection against harmful interference in a residential installation.

This equipment generates, uses and can radiate radio frequency energy and, if not installed and used in accordance with the instructions, may cause harmful interference to radio communications. However, there is no guarantee that interference will not occur in a particular installation.

If this equipment does cause harmful interference to radio or television reception, which can be determined by turning the equipment off and on, the user is encouraged to try to correct the interference by one or more of the following measures:

- Reorient or relocate the receiving antenna.
- Increase the separation between the equipment and receiver.
- Connect the equipment into an outlet on a circuit different from that to which the receiver is connected.
- Consult the dealer or an experienced radio/TV technician for help.

Changes or modifications not expressly approved by the party responsible for compliance could void the user's authority to operate the equipment.

FCC Label Instructions

The outside of final products that contains this module device must display a label referring to the enclosed module. This exterior label can use wording such as the following: “**Contains Transmitter Module FCC ID: TX2-RTL8763BA**” or “**Contains FCC ID: TX2-RTL8763BA**.” Any similar wording that expresses the same meaning may be used.

Additionally, there must be the following sentence on the device, unless it is too small to carry it:

“This device complies with part 15 of the FCC Rules. Operation is subject to the following two conditions:

(1) This device may not cause harmful interference, and (2) this device must accept any interference received, including interference that may cause undesired operation.”

IC Statement

This device complies with Industry Canada license-exempt RSS standard(s).

Operation is subject to the following two conditions: (1) this device may not cause interference, and (2) this device must accept any interference, including interference that may cause undesired operation of the device.

Le present appareil est conforme aux CNR d'Industrie Canada applicables aux appareils radio exempts de licence. L'exploitation est autorisee aux deux conditions suivantes : (1) l'appareil ne doit pas produire de brouillage, et (2) l'utilisateur de l'appareil doit accepter tout brouillage radioelectrique subi, meme si le brouillage est susceptible d'en compromettre le fonctionnement.

If the final product is to be sold in Canada, then this exterior label should use wording such as the following: "Contains Transmitter Module IC: 6317A-RTL8763BA"

Taiwan regulatory information(NCC)

低功率電波輻射性電機管理辦法

第十二條 經型式認證合格之低功率射頻電機，非經許可，公司、商號或使用者均不得擅自變更頻率、加大功率或變更原設計之特性及功能。

第十四條 低功率射頻電機之使用不得影響飛航安全及干擾合法通信；經發現有干擾現象時，應立即停用，並改善至無干擾時方得繼續使用。

前項合法通信，指依電信法規定作業之無線電通信。低功率射頻電機須忍受合法通信或工業、科學及醫療用電波輻射性電機設備之干擾。