



## Features

- 150V/120A  
 $R_{DS(ON)}=15m\Omega(Typ.) @ V_{GS}=10V$
- Avalanche Rated
- Reliable and Rugged
- Lead Free and Green Devices Available

## Applications

- Automotive applications and a wide variety of other applications
- High Efficiency Synchronous in SMPS
- High Speed Power Switching

## Pin Description



## Absolute Maximum Ratings

| Symbol   | Parameter                                     | Rating                                      | Unit                      |
|--|---|---|---------------------------|
| <b>Common Ratings</b> ( $T_A=25^\circ\text{C}$ Unless Otherwise Noted) |   |   |                           |
| $V_{DSS}$  | Drain-Source Voltage                          | 150   | V                         |
| $V_{GSS}$  | Gate-Source Voltage                           | $\pm 25$                                    |                           |
| $T_J$  | Maximum Junction Temperature                  | 175   | $^\circ\text{C}$          |
| $T_{STG}$  | Storage Temperature Range                     | -55 to 175                                  | $^\circ\text{C}$          |
| $I_S$  | Diode Continuous Forward Current              | $T_C=25^\circ\text{C}$<br>120 <sup>①</sup>  | A                         |
| <b>Mounted on Large Heat Sink</b>                                      |   |   |                           |
| $I_{DP}$   | 300 $\mu\text{s}$ Pulsed Drain Current Tested | $T_C=25^\circ\text{C}$<br>400 <sup>②</sup>  | A                         |
| $I_D$  | Continue Drain Current                        | $T_C=25^\circ\text{C}$<br>120 <sup>①</sup>  |                           |
|  |   | $T_C=100^\circ\text{C}$<br>100 <sup>①</sup> |                           |
| $P_D$  | Maximum Power Dissipation                     | $T_C=25^\circ\text{C}$<br>326               | W                         |
|  |   | $T_C=100^\circ\text{C}$<br>163              |                           |
| $R_{\theta JC}$  | Thermal Resistance -Junction to Case          | 0.46  | $^\circ\text{C}/\text{W}$ |
| <b>Drain-Source Avalanche Ratings</b>                                  |   |   |                           |
| $E_{AS}$ <sup>③</sup>  | Avalanche Energy ,Single Pulsed               | 441   | mJ                        |


**Electrical Characteristics** ( $T_A=25^{\circ}\text{C}$  Unless Otherwise Noted)

| Symbol  | Parameter                        | Test Condition  | RU120N15Q |      |           | Unit       |
|---|----------------------------------|---|-----------|------|-----------|------------|
|   |                                  |   | Min.      | Typ. | Max.      |            |
| <b>Static Characteristics</b>                     |                                  |   |           |      |           |            |
| $BV_{DSS}$  | Drain-Source Breakdown Voltage   | $V_{GS}=0V, I_{DS}=250\mu A$  | 150       |      |           | V          |
| $I_{DSS}$   | Zero Gate Voltage Drain Current  | $V_{DS}=150V, V_{GS}=0V$<br>$T_J=85^{\circ}\text{C}$                      |           |      | 1         | $\mu A$    |
|   |                                  |   |           |      | 30        |            |
| $V_{GS(th)}$                                      | Gate Threshold Voltage           | $V_{DS}=V_{GS}, I_{DS}=250\mu A$  | 2         | 3    | 4         | V          |
| $I_{GSS}$   | Gate Leakage Current             | $V_{GS}=\pm 25V, V_{DS}=0V$   |           |      | $\pm 100$ | nA         |
| $R_{DS(ON)}^{(4)}$                                | Drain-Source On-state Resistance | $V_{GS}=10V, I_{DS}=60A$  |           | 15   | 17        | m $\Omega$ |
| <b>Diode Characteristics</b>                      |                                  |   |           |      |           |            |
| $V_{SD}^{(4)}$                                    | Diode Forward Voltage            | $I_{SD}=60A, V_{GS}=0V$   |           |      | 1.2       | V          |
| $t_{rr}$  | Reverse Recovery Time            | $I_{SD}=60A, di_{SD}/dt=100A/\mu s$                                       |           | 68   |           | ns         |
| $q_{rr}$  | Reverse Recovery Charge          |   |           | 130  |           | nC         |
| <b>Dynamic Characteristics</b> <sup>(5)</sup>     |                                  |   |           |      |           |            |
| $R_G$   | Gate Resistance                  | $V_{GS}=0V, V_{DS}=0V, F=1\text{MHz}$                                     |           | 1.0  |           | $\Omega$   |
| $C_{iss}$   | Input Capacitance                | $V_{GS}=0V,$<br>$V_{DS}=30V,$<br>Frequency=1.0MHz                         |           | 6600 |           | pF         |
| $C_{oss}$   | Output Capacitance               |   |           | 900  |           |            |
| $C_{riss}$  | Reverse Transfer Capacitance     |   |           | 480  |           |            |
| $t_{d(ON)}$                                       | Turn-on Delay Time               | $V_{DD}=35V, R_L=35\Omega,$<br>$I_{DS}=1A, V_{GEN}=10V,$<br>$R_G=6\Omega$ |           | 21   |           | ns         |
| $t_r$   | Turn-on Rise Time                |   |           | 40   |           |            |
| $t_{d(OFF)}$                                      | Turn-off Delay Time              |   |           | 110  |           |            |
| $t_f$   | Turn-off Fall Time               |   |           | 69   |           |            |
| <b>Gate Charge Characteristics</b> <sup>(5)</sup> |                                  |   |           |      |           |            |
| $Q_g$   | Total Gate Charge                | $V_{DS}=30V, V_{GS}=10V,$<br>$I_{DS}=60A$                                 |           | 155  |           | nC         |
| $Q_{gs}$  | Gate-Source Charge               |   |           | 45   |           |            |
| $Q_{gd}$  | Gate-Drain Charge                |   |           | 48   |           |            |

- Notes:
- ① Calculated continuous current based on maximum allowable junction temperature. The package limitation current is 90A.
  - ② Pulse width limited by safe operating area.
  - ③ Limited by  $T_{Jmax}$ ,  $I_{AS}=30A$ ,  $V_{DD}=48V$ ,  $R_G=47\Omega$ , Starting  $T_J=25^{\circ}\text{C}$ .
  - ④ Pulse test; Pulse width  $\leq 300\mu s$ , duty cycle  $\leq 2\%$ .
  - ⑤ Guaranteed by design, not subject to production testing.


**Typical Characteristics**

**Power Dissipation**




$T_j$  - Junction Temperature ( $^{\circ}C$ )

**Drain Current**




$T_j$  - Junction Temperature ( $^{\circ}C$ )





**Safe Operation Area**







**Thermal Transient Impedance**





**Typical Characteristics**





**Typical Characteristics**



### Avalanche Test Circuit and Waveforms



### Switching Time Test Circuit and Waveforms




**Ordering and Marking Information**

| <b>Device</b> | <b>Marking</b> | <b>Package</b> | <b>Packaging</b> | <b>Quantity</b> | <b>Reel Size</b> | <b>Tape width</b> |
|---------------|----------------|----------------|------------------|-----------------|------------------|-------------------|
| RU120N15Q     | RU120N15Q      | TO-247         | Tube             | 30              | -                | -                 |

**Package Information**

**TO-247**



| SYMBOL | MM         |        | INCH       |       | SYMBOL | MM         |        | INCH       |       |
|--------|------------|--------|------------|-------|--------|------------|--------|------------|-------|
|        | MIN        | MAX    | MIN        | MAX   |        | MIN        | MAX    | MIN        | MAX   |
| A      | 4.850      | 5.150  | 0,191      | 0.200 | E2     | 3.600 REF. |        | 0.142 REF. |       |
| A1     | 2.200      | 2.600  | 0.087      | 0.102 | L      | 40.900     | 41.300 | 1.610      | 1.626 |
| B      | 1.000      | 1.400  | 0.039      | 0.055 | L1     | 24.800     | 25.100 | 0.976      | 0.988 |
| b1     | 2.800      | 3.200  | 0.110      | 0.126 | L2     | 20.300     | 20.600 | 0.799      | 0.811 |
| b2     | 1.800      | 2.200  | 0.071      | 0.087 | Φ      | 7.100      | 7.300  | 0.280      | 0.287 |
| c      | 0.500      | 0.700  | 0.020      | 0.028 | e      | 5.450 TYP  |        | 0.215 TYP  |       |
| c1     | 1.900      | 2.100  | 0.075      | 0.083 | H      | 5.980 REF. |        | 0.235 REF. |       |
| D      | 15.450     | 15.750 | 0.608      | 0.620 | h      | 0.000      | 0.300  | 0.000      | 0.012 |
| E1     | 3.500 REF. |        | 0.138 REF. |       |        |            |        |            |       |

**ALL DIMENSIONS REFER TO JEDEC STANDARD  
DO NOT INCLUDE MOLD FLASH OR PROTRUSIONS**



## Customer Service

**Worldwide Sales and Service:**

Sales@ruichips.com

**Technical Support:**

Technical@ruichips.com

**Investor Relations Contacts:**

Investor@ruichips.com

**Marcom Contact:**

Marcom@ruichips.com

**Editorial Contact:**

Editorial@ruichips.com

**HR Contact:**

HR@ruichips.com

**Legal Contact:**

Legal@ruichips.com

**Shen Zhen RUICHIPS Semiconductor CO., LTD**

Room 501, the 5floor An Tong Industrial Building,  
NO.207 Mei Hua Road Fu Tian Area Shen Zhen City, CHINA

**TEL:** (86-755) 8311-5334

**FAX:** (86-755) 8311-4278

**E-mail:** Sales-SZ@ruichips.com