


Features

- 20V/6A,
 $R_{DS(ON)} = 21m\Omega$ (Typ.) @ $V_{GS} = 4.5V$
 $R_{DS(ON)} = 30m\Omega$ (Typ.) @ $V_{GS} = 2.5V$
- Super High Dense Cell Design
- Reliable and Rugged
- Lead Free and Green Available

Applications

- Power Management

Pin Description



Absolute Maximum Ratings





Symbol	Parameter		Rating	Unit
Common Ratings (T _A =25°C Unless Otherwise Noted)				
V _{DSS}	Drain-Source Voltage		20	V
V _{GSS}	Gate-Source Voltage		±12	
T _J	Maximum Junction Temperature		150	°C
T _{STG}	Storage Temperature Range		-55 to 150	°C
I _S	Diode Continuous Forward Current	T _A =25°C	1.7	A
Mounted on Large Heat Sink				
I _{DP}	300μs Pulse Drain Current Tested	T _A =25°C	24 ^①	A
I _D	Continuous Drain Current(V _{GS} =4.5V)	T _A =25°C	6	A
		T _A =70°C	4.5	
P _D	Maximum Power Dissipation	T _A =25°C	1.5	W
		T _A =70°C	0.96	
R _{θJA} ^②	Thermal Resistance-Junction to Ambient		83.5	°C/W

Electrical Characteristics ($T_A=25^{\circ}\text{C}$ Unless Otherwise Noted)

Symbol	Parameter	Test Condition	RU8205G			Unit
			Min.	Typ.	Max.	
Static Characteristics						
BV _{DSS}	Drain-Source Breakdown Voltage	V _{GS} =0V, I _{DS} =250μA	20			V
I _{DSS}	Zero Gate Voltage Drain Current	V _{DS} =20V, V _{GS} =0V			1	μA
		T _J =85°C			30	
V _{GS(th)}	Gate Threshold Voltage	V _{DS} =V _{GS} , I _{DS} =250μA	0.5	0.7	1.5	V
I _{GSS}	Gate Leakage Current	V _{GS} =±10V, V _{DS} =0V			±100	nA
R _{DS(ON)} ^③	Drain-Source On-state Resistance	V _{GS} =4.5V, I _{DS} =6A		21	24	mΩ
		V _{GS} =2.5V, I _{DS} =5A		30	40	mΩ
Diode Characteristics						
V _{SD} ^③	Diode Forward Voltage	I _{SD} =1A, V _{GS} =0V			1	V
Dynamic Characteristics ^④						
R _G	Gate Resistance	V _{GS} =0V, V _{DS} =0V, F=1MHz		1.8		Ω
C _{iSS}	Input Capacitance	V _{GS} =0V, V _{DS} =10V, Frequency=1.0MHz		580		pF
C _{oSS}	Output Capacitance			120		
C _{rSS}	Reverse Transfer Capacitance			95		
t _{d(ON)}	Turn-on Delay Time	V _{DD} =10V, R _L =1.7Ω, I _{DS} =6A, V _{GEN} =4.5V, R _G =6Ω		5		ns
t _r	Turn-on Rise Time			11		
t _{d(OFF)}	Turn-off Delay Time			38		
t _f	Turn-off Fall Time			13		
Gate Charge Characteristics ^④						
Q _g	Total Gate Charge	V _{DS} =16V, V _{GS} =4.5V, I _{DS} =6A		10	14	nC
Q _{gs}	Gate-Source Charge			1.5		
Q _{gd}	Gate-Drain Charge			3.4		


- Notes: ① Pulse width limited by safe operating area.
 ② When mounted on 1 inch square copper board, $t \leq 10\text{sec}$.
 ③ Pulse test ; Pulse width $\leq 300\mu\text{s}$, duty cycle $\leq 2\%$.
 ④ Guaranteed by design, not subject to production testing.

Typical Characteristics




Typical Characteristics


Output Characteristics




Drain-Source On Resistance



Drain-Source On Resistance




Gate Threshold Voltage




Typical Characteristics


Drain-Source On Resistance




Source-Drain Diode Forward





Capacitance





Gate Charge



Avalanche Test Circuit and Waveforms



Switching Time Test Circuit and Waveforms




Ordering and Marking Information

Device	Marking	Package	Packaging	Quantity	Reel Size	Tape width
RU8205G	RU8205G	TSSOP8	Tape&Reel	3000	13''	12mm

Package Information

TSSOP-8



SYMBOL	MM		INCH		SYMBOL	MM		INCH	
	MIN	MAX	MIN	MAX		MIN	MAX	MIN	MAX
D	2.900	3.100	0.114	0.122	A2	0.800	1.050	0.031	0.041
E	4.300	4.500	0.169	0.177	A1	0.050	0.150	0.002	0.006
b	0.190	0.300	0.007	0.012	e	0.65 (BSC)		0.026 (BSC)	
c	0.090	0.200	0.004	0.008	L	0.500	0.700	0.020	0.028
E1	6.250	6.550	0.246	0.258	H	0.25(TYP)		0.01(TYP)	
A		1.200		0.047	θ	0°	8°	0°	8°

ALL DIMENSIONS REFER TO JEDEC STANDARD
DO NOT INCLUDE MOLD FLASH OR PROTRUSIONS

Customer Service

Worldwide Sales and Service:

Sales@ruichips.com

Technical Support:

Technical@ruichips.com

Investor Relations Contacts:

Investor@ruichips.com

Marcom Contact:

Marcom@ruichips.com

Editorial Contact:

Editorial@ruichips.com

HR Contact:

HR@ruichips.com

Legal Contact:

Legal@ruichips.com

Shen Zhen RUICHIPS Semiconductor CO., LTD

Room 501, the 5floor An Tong Industrial Building,
NO.207 Mei Hua Road Fu Tian Area Shen Zhen City, CHINA

TEL: (86-755) 8311-5334

FAX: (86-755) 8311-4278

E-mail: Sales-SZ@ruichips.com