

**SURFACE MOUNT  
GLASS PASSIVATED RECTIFIER**

**REVERSE VOLTAGE – 50 to 1000 Volts  
FORWARD CURRENT – 1.0 Ampere**


**FEATURES**

- Glass passivated chip
- For surface mounted applications
- Low reverse leakage current
- Low forward voltage drop
- High current capability

**MECHANICAL DATA**

- Case: Molded plastic
- Case Material: "Green" molding compound, UL flammability classification 94V-0, (No Br. Sb. Cl.), "Halogen-free"
- Suffix "Q" with Part No. means AEC-Q101 Qualified
- Polarity: Indicated by cathode band
- Weight : 0.07 grams ( Approximate )

**SMA**



SMA		
DIM.	MIN.	MAX
A	4.06	4.57
B	2.29	2.92
C	1.27	1.63
D	0.15	0.31
E	4.83	5.59
F	0.05	0.20
G	1.96	2.40
H	0.76	1.52
All dimension in millimeter		

**MAXIMUM RATINGS AND ELECTRICAL CHARACTERISTICS**

Ratings at 25°C ambient temperature unless otherwise specified.

**ABSOLUTE RATINGS**

PARAMETER	SYMBOL	S1A	S1B	S1D	S1G	S1J	S1K	S1M	UNIT
Maximum repetitive peak reverse voltage	$V_{RRM}$	50	100	200	400	600	800	1000	V
Maximum DC blocking voltage	$V_{DC}$	50	100	200	400	600	800	1000	V
Average rectified output current @ $T_L=100^\circ\text{C}$ @ $T_C=100^\circ\text{C}$	$I_{F(AV)}$	1.0							A
Peak forward surge current 8.3 ms single half sine-wave superimposed on rated load. ( JEDEC METHOD)	$I_{FSM}$	30							A
Operation and storage temperature range	$T_J, T_{STG}$	-55 to +150							°C

**STATIC ELECTRICAL CHARACTERISTICS**

PARAMETER	TEST CONDITION	SYMBOL	MAX	UNIT
Forward voltage	$I_F=1.0A$	$V_F$	1.1	V
Reverse leakage current	$V_R$ at rated $T_J=25^\circ\text{C}$ $T_J=125^\circ\text{C}$	$I_R$	5.0 100	uA
Typical junction capacitance (Note 1)		$C_J$	10	pF

**THERMAL CHARACTERISTICS**

PARAMETER	SYMBOL	TYP.	UNIT
Typical thermal resistance (Note 2)	$R_{thJL}$ $R_{thJC}$	30 30	°C/W

**DYNAMIC ELECTRICAL CHARACTERISTICS**

PARAMETER	TEST CONDITION	SYMBOL	TYP.	UNIT
Reverse recovery time	$I_F=0.5A, I_{RR}=0.25A, I_R=1.0A$	$T_{RR}$	1300	ns

**Note :**


- (1) Measured at 1.0MHz and applied reverse voltage of 4.0V DC.
- (2) Thermal resistance junction to ambient, case and lead.

REV. 14, Apr.-2017, KSDA01


# RATING AND CHARACTERISTIC CURVES S1A thru S1M




**FIG.1- FORWARD CURRENT DERATING CURVE**




**FIG.2- MAXIMUM NON-REPETITIVE SURGE CURRENT**



**FIG.3- TYPICAL FORWARD CHARACTERISTICS**



**FIG.4- TYPICAL REVERSE CHARACTERISTICS**



## **Important Notice and Disclaimer**

LSC reserves the right to make changes to this document and its products and specifications at any time without notice. Customers should obtain and confirm the latest product information and specifications before final design, purchase or use.

LSC makes no warranty, representation or guarantee regarding the suitability of its products for any particular purpose, nor does LSC assume any liability for application assistance or customer product design. LSC does not warrant or accept any liability with products which are purchased or used for any unintended or unauthorized application.

No license is granted by implication or otherwise under any intellectual property rights of LSC.

LSC products are not authorized for use as critical components in life support devices or systems without express written approval of LSC.