


Features

- $V_{DS}=40V, I_D=120A$
 $R_{ds(on)}(typ)=3.5m\Omega @ V_{GS}=4.5V$
 $R_{ds(on)}(typ)=3m\Omega @ V_{GS}=10V$
- 100% Avalanche Tested
- 100% Rg Tested
- Lead-Free (RoHS Compliant)


Applications

- DC Motor Control
- DC-DC Converters
- BMS
- SMPS
- Automotive Environment

Internal Circuit and Pin Description

	
Package	TO-252
Package Code	M

Package Marking



Absolute Maximum Ratings ($T_C=25^{\circ}C$ unless otherwise noted)

Symbol	Parameter	Value	Units
V_{DS}	Drain-Source Voltage	40	V
I_D	Continuous Drain Current ($T_C=25^{\circ}C$)	120	A
	Continuous Drain Current ($T_C=100^{\circ}C$)	76	A
I_{DM}	Pulsed Drain Current (Note 1)	480	A
V_{GS}	Gate-Source Voltage	± 20	V
E_{AS}	Single Pulsed Avalanche Energy (Note 2)	462	mJ
P_D	Maximum Power Dissipation ($T_C=25^{\circ}C$)	105	W
	Derating Factor above $25^{\circ}C$	0.84	W/ $^{\circ}C$
T_J	Operating Junction Temperature Range	-55 to +150	$^{\circ}C$
T_{STG}	Storage Temperature Range	-55 to +150	$^{\circ}C$

Thermal Characteristics

Symbol	Parameter	Value	Units
$R_{th\ j-c}$	Thermal Resistance, Junction to case	1.19	$^{\circ}\text{C}/\text{W}$

Electrical Characteristics ($T_C=25^{\circ}\text{C}$ unless otherwise noted)

Symbol	Parameter	Test Conditions	Min.	Typ.	Max.	Units
BV_{DSS}	Drain-Source Breakdown Voltage	$V_{GS}=0V, I_D=250\mu A$	40	-	-	V
I_{DSS}	Drain-Source Leakage Current	$V_{DS}=38V, V_{GS}=0V$	-	-	1	μA
I_{GSS}	Gate Leakage Current, Forward	$V_{GS}=20V, V_{DS}=0V$	-	-	100	nA
	Gate Leakage Current, Reverse	$V_{GS}=-20V, V_{DS}=0V$	-	-	-100	nA
$V_{GS(th)}$	Gate Threshold Voltage	$V_{GS}=V_{DS}, I_D=250\mu A$	1.5	2	2.5	V
$R_{DS(on)}$	Drain-Source On-State Resistance	$V_{GS}=4.5V, I_D=40A$	2.8	3.5	4.2	$m\Omega$
		$V_{GS}=10V, I_D=40A$	2.4	3	3.6	$m\Omega$
Q_g	Total Gate Charge	$V_{DD}=30V$	-	63	-	nC
Q_{gs}	Gate-Source Charge	$V_{GS}=4.5V$	-	17	-	nC
Q_{gd}	Gate-Drain Charge	$I_D=40A$ (Note 3)	-	32	-	nC
$t_{d(on)}$	Turn-on Delay Time	$V_{DD}=37.5V, V_{GS}=10V$	-	26	-	ns
t_r	Turn-on Rise Time	$I_D=45A, R_G=4.7\Omega$	-	37	-	ns
$t_{d(off)}$	Turn-off Delay Time	$T_C=25^{\circ}\text{C}$	-	81	-	ns
t_f	Turn-off Fall Time	(Note 3)	-	47	-	ns
R_g	Gate Resistance	$V_{DS}=0V, V_{GS}=0V, f=1\text{MHz}$	-	0.8	-	Ω
C_{iss}	Input Capacitance	$V_{DS}=25V$	-	5829	-	pF
C_{oss}	Output Capacitance	$V_{GS}=0V$	-	596	-	pF
Cr_{ss}	Reverse Transfer Capacitance	$f = 1\text{MHz}$	-	418	-	pF







Source-Drain Diode Characteristics ($T_C=25^{\circ}\text{C}$ unless otherwise noted)







Symbol	Parameter	Test Conditions	Min.	Typ.	Max.	Units
I_S	Continuous Source Diode Forward Current		-	-	120	A
I_{SM}	Pulsed Source Diode Forward Current (Note 1)		-	-	480	A
V_{SD}	Forward On Voltage	$V_{GS}=0V, I_S=45A$	-	0.89	1	V
t_{rr}	Reverse Recovery Time	$V_{GS}=0V, I_S=45A$	-	48	-	ns
Q_{rr}	Reverse Recovery Charge	$dI_F/dt = 100A/\mu s$	-	95	-	nC

Notes:



1. Repetitive Rating: Pulse width limited by maximum junction temperature
2. $L=0.5mH, V_{DD}=36V, R_G=25\Omega$, Starting $T_J=25^{\circ}\text{C}$
3. Pulse Width $\leq 300\mu s$; Duty Cycle $\leq 2\%$

Typical Characteristics









Gate Charge Test Circuit and Waveforms



Switching Time Test Circuit & Waveforms





Avalanche Test Circuit& Waveforms




Package Outline

TO252



UNIT:mm



SYMBOL	MIN	NOM	MAX
A	2.25	2.30	2.35
A1	1.02	1.07	1.12
A2	0.05	0.1	0.15
b	0.71	0.76	0.81
c	0.46	0.51	0.56
c1	0.46	0.51	0.56
D	6.05	6.10	6.15
E	6.55	6.60	6.65
E1	5.23	5.33	5.43
E2	4.73	4.83	4.93
E3	5.30	5.40	5.50
e	2.286 BSC		
H	9.82	10.02	10.22
L	0.96	1.01	1.06
L1	0.7	0.8	0.9
θ	5°	7°	9°
θ_1	1°	3°	5°
θ_2	23°	25°	27°
θ_3	5°	7°	9°