


isc Thyristors

S8008R

DESCRIPTION

- With TO-220 Non-isolated packaging
- Glass passivated junctions and center gate fire for greater parameter uniformity and stability
- Minimum Lot-to-Lot variations for robust device performance and reliable operation

ABSOLUTE MAXIMUM RATINGS($T_a=25^\circ\text{C}$)

SYMBOL	PARAMETER	MIN	UNIT	
V_{DRM}	Repetitive peak off-state voltage	800	V	
V_{RRM}	Repetitive peak reverse voltage	800	V	
$I_{T(RMS)}$	RMS on-state current	8	A	
I_{TSM}	Surge non-repetitive on-state current	50Hz 60Hz	83 100	A
$P_{G(AV)}$	Average gate power dissipation	0.5	W	
T_j	Operating junction temperature	-40~125	$^\circ\text{C}$	
T_{stg}	Storage temperature	-40~150	$^\circ\text{C}$	

ELECTRICAL CHARACTERISTICS ($T_c=25^\circ\text{C}$ unless otherwise specified)

SYMBOL	PARAMETER	CONDITIONS	MIN	MAX	UNIT
I_{RRM}	Repetitive peak reverse current	$V_{RM}=V_{RRM}$ $V_{DM}=V_{DRM}$ $T_j=25^\circ\text{C}$ $T_j=100^\circ\text{C}$ $T_j=125^\circ\text{C}$		0.01	mA
I_{DRM}	Repetitive peak off-state current			0.2	
				0.5	
V_{TM}	On-state voltage	$I_{TM}=8\text{A}$		1.6	V
I_{GT}	Gate-trigger current	$V_D=12\text{V}$; $RL=33\ \Omega$	1	15	mA
V_{GT}	Gate-trigger voltage	$V_D=12\text{V}$; $RL=33\ \Omega$		1.5	V
I_H	Holding current	$I_{GT}=0.2\text{A}$		30	mA

NOTICE:

ISC reserves the rights to make changes of the content herein the datasheet at any time without notification. The information contained herein is presented only as a guide for the applications of our products.

ISC products are intended for usage in general electronic equipment. The products are not designed for use in equipment which require specialized quality and/or reliability, or in equipment which could have applications in hazardous environments, aerospace industry, or medical field. Please contact us if you intend our products to be used in these special applications.

ISC makes no warranty or guarantee regarding the suitability of its products for any particular purpose, nor does ISC assume any liability arising from the application or use of any products, and specifically disclaims any and all liability, including without limitation special, consequential or incidental damage.