



# SB2520CT thru SB25150CT

## SCHOTTKY BARRIER RECTIFIER

VOLTAGE - 20 TO 150 VOLTS CURRENT - 25 AMPERES



TO-220AB



Dimensions in inches and (millimeters)

### FEATURES

- Plastic Package has Underwriters Laboratory Flammability Classification 94-0 utilizing Flame Retardant Epoxy Molding Compound
- Exceeds environmental standards of MIL-S-19500/228
- Low power loss, high efficiency
- Low Forward Voltage, high Current Capability
- High surge Capability
- For use low Voltage, high frequency inverters, free wheeling, and polarity protection applications
- High temperature soldering : 260°C/10seconds at terminals
- Pb free product are available : 99% Sn above can meet RoHS
- environment substance directive request

### MECHANICAL DATA

Case : TO220AB Molded plastic  
 Terminals : Lead solderable per MIL-STD-202, Method 208  
 Polarity : As Marked on Body  
 Mounting Position : Any  
 Weight : 0.08ounces, 2.24gram

### MAXIMUM RATINGS AND ELECTRICAL CHARACTERISTICS

Ratings at 25°C ambient temperature unless otherwise specified  
 Single phase, half wave, 60Hz, resistive or inductive load  
 For capacitive load, derate current by 20%

PARAMETER	SB 2520CT	SB 2530CT	SB 2540CT	SB 2550CT	SB 2560CT	SB 2580CT	SB 25100CT	SB 25150CT	UNITS
Maximum Repetitive Peak Reverse Voltage	20	30	40	50	60	80	100	150	Volts
Maximum RMS Voltage	14	21	28	35	42	56	70	105	Volts
Maximum DC Blocking Voltage	20	30	40	50	60	80	100	150	Volts
Maximum Average Forward Rectified Current at Tc=90°C	25								Amps
Peak Forward Surge Current 8.3ms Single Half Sine-Wave Superimposed on Rated Load (JEDEC Method)	200							150	Amps
Maximum Forward Voltage at 12.5A per element	0.55		0.75		0.85		0.92		Volts
Maximum DC Reverse Current at Rated Tc=25°C DC Blocking Voltage Tc=100°C	0.5 100							0.1 7	mA
Typical Junction Resistance Note RθJA	100								°C / W
Operating and Storage Temperature Range Tj	-55 to +150								°C

NOTE:

1. Thermal Resistance Junction to Ambient

# SB2520CT thru SB25150CT

## SCHOTTKY BARRIER RECTIFIER

### RATINGS AND CHARACTERISTIC CURVES SB2520CT THRU SB25150CT




Fig.1-FORWARD CURRENT DERATING CURVE




Fig.2- TMAXIMUM NON - REPETITIVE SURGE CURRENT




Fig.3- TYPICAL REVERSE CHARACTERISTIC




Fig.4- TYPICAL INSTANTANEOUS FORWARD CHARACTERISTIC

### LEGAL STATEMENT

#### Copyright PanJit International, Inc 2006

The information presented in this document is believed to be accurate and reliable. The specifications and information herein are subject to change without notice. Pan Jit makes no warranty, representation or guarantee regarding the suitability of its products for any particular purpose. Pan Jit products are not authorized for use in life support devices or systems. Pan Jit does not convey any license under its patent rights or rights of others.