



Features

- Low Forward Voltage
- Epitaxial Construction with Oxide Passivation
- Guard Ring for Transient and ESD Protection
- Surge Overload Rating to 200A Peak
- Low Power Loss, High Efficiency
- Fast Switching
- For Use in Low Voltage, High Frequency Inverters, Free Wheeling, and Switching Power Supplies



Mechanical Data

- Case: D²PAK/TO-263, Molded Plastic
- Terminals: Plated Leads Solderable per MIL-STD-202, Method 208
- Polarity: See Diagram
- Weight: 1.7 grams (approx.)
- Mounting Position: Any
- Marking: Type Number
- **Lead Free: For RoHS / Lead Free Version, Add "-LF" Suffix to Part Number, See Page 4**



| D ² PAK/TO-263 | | |
|---------------------------|------|-------|
| Dim | Min | Max |
| A | 9.80 | 10.40 |
| B | 9.60 | 10.60 |
| C | 4.40 | 4.80 |
| D | 8.50 | 9.10 |
| E | — | 2.80 |
| G | 1.00 | 1.40 |
| H | — | 0.99 |
| J | 1.20 | 1.40 |
| K | 0.30 | 0.70 |
| P | 2.35 | 2.75 |
| All Dimensions in mm | | |

Maximum Ratings and Electrical Characteristics @T_A=25°C unless otherwise specified

Single Phase, half wave, 60Hz, resistive or inductive load. For capacitive load, derate current by 20%.

| Characteristic | Symbol | SB | SB | SB | SB | SB | SB | SB | SB | Unit |
|---|--|--------------|--------|--------------|--------|--------|--------------|--------|---------|------|
| | | 2520DC | 2530DC | 2540DC | 2545DC | 2550DC | 2560DC | 2580DC | 25100DC | |
| Peak Repetitive Reverse Voltage Working Peak Reverse Voltage DC Blocking Voltage | V _{RRM} V _{RWM} V _R | 20 | 30 | 40 | 45 | 50 | 60 | 80 | 100 | V |
| RMS Reverse Voltage | V _{R(RMS)} | 14 | 21 | 28 | 32 | 35 | 42 | 56 | 70 | V |
| Average Rectified Output Current @T _C = 100°C | I _O | 25 12.5 | | | | | | | | A |
| Non-Repetitive Peak Forward Surge Current 8.3ms Single Half Sine-Wave Superimposed on Rated Load (JEDEC Method) | I _{FSM} | 200 | | | | | | | | A |
| Forward Voltage per diode | V _{FM} | 0.62 0.57 | | 0.75 0.65 | | | 0.85 0.75 | | V | |
| Peak Reverse Current At Rated DC Blocking Voltage | I _{RM} | 1.0 20 | | | | | | | | mA |
| Typical Junction Capacitance (Note 1) | C _J | 750 | | | | 500 | | | | pF |
| Thermal Resistance Junction to Ambient (Note 2) Thermal Resistance Junction to Case (Note 2) | R _{JA} R _{JC} | 55 1.5 | | | | | | | | °C/W |
| Operating and Storage Temperature Range | T _J , T _{STG} | -55 to +150 | | | | | | | | °C |

Note: 1. Measured at 1.0 MHz and applied reverse voltage of 4.0V D.C.
2. Mounted on FR-4 PCB with minimum recommended pad layout per diode.




Fig. 1 Forward Current Derating Curve




Fig. 2 Typical Forward Characteristics




Fig. 3 Forward Surge Current Derating Curve




Fig. 4 Typical Reverse Characteristics




Fig. 5 Forward Power Dissipation






Fig. 6 Typical Junction Capacitance

MARKING INFORMATION




SB25xxDC = Device Number
 xx = 20, 30, 40, 45, 50, 60, 80 or 100
 Polarity = As Marked on Body

RECOMMENDED FOOTPRINT



PACKAGING INFORMATION

TAPE & REEL



| Reel Diameter (mm) | Quantity (PCS) | Inner Box Size L x W x H (mm) | Quantity (PCS) | Carton Size L x W x H (mm) | Quantity (PCS) | Approx. Gross Weight (KG) |
|--------------------|----------------|-------------------------------|----------------|----------------------------|----------------|---------------------------|
| 330 | 800 | 340 x 337 x 45 | 800 | 370 x 370 x 420 | 6,400 | 15.0 |

Note: 1. Paper reel, white or gray color.
 2. Components are packed in accordance with EIA standard 481-1 and 481-2.

ORDERING INFORMATION

| Product No. | Package Type | Shipping Quantity |
|--------------|--------------------|-------------------|
| SB2520DC-T3 | D ² PAK | 800/Tape & Reel |
| SB2530DC-T3 | D ² PAK | 800/Tape & Reel |
| SB2540DC-T3 | D ² PAK | 800/Tape & Reel |
| SB2545DC-T3 | D ² PAK | 800/Tape & Reel |
| SB2550DC-T3 | D ² PAK | 800/Tape & Reel |
| SB2560DC-T3 | D ² PAK | 800/Tape & Reel |
| SB2580DC-T3 | D ² PAK | 800/Tape & Reel |
| SB25100DC-T3 | D ² PAK | 800/Tape & Reel |

1. Shipping quantity given is for minimum packing quantity only. For minimum order quantity, please consult the Sales Department.
2. **To order RoHS / Lead Free version (with Lead Free finish), add "-LF" suffix to part number above. For example, SB2520DC-T3-LF.**

WON-TOP ELECTRONICS and  are registered trademarks of Won-Top Electronics Co., Ltd (WTE). WTE has checked all information carefully and believes it to be correct and accurate. However, WTE cannot assume any responsibility for inaccuracies. Furthermore, this information does not give the purchaser of semiconductor devices any license under patent rights to manufacturer. WTE reserves the right to change any or all information herein without further notice.

WARNING: DO NOT USE IN LIFE SUPPORT EQUIPMENT. WTE power semiconductor products are not authorized for use as critical components in life support devices or systems without the express written approval.

Won-Top Electronics Co., Ltd.

No. 44 Yu Kang North 3rd Road,

Chine Chen Dist., Kaohsiung 806, Taiwan

Phone: 886-7-822-5408 or 886-7-822-5410

Fax: 886-7-822-5417

Email: sales@wontop.com

Internet: <http://www.wontop.com>

We power your everyday.