



SCHOTTKY BARRIER RECTIFIERS	REVERSE VOLTAGE - 40 to 60 Volts FORWARD CURRENT - 40 Ampere																																																
<p>FEATURES</p> <ul style="list-style-type: none"> • Metal of silicon rectifier, majority carrier conducton • Guard ring for transient protection • Low power loss, high efficiency • High current capability, low VF • High surge capacity • Plastic package has UL flammability classification 94V-0 • For use in low voltage, high frequence inverters, free wheeling, and polarity protection applications <p>MECHANICAL DATA</p> <ul style="list-style-type: none"> • Case : TO-3P molded plastic • Polarity : As marked on the body • Weight : 0.2 ounces, 5.6 grams • Mounting position : Any 	<p>TO-247AB</p> <table border="1" style="margin-left: auto; margin-right: auto;"> <thead> <tr> <th>Dim.</th> <th>Min.</th> <th>Max.</th> </tr> </thead> <tbody> <tr><td>A</td><td>15.45</td><td>16.25</td></tr> <tr><td>B</td><td>20.30</td><td>21.75</td></tr> <tr><td>C</td><td>20.10</td><td>19.60</td></tr> <tr><td>D</td><td>6.50</td><td>Typ.</td></tr> <tr><td>E</td><td>3.70</td><td>4.38</td></tr> <tr><td>F</td><td>3.00</td><td>3.40</td></tr> <tr><td>G</td><td>1.80</td><td>2.20</td></tr> <tr><td>H</td><td>1.00</td><td>1.40</td></tr> <tr><td>I</td><td>5.45</td><td>Typ.</td></tr> <tr><td>J</td><td>4.85</td><td>5.15</td></tr> <tr><td>K</td><td>1.90</td><td>2.10</td></tr> <tr><td>L</td><td>3.50</td><td>Typ.</td></tr> <tr><td>M</td><td>3.20</td><td>Typ.</td></tr> <tr><td>N</td><td>2.20</td><td>2.60</td></tr> <tr><td>O</td><td>0.51</td><td>0.76</td></tr> </tbody> </table> <p style="font-size: small; text-align: center;">All Dimensions in millimeter</p>	Dim.	Min.	Max.	A	15.45	16.25	B	20.30	21.75	C	20.10	19.60	D	6.50	Typ.	E	3.70	4.38	F	3.00	3.40	G	1.80	2.20	H	1.00	1.40	I	5.45	Typ.	J	4.85	5.15	K	1.90	2.10	L	3.50	Typ.	M	3.20	Typ.	N	2.20	2.60	O	0.51	0.76
Dim.	Min.	Max.																																															
A	15.45	16.25																																															
B	20.30	21.75																																															
C	20.10	19.60																																															
D	6.50	Typ.																																															
E	3.70	4.38																																															
F	3.00	3.40																																															
G	1.80	2.20																																															
H	1.00	1.40																																															
I	5.45	Typ.																																															
J	4.85	5.15																																															
K	1.90	2.10																																															
L	3.50	Typ.																																															
M	3.20	Typ.																																															
N	2.20	2.60																																															
O	0.51	0.76																																															

MAXIMUM RATINGS AND ELECTRICAL CHARACTERISTICS

Ratings at 25°C ambient temperature unless otherwise specified.
 Single phase, half wave, 60Hz, resistive or inductive load.
 For capacitive load, derate current by 20%

CHARACTERISTICS	SYMBOL	SBL 4040PT	SBL 4045PT	SBL 4060PT	UNIT
Maximum Recurrent Peak Reverse Voltage	V_{RRM}	40	45	60	V
Maximum RMS Voltage	V_{RMS}	28	31.5	42	V
Maximum DC Blocking Voltage	V_{DC}	40	45	60	V
Maximum Average Forward Rectified Current @ $T_C=100^\circ C$	$I_{(AV)}$	40			A
Peak Forward Surge current 8.3ms single half sine-wave super imposed on rated load (JEDEC METHOD)	I_{FSM}	375			A
Maximum forward Voltage at 20A DC @ $T_J=25^\circ C$	V_F	0.58		0.70	V
Maximum DC Reverse Current at Rated DC Blocking Voltage @ $T_J=25^\circ C$ @ $T_J=100^\circ C$	I_R	10 100			mA
Typical Junction Capacitance per element (Note 1)	C_J	800			pF
Typical Thermal Resistance (Note 2)	$R_{\theta JC}$	1.4			$^\circ C/W$
Operating Temperature Range	T_J	-55 to +125			$^\circ C$
Storage Temperature Range	T_{STG}	-55 to +150			$^\circ C$

NOTES : 1. Measured at 1.0MHz and applied reverse voltage of 4.0V DC. REV.0, 01.-Oct-2013
 2. Thermal Resistance Junction to Case.

RATING AND CHARACTERISTIC CURVES
SBL4040PT thru SBL4060PT

