

Super Barrier Rectifier™

Using state-of-the-art SBR IC process technology,
the following features are made possible in a single device:

Major ratings and characteristics

Characteristics	Values	Units
$I_{F(AV)}$ Rectangular Waveform	60	A
V_{RRM}	150	V
$V_F @ 30A, T_j = 125^\circ C$	0.73	V, typ
T_j (operating/storage)	-65 to 175	$^\circ C$


Device optimized for low forward voltage drop to maximize efficiency in Power Supply applications

MECHANICAL:

* Molded Plastic TO-3P package

ELECTRICAL:

- * Low Forward Voltage Drop
- * Reliable High Temperature Operation
- * Super Barrier Design
- * Softest, fast switching capability
- * 175 $^\circ C$ Operating Junction Temperature



Maximum Ratings and Electrical Characteristics

(at 25 $^\circ C$ unless otherwise specified)

	SYMBOL			UNITS
DC Blocking Voltage	V_{RM}	150		Volts
Working Peak Reverse Voltage	V_{RWM}			
Peak Repetitive Reverse Voltage	V_{RRM}			
Average Rectified Forward Current (Rated V_R -20Khz Square Wave) - 50% duty cycle	I_O	60		Amps
Peak Forward Surge Current - 1/2 60hz	I_{FSM}	350		Amps
Peak Repetitive Reverse Surge Current (2uS-1Khz)	I_{RRM}	3		Amps
Instantaneous Forward Voltage (per leg) $I_F = 30A; T_j = 25^\circ C$ $I_F = 30A; T_j = 125^\circ C$	V_F	Typ --- ---	Max 0.93 0.77	Volts
Maximum Instantaneous Reverse Current at Rated V_{RM} $T_j = 25^\circ C$ $T_j = 125^\circ C$	I_R^*	Typ --- ---	Max 100 10	μA mA
Maximum Rate of Voltage Change (at Rated V_R)	dv/dt	10,000		V/ μS
Maximum Thermal Resistance JC (per leg)	$R_{\theta_{JC}}$	2		$^\circ C/W$
Operating and Storage Junction Temperature	T_j	-65 to +175		$^\circ C$

* Pulse width < 300 μS , Duty cycle < 2%




Figure 1: Typical Reverse Current (per leg)




Figure 2: Typical Forward Voltage (per leg)




Figure 3: Current Derating, Case (per leg)

APD SEMICONDUCTOR reserves the right to make changes without further notice to any products herein. APD SEMICONDUCTOR makes no warranty, representation or guarantee regarding the suitability of its products for any particular purpose, nor does APD SEMICONDUCTOR assume any liability arising out of the application or use of any product or circuit, and specifically disclaims any and all liability, including without limitation special, consequential or incidental damages. "Typical" parameters which may be provided in APD SEMICONDUCTOR data sheets and/or specifications can and do vary in different applications and actual performance may vary over time. All operating parameters, including "Typicals" must be validated for each customer application by customer's technical experts. APD SEMICONDUCTOR does not convey any license under its patent rights nor the rights of others. APD SEMICONDUCTOR products are not designed, intended, or authorized for use as components in systems intended for surgical implant into the body, or other applications intended to support or sustain life, or for any other application in which the failure of the APD SEMICONDUCTOR product could create a situation where personal injury or death may occur. Should Buyer purchase or use APD SEMICONDUCTOR products for any such unintended or unauthorized application, Buyer shall indemnify and hold APD SEMICONDUCTOR and its officers, employees, subsidiaries, affiliates, and distributors harmless against all claims, costs, damages, and expenses, and reasonable attorney fees arising out of, directly or indirectly, any claim of personal injury or death associated with such unintended or unauthorized use, even if such claim alleges that APD SEMICONDUCTOR was negligent regarding the design or manufacture of the part.