



## Silicon carbide Power MOSFET 650 V, 58 mΩ typ., 30 A in a TO-LL package



### Product status link

[SCT055TO65G3](#)

### Product summary

<b>Order code</b>	SCT055TO65G3
<b>Marking</b>	055TO65G3
<b>Package</b>	TO-LL
<b>Packing</b>	Tape and reel

## Features

Order code	V <sub>DS</sub>	R <sub>DS(on)</sub> typ.	I <sub>D</sub>
SCT055TO65G3	650 V	58 mΩ	30 A

- Very fast and robust intrinsic body diode
- Very low R<sub>DS(on)</sub> over the entire temperature range
- High speed switching performances
- Source sensing pin for increased efficiency

## Applications

- Switching mode power supply
- DC-DC converters

## Description

This silicon carbide Power MOSFET device has been developed using ST's advanced and innovative 3<sup>rd</sup> generation SiC MOSFET technology. The device features a very low R<sub>DS(on)</sub> over the entire temperature range combined with low capacitances and very high switching operations, which improve application performance in frequency, energy efficiency, system size and weight reduction.

# 1 Electrical ratings

**Table 1. Absolute maximum ratings**

Symbol	Parameter	Value	Unit
$V_{DS}$	Drain-source voltage	650	V
$V_{GS}$	Gate-source voltage	-10 to 22	V
	Gate-source voltage (recommended operating values)	-5 to 18	
	Gate-source transient voltage, $t_p < 1 \mu s$ , $t \leq 10$ hours over lifetime	-11 to 25	
$I_D^{(1)}$	Drain current (continuous) at $T_C = 25 \text{ }^\circ\text{C}$	30	A
	Drain current (continuous) at $T_C = 100 \text{ }^\circ\text{C}$	30	
$I_{DM}^{(2)}$	Drain current (pulsed)	147	A
$P_{TOT}$	Total power dissipation at $T_C = 25 \text{ }^\circ\text{C}$	234	W
$T_{stg}$	Storage temperature range	-55 to 175	$^\circ\text{C}$
$T_J$	Operating junction temperature range		$^\circ\text{C}$

1. Limited by bonding wires.
2. Pulse width is limited by safe operating area.

**Table 2. Thermal data**

Symbol	Parameter	Value	Unit
$R_{thJC}$	Thermal resistance, junction-to-case	0.64	$^\circ\text{C/W}$
$R_{thJA}$	Thermal resistance, junction-to-ambient	50	$^\circ\text{C/W}$

## 2 Electrical characteristics

$T_C = 25\text{ °C}$  unless otherwise specified.

**Table 3. On/off states**

Symbol	Parameter	Test conditions	Min.	Typ.	Max.	Unit
$V_{(BR)DSS}$	Drain-source breakdown voltage	$V_{GS} = 0\text{ V}, I_D = 1\text{ mA}$	650			V
$I_{DSS}$	Zero gate voltage drain current	$V_{GS} = 0\text{ V}, V_{DS} = 650\text{ V}$			10	$\mu\text{A}$
$I_{GSS}$	Gate-body leakage current	$V_{DS} = 0\text{ V}, V_{GS} = -10\text{ to }22\text{ V}$			$\pm 100$	nA
$V_{GS(th)}$	Gate threshold voltage	$V_{DS} = V_{GS}, I_D = 1\text{ mA}$	1.8	3.0	4.2	V
$R_{DS(on)}$	Static drain-source on-resistance	$V_{GS} = 15\text{ V}, I_D = 15\text{ A}$		67		m $\Omega$
		$V_{GS} = 18\text{ V}, I_D = 15\text{ A}$		58	72	
		$V_{GS} = 18\text{ V}, I_D = 15\text{ A}, T_J = 175\text{ °C}$		75		

**Table 4. Dynamic**

Symbol	Parameter	Test conditions	Min.	Typ.	Max.	Unit
$C_{iss}$	Input capacitance	$V_{DS} = 400\text{ V}, f = 1\text{ MHz}, V_{GS} = 0\text{ V}$	-	687	-	pF
$C_{oss}$	Output capacitance		-	71	-	pF
$C_{rss}$	Reverse transfer capacitance		-	11	-	pF
$Q_g$	Total gate charge	$V_{DD} = 400\text{ V}, V_{GS} = -5\text{ to }18\text{ V}, I_D = 15\text{ A}$	-	31	-	nC
$Q_{gs}$	Gate-source charge		-	9.5	-	nC
$Q_{gd}$	Gate-drain charge		-	8.1	-	nC
$R_g$	Gate input resistance	$f = 1\text{ MHz}, I_D = 0\text{ A}$	-	1.6	-	$\Omega$

**Table 5. Switching energy (inductive load)**

Symbol	Parameter	Test conditions	Min.	Typ.	Max.	Unit
$E_{on}$	Turn-on switching energy	$V_{DD} = 400\text{ V}, I_D = 15\text{ A},$	-	42	-	$\mu\text{J}$
$E_{off}$	Turn-off switching energy	$R_G = 8.2\ \Omega, V_{GS} = -5\text{ V to }18\text{ V}$	-	35.6	-	$\mu\text{J}$

**Table 6. Switching times**

Symbol	Parameter	Test conditions	Min.	Typ.	Max.	Unit
$t_{d(on)}$	Turn-on delay time	$V_{DD} = 400\text{ V}, I_D = 15\text{ A},$ $R_G = 8.2\ \Omega, V_{GS} = -5\text{ to }18\text{ V}$	-	9.2	-	ns
$t_r$	Rise time		-	5	-	ns
$t_{d(off)}$	Turn-off delay time		-	19.4	-	ns
$t_f$	Fall time		-	13.6	-	ns

**Table 7. Reverse SiC diode characteristics**

Symbol	Parameter	Test conditions	Min.	Typ.	Max.	Unit
$I_{SD}^{(1)}$	Continuous diode forward current	$T_C = 25\text{ }^\circ\text{C}$	-		30	A
		$T_C = 100\text{ }^\circ\text{C}$	-		30	
$V_{SD}$	Diode forward voltage	$I_{SD} = 15\text{ A}, V_{GS} = 0\text{ V}$	-	2.75		V
$t_{rr}$	Reverse recovery time	$I_{SD} = 15\text{ A}, 1\text{ kA}/\mu\text{s}, V_{DD} = 400\text{ V}$	-	13		ns
$Q_{rr}$	Reverse recovery charge		-	57		nC
$I_{RRM}$	Reverse recovery current		-	7.6		A

1. Limited by bonding wires.

## 2.1 Electrical characteristics (curves)

Figure 1. Safe operating area




Figure 2. Maximum transient thermal impedance




Figure 3. Typical output characteristics ( $T_J = 25\text{ °C}$ )




Figure 4. Typical output characteristics ( $T_J = 175\text{ °C}$ )




Figure 5. Typical transfer characteristics







Figure 6. Total power dissipation




**Figure 7. Maximum continuous drain current vs. case temperature**




**Figure 8. Typical gate charge characteristics**




**Figure 9. Typical capacitance characteristics**




**Figure 10. Normalized breakdown voltage vs temperature**




**Figure 11. Normalized gate threshold vs temperature**




**Figure 12. Normalized on-resistance vs temperature**




**Figure 13. Typical reverse conduction characteristics**  
( $T_J = 25\text{ }^\circ\text{C}$ )




**Figure 14. Typical reverse conduction characteristics**  
( $T_J = 175\text{ }^\circ\text{C}$ )




**Figure 15. Typical switching energy vs drain current**



**Figure 16. Typical switching energy vs supply voltage**



**Figure 17. Typical switching energy vs gate resistance**




### 3 Package information

To meet environmental requirements, ST offers these devices in different grades of **ECOPACK** packages, depending on their level of environmental compliance. ECOPACK specifications, grade definitions, and product status are available at: [www.st.com](http://www.st.com). ECOPACK is an ST trademark.

#### 3.1 TO-LL package information

**Figure 18. TO-LL package outline**




DM00276569\_SiC\_Rev\_7

**Table 8. TO-LL package mechanical data**

Dim.	mm		
	Min.	Typ.	Max.
A	2.20	2.30	2.40
b	0.60	0.80	0.90
b1	9.70	9.80	9.90
b2	0.20		0.50
c	0.40	0.50	0.60
D	10.28	10.43	10.58
D1	3.15	3.30	3.45
E	9.70	9.90	10.10
E1	9.31	9.46	9.61
E2	8.35	8.50	8.65
e	1.10	1.20	1.30
H	11.48	11.73	11.88
H1	7.00	7.15	7.30
H2	3.34	3.59	3.84
H3	3.11	3.26	3.41
K	4.03	4.18	4.33
K1	2.70		
L	1.45	1.60	1.75
L1	0.55	0.70	0.85
L2	0.45	0.60	0.75
L3	1.00	1.15	1.30
L4	0.05		0.40

Figure 19. TO-LL recommended footprint (dimensions are in mm)



DM00276569\_7\_SIC\_FP

### 3.2 TO-LL packing information

Figure 20. Carrier tape outline and dimensions






Figure 21. Reel outline and dimensions



**Figure 22. TO-LL orientation in tape pocket**



## Revision history

**Table 9. Document revision history**

Date	Revision	Changes
29-Oct-2024	1	First release.

---

## Contents

<b>1</b>	<b>Electrical ratings</b> .....	<b>2</b>
<b>2</b>	<b>Electrical characteristics</b> .....	<b>3</b>
<b>2.1</b>	Electrical characteristics (curves) .....	<b>5</b>
<b>3</b>	<b>Package information</b> .....	<b>8</b>
<b>3.1</b>	TO-LL package information .....	<b>8</b>
<b>3.2</b>	TO-LL packing information .....	<b>11</b>
	<b>Revision history</b> .....	<b>13</b>

**IMPORTANT NOTICE – READ CAREFULLY**

STMicroelectronics NV and its subsidiaries (“ST”) reserve the right to make changes, corrections, enhancements, modifications, and improvements to ST products and/or to this document at any time without notice. Purchasers should obtain the latest relevant information on ST products before placing orders. ST products are sold pursuant to ST’s terms and conditions of sale in place at the time of order acknowledgment.

Purchasers are solely responsible for the choice, selection, and use of ST products and ST assumes no liability for application assistance or the design of purchasers’ products.

No license, express or implied, to any intellectual property right is granted by ST herein.

Resale of ST products with provisions different from the information set forth herein shall void any warranty granted by ST for such product.

ST and the ST logo are trademarks of ST. For additional information about ST trademarks, refer to [www.st.com/trademarks](http://www.st.com/trademarks). All other product or service names are the property of their respective owners.

Information in this document supersedes and replaces information previously supplied in any prior versions of this document.

© 2024 STMicroelectronics – All rights reserved