
DISCRETE POWER DIODES and THYRISTORS
DATA BOOK

STANDARD RECOVERY DIODES

Hockey Puk Version


Features

- Wide current range
- High voltage ratings up to 2500V
- High surge current capabilities
- Diffused junction
- Hockey Puk version
- Case style DO-200AC (K-PUK)

3000A

Typical Applications

- Converters
- Power supplies
- Machine tool controls
- High power drives
- Medium traction applications



case style DO-200AC (K-PUK)

Major Ratings and Characteristics

| Parameters | SD2500C..K | Units |
|------------------|--------------|-------------------|
| $I_{F(AV)}$ | 3000 | A |
| @ T_{hs} | 55 | °C |
| $I_{F(RMS)}$ | 5000 | A |
| @ T_{hs} | 25 | °C |
| I_{FSM} @ 50Hz | 31000 | A |
| @ 60Hz | 32460 | A |
| I^2t @ 50Hz | 4810 | KA ² s |
| @ 60Hz | 4390 | KA ² s |
| V_{RRM} range | 1200 to 2500 | V |
| T_J | - 40 to 180 | °C |

ELECTRICAL SPECIFICATIONS

Voltage Ratings

| Type number | Voltage Code | V_{RRM} , maximum repetitive peak reverse voltage V | V_{RSM} , maximum non-repetitive peak rev. voltage V | I_{RRM} max. @ $T_J = 180^\circ\text{C}$ mA |
|-------------|--------------|--|---|---|
| SD2500C..K | 12 | 1200 | 1300 | 75 |
| | 16 | 1600 | 1700 | |
| | 20 | 2000 | 2100 | |
| | 25 | 2500 | 2600 | |

Forward Conduction

| Parameter | SD2500C..K | Units | Conditions |
|--|-------------|--------------------|--|
| $I_{F(AV)}$ Max. average forward current @ Heatsink temperature | 3000 (1550) | A | 180° conduction, half sine wave |
| | 55 (85) | °C | Double side (single side) cooled |
| $I_{F(RMS)}$ Max. RMS forward current | 5000 | A | @ 25°C heatsink temperature double side cooled |
| I_{FSM} Max. peak, one-cycle forward, non-repetitive surge current | 31000 | A | t = 10ms No voltage |
| | 32460 | | t = 8.3ms reapplied |
| | 26050 | | t = 10ms 100% V_{RRM} |
| | 27300 | | t = 8.3ms reapplied |
| I^2t Maximum I^2t for fusing | 4810 | KA ² s | t = 10ms No voltage |
| | 4390 | | t = 8.3ms reapplied |
| | 3400 | | t = 10ms 100% V_{RRM} |
| | 3100 | | t = 8.3ms reapplied |
| $I^2\sqrt{t}$ Maximum $I^2\sqrt{t}$ for fusing | 48100 | KA ² /s | t = 0.1 to 10ms, no voltage reapplied |
| $V_{F(TO)1}$ Low level value of threshold voltage | 0.76 | V | $(16.7\% \times \pi \times I_{F(AV)} < I < \pi \times I_{F(AV)})$, $T_J = T_J$ max. |
| $V_{F(TO)2}$ High level value of threshold voltage | 0.97 | | $(I > \pi \times I_{F(AV)})$, $T_J = T_J$ max. |
| r_{f1} Low level value of forward slope resistance | 0.16 | mΩ | $(16.7\% \times \pi \times I_{F(AV)} < I < \pi \times I_{F(AV)})$, $T_J = T_J$ max. |
| r_{f2} High level value of forward slope resistance | 0.13 | | $(I > \pi \times I_{F(AV)})$, $T_J = T_J$ max. |
| V_{FM} Max. forward voltage drop | 1.41 | V | $I_{pk} = 4000\text{A}$, $T_J = T_J$ max, $t_p = 10\text{ms}$ sinusoidal wave |




Fig. 3 - Current Ratings Characteristics




Fig. 4 - Current Ratings Characteristics




Fig. 5 - Forward Power Loss Characteristics




Fig. 6 - Forward Power Loss Characteristics




Fig. 7 - Maximum Non-Repetitive Surge Current




Fig. 8 - Maximum Non-Repetitive Surge Current



Fig. 9 - Forward Voltage Drop Characteristics




Fig. 10 - Thermal Impedance Z_{thJC} Characteristics

Thermal and Mechanical Specifications

| Parameter | SD2500C..K | Units | Conditions |
|--|-----------------|-----------|--|
| T_J Max. junction operating temperature range | -40 to 180 | °C | |
| T_{stg} Max. storage temperature range | -55 to 200 | | |
| R_{thJ-hs} Max. thermal resistance, junction to heatsink | 0.042 0.020 | K/W | DC operation single side cooled DC operation double side cooled |
| F Mounting force, $\pm 10\%$ | 22250 (2250) | N (Kg) | |
| wt Approximate weight | 425 | g | |
| Case style | DO-200AC(K-PUK) | | See Outline Table |


 ΔR_{thJ-hs} Conduction

(The following table shows the increment of thermal resistance R_{thJ-hs} when devices operate at different conduction angles than DC)

| Conduction angle | Sinusoidal conduction | | Rectangular conduction | | Units | Conditions |
|------------------|-----------------------|-------------|------------------------|-------------|-------|--------------------------|
| | Single Side | Double Side | Single Side | Double Side | | |
| 180° | 0.002 | 0.002 | 0.001 | 0.001 | K/W | $T_J = T_J \text{ max.}$ |
| 120° | 0.002 | 0.002 | 0.002 | 0.002 | | |
| 90° | 0.003 | 0.003 | 0.003 | 0.003 | | |
| 60° | 0.004 | 0.004 | 0.004 | 0.004 | | |
| 30° | 0.007 | 0.007 | 0.007 | 0.007 | | |

Ordering Information Table

Device Code



- 1** - Diode
- 2** - Essential part number
- 3** - 0 = Standard recovery
- 4** - C = Ceramic Puk
- 5** - Voltage code: code x 100 = V_{RRM} (see Voltage Ratings Table)
- 6** - K = Puk Case DO-200AC (K-PUK)

Outline Table





Fig. 1 - Current Ratings Characteristics




Fig. 2 - Current Ratings Characteristics