


Schottky Barrier Rectifier

General Description

The SDB1150 surface mounted Schottky rectifier has been designed for applications requiring low forward drop and very small foot prints on PC boards. Typical applications are in disk drives, switching power supplies, converters, free-wheeling diodes, battery charging, and reverse battery protection.



SOD-106

Features and Benefits

- Low forward drop voltage and low reverse leakage current
- Low power rectified
- “Green” device and RoHS compliant device
- Available in full lead (Pb)-free device

Applications

- Free-wheeling applications
- Switching mode power supplies applications

Ordering Information

Part Number	Marking Code	Package	Packaging
SDB1150	1A15	SOD-106	Tape & Reel

Marking Information



1A15 = Specific Device Code



YWW = Year & Week Code Marking

-. Y = Year Code

-. WW = Week Code

 = Color band denote cathode

Pinning Information

Pin	Description	Simplified Outline	Graphic Symbol
1	Cathode		
2	Anode		

Absolute Maximum Ratings ($T_{amb}=25^{\circ}\text{C}$, Unless otherwise specified)

Characteristic	Symbol	Ratings	Unit
Maximum repetitive reverse voltage Maximum working peak reverse voltage Maximum DC blocking voltage	V_{RRM} V_{RWM} V_R	150	V
Maximum average forward rectified current	$I_{F(AV)}$	1	A
Peak forward surge current 8.3ms single half sine-wave superimposed on rated load per diode	I_{FSM}	75	A
Maximum operating junction temperature	T_J	150	$^{\circ}\text{C}$
Storage temperature range	T_{stg}	-55 ~ 150	

Thermal Characteristics

Characteristic		Symbol	Value	Unit
Maximum thermal resistance	Junction to ambient	$R_{th(j-a)}^{3)}$	145	$^{\circ}\text{C/W}$

Electrical Characteristics ($T_{amb}=25^{\circ}\text{C}$, Unless otherwise specified)

Characteristic	Symbol	Test Condition		Min.	Typ.	Max.	Unit
Forward drop voltage	$V_F^{1)}$	$I_F=1\text{A}$		-	0.72	0.83	V
Reverse leakage current	$I_R^{2)}$	$V_R=150\text{V}$	$T_J=25^{\circ}\text{C}$	-	-	0.5	mA
			$T_J=125^{\circ}\text{C}$	-	-	5	mA
Total capacitance	C_T	$V_R=5\text{V}, f=1\text{MHz}$		-	35	-	pF

¹⁾ Pulse test: $t_P \leq 380\mu\text{s}$, Duty cycle $\leq 2\%$

²⁾ Pulse test: $t_P \leq 5\text{ms}$, Duty cycle $\leq 2\%$

³⁾ Device mounted on glass epoxy PCB (recommanderable minimum solder land)

Rating and Characteristic Curves

Fig. 1) Typical Forward Characteristic




Fig. 2) Typical Reverse Characteristic




Fig. 3) Total Capacitance vs. Reverse Voltage






Fig. 4) Average Forward Power Dissipation vs. Average Forward Current




Package Outline Dimensions



SYMBOL	MILLIMETERS			NOTE
	MINIMUM	NOMINAL	MAXIMUM	
A	1.25	1.30	1.35	
A1	0.00	—	0.10	
A2	1.05	1.10	1.15	
b	1.35	1.42	1.49	
c	0.17	0.22	0.27	
D	2.50	2.60	2.70	
E	4.60	4.80	5.00	
E1	3.90	4.00	4.10	
L	0.79	0.94	1.09	
L1	0.30	0.40	0.50	
Θ	4°	—	10°	

※ Recommend PCB solder land (Unit: mm)



The AUK Corp. products are intended for the use as components in general electronic equipment (Office and communication equipment, measuring equipment, home appliance, etc.).

Please make sure that you consult with us before you use these AUK Corp. products in equipments which require high quality and / or reliability, and in equipments which could have major impact to the welfare of human life(atomic energy control, airplane, spaceship, transportation, combustion control, all types of safety device, etc.). AUK Corp. cannot accept liability to any damage which may occur in case these AUK Corp. products were used in the mentioned equipments without prior consultation with AUK Corp..

Specifications mentioned in this publication are subject to change without notice.