

## Dual Common-Cathode Schottky Rectifier

### General Description


The SDB20D200D2 has two schottky barriers arranged in a common cathode configuration and is ideally suited for a full wave output rectifier in low switching power supplies and DC to DC converters where small size and high reliability are required.

### Features and Benefits

- Low forward drop voltage and low leakage current
- Low power loss and high efficiency
- Dual common-cathode rectifier construction
- “Green” device and RoHS compliant device

### Applications

- Switching power supply
- Output rectification
- High frequency switching
- DC/DC Converter system


**D2-PAK**

Product Characteristics	
$I_{F(AV)}$	2 X 10A
$V_{RRM}$	200V
$V_{FM}$ at 125°C	0.88V
$I_{FSM}$	120A

### Ordering Information


Part Number	Marking Code	Package	Packaging
SDB20D200D2	SDB20D200D2	D2-PAK	Tape & Reel

### Marking Information



**AUK** = Manufacture Logo  
**Δ** = Control Code of Manufacture  
**YMDD** = Date Code Marking  
 -. **Y** = Year Code  
 -. **M** = Monthly Code  
 -. **DD** = Daily Code  
**SDB20D200D2** = Specific Device Code

### Pinning Information

Pin	Description	Simplified Outline	Graphic Symbol
1	Anode		
2, 4	Common-Cathode		
3	Anode		

# SDB20D200D2

## Absolute Maximum Ratings (Limiting values at 25°C, unless otherwise specified)

Characteristic		Symbol	Ratings	Unit
Maximum repetitive reverse voltage Maximum working peak reverse voltage Maximum DC blocking voltage		$V_{RRM}$ $V_{RWM}$ $V_R$	200	V
Maximum average forward rectified current	per diode	$I_{F(AV)}$	10	A
	total device		20	
Peak forward surge current 8.3ms single half sine-wave superimposed on rated load per diode		$I_{FSM}$	120	A
Storage temperature range		$T_{stg}$	-45 to +150	°C
Maximum operating junction temperature		$T_J$	150	°C

## Thermal Characteristics

Characteristic		Symbol	Ratings	Unit
Thermal resistance, junction to case	per diode	$R_{th(j-c)}$	4.0	°C/W
	total device		3.6	

## Electrical Characteristics

Characteristic	Symbol	Test Condition	Min.	Typ.	Max.	Unit	
Peak forward voltage drop	$V_{FM}^{(1)}$	$I_{FM} = 10A$	$T_j = 25^\circ C$	-	-	0.95	V
			$T_j = 125^\circ C$	-	-	0.88	V
Reverse leakage current	$I_{RM}^{(1)}$	$V_R = V_{RRM}$	$T_j = 25^\circ C$	-	-	20	uA
			$T_j = 125^\circ C$	-	-	10	mA
Junction capacitance	$C_j$	$V_R = 10V_{DC}, f = 1MHz$	-	100	-	pF	

<sup>1)</sup> Pulse test:  $t_p \leq 380\mu s$ , Duty cycle  $\leq 2\%$

<sup>2)</sup> Pulse test:  $t_p \leq 5ms$ , Duty cycle  $\leq 2\%$

## Rating and Characteristic Curves

Fig. 1) Typical Forward Characteristics (Per Diode)




Fig. 2) Typical Reverse Characteristics (Per Diode)




Fig. 3) Maximum Forward Derivative Curve




Fig. 4) Forward Power Dissipation (Per Diode)




Fig. 5) Maximum Non-Repetitive Peak Forward Surge Current (Per Diode)






Fig. 6) Typical Junction Capacitance (Per Diode)




## Package Outline Dimensions



SYMBOL	MILLIMETERS			NOTE
	MINIMUM	NOMINAL	MAXIMUM	
A	4.35	4.50	4.65	
A1	—	—	0.15	
A2	2.20	2.40	2.60	
b	0.70	0.80	0.90	
b1	1.17	1.27	1.37	
c	0.40	0.50	0.60	
c1	0.40	0.50	0.60	
D	9.80	10.00	10.20	
D1	6.40	6.60	6.80	
E	15.00	15.40	15.80	
E1	9.05	9.20	9.35	
E2	1.00	1.20	1.40	
E3	2.50	2.70	2.90	
e	2.34	2.54	2.74	
e1	4.88	5.08	5.28	
L	4.60	5.00	5.40	
L1	1.40	1.45	1.50	
L2	2.50	—	—	

※ Recommend PCB solder land (Unit : mm)



**The AUK Corp. products are intended for the use as components in general electronic equipment (Office and communication equipment, measuring equipment, home appliance, etc.).**

**Please make sure that you consult with us before you use these AUK Corp. products in equipments which require high quality and / or reliability, and in equipments which could have major impact to the welfare of human life(atomic energy control, airplane, spaceship, transportation, combustion control, all types of safety device, etc.). AUK Corp. cannot accept liability to any damage which may occur in case these AUK Corp. products were used in the mentioned equipments without prior consultation with AUK Corp..**

**Specifications mentioned in this publication are subject to change without notice.**