

## General Description

The SDC266 is an integrated circuit which includes Hall sensor and output drive circuits. It's widely used in 2-phase brushless DC motor and fan. It's composed of power reverse protection circuit, high stable voltage regulator, Hall voltage generator, a differential amplifier, Schmitt trigger and open collector output (DO, DOB).

In the case of power supply reverse connecting, the internal protection diode can protect IC but not protect coil, a protection diode can be added if necessary.

## Features

- Wide operating voltage range: 3.5V~24V
- 250mA(AVG) output sink current
- Building-in protection diode
- Operating temperature range: -20°C~85°C
- Package: TO-94

## Applications

- Brushless DC motor
- Brushless DC fan
- Revolution counting
- Speed measurement




Figure 1. Package Type


**Pin Configuration**


Figure 2. Pin Configuration

| Pin Number | Pin Name | Function           |
|------------|----------|--------------------|
| 1          | VCC      | Supply voltage pin |
| 2          | DO       | Output 2 pin       |
| 3          | DOB      | Output 3 pin       |
| 4          | GND      | Ground pin         |

Table 1. Pin Description



**Functional Block Diagram**


Figure 3. Functional Block Diagram

**Ordering Information**


| Package | Temperature Range | Part Number  |              | Marking ID |              | Packing Type |
|---------|-------------------|--------------|--------------|------------|--------------|--------------|
|         |                   | Pb-free      | Halogen-free | Pb-free    | Halogen-free |              |
| TO-94   | -20°C~85°C        | SDC266AZ4-E1 | SDC266AZ4-G1 | 266        | 266G         | Bulk         |
|         |                   | SDC266BZ4-E1 | SDC266BZ4-G1 | 266        | 266G         | Bulk         |
|         |                   | SDC266CZ4-E1 | SDC266CZ4-G1 | 266        | 266G         | Bulk         |
|         |                   | SDC266DZ4-E1 | SDC266DZ4-G1 | 266        | 266G         | Bulk         |

**Absolute Maximum Ratings** (Note: Stresses greater than those listed under absolute maximum ratings may cause permanent damage to the device.)

| Parameter                                   | Symbol     | Value     | Units |
|---|------------|-----------|-------|
| Supply Voltage                              | $V_{CC}$   | 26.5      | V     |
| Output Voltage                              | $V_{OUT}$  | 26.5      | V     |
| Reverse voltage                             | $V_{RCC}$  | -20       | V     |
| Magnetic flux density                       | B          | unlimited | GS    |
| Output current                              | Continuous | 250       | mA    |
|   | Hold       | 400       |       |
|   | Peak       | 700       |       |
| Storage temperature range                   | $T_S$      | -65~150   | °C    |
| Package power dissipation                   | $P_D$      | 550       | mW    |
| ESD, HBM model per Mil-Std-883, Method 3015 | HBM        | 4000      | V     |
| ESD, MM model per JEDEC EIA/JESD22-A115     | MM         | 400       | V     |
| Latch-up test per JEDEC 78                  | -          | 200       | mA    |
| Maximum junction temperature                | $T_J$      | 150       | °C    |

Table 2. Absolute Maximum Ratings

**Recommended Operating Conditions**

| Parameter             | Symbol   | Min | Max | Unit |
|-----------------------|----------|-----|-----|------|
| Power supply          | $V_{CC}$ | 3.5 | 24  | V    |
| Operation temperature | $T_a$    | -20 | 85  | °C   |

Table 3. Recommended Operating Conditions

**Electrical Characteristics** ( $T_a=25^\circ\text{C}$ ,  $V_{CC}=12\text{V}$ , unless otherwise specified)

| Parameter                 | Symbol     | Conditions                          | Min | Typ | Max | Unit |
|---------------------------|------------|-------------------------------------|-----|-----|-----|------|
| Supply voltage            | $V_{CC}$   | -                                   | 3.5 | -   | 24  | V    |
| Output zener breakdown    | $V_Z$      | -                                   | -   | 46  | -   | V    |
| Output saturation voltage | $V_{SAT}$  | $I_O=300\text{mA}$                  | -   | 0.3 | 0.6 | V    |
| Output leakage current    | $I_{CEX}$  | $V_{CC}=V_{CE}$                     | -   | 0.1 | 10  | uA   |
| Supply current            | $I_{CC}$   | $V_{CC}=20\text{V}$ , output open   | -   | 12  | 16  | mA   |
| Output rise time          | $t_r$      | $R_L=820\Omega$ , $C_L=20\text{pF}$ | -   | 3.0 | 10  | us   |
| Output falling time       | $t_f$      | $R_L=820\Omega$ , $C_L=20\text{pF}$ | -   | 0.3 | 1.5 | us   |
| Switch time differential  | $\Delta t$ | $R_L=820\Omega$ , $C_L=20\text{pF}$ | -   | 3.0 | 10  | us   |

Table 4. Electrical Characteristics


**Magnetic Characteristics** ( $T_a=25^\circ\text{C}$ ,  $V_{CC}=24\text{V}$ , unless otherwise specified)


Figure 4. Magnetic Characteristics

**Grade A**

| Parameter     | Symbol   | Min | Max | Unit |
|---------------|----------|-----|-----|------|
| Operate point | $B_{OP}$ | 10  | 50  | GS   |
| Release point | $B_{RP}$ | -50 | -10 | GS   |

**Grade B**

| Parameter     | Symbol   | Min | Max | Unit |
|---------------|----------|-----|-----|------|
| Operate point | $B_{OP}$ | 5   | 70  | GS   |
| Release point | $B_{RP}$ | -70 | -5  | GS   |

**Grade C**

| Parameter     | Symbol   | Min | Max | Unit |
|---------------|----------|-----|-----|------|
| Operate point | $B_{OP}$ | -   | 90  | GS   |
| Release point | $B_{RP}$ | -90 | -   | GS   |

**Grade D**

| Parameter     | Symbol   | Min  | Max | Unit |
|---------------|----------|------|-----|------|
| Operate point | $B_{OP}$ | -    | 125 | GS   |
| Release point | $B_{RP}$ | -125 | -   | GS   |

**Typical Performance Characteristics**




Figure 5. Magnetic Characteristics




Figure 5. Typical Magnetic Switch Point vs. Supply Voltage

**Typical Application**





Figure 6. Typical Application

**Package Dimension**
**TO-94**


| Symbol | Dimensions In Millimeters |        | Dimensions In Inches |       |
|--------|---------------------------|--------|----------------------|-------|
|        | Min                       | Max    | Min                  | Max   |
| A      | 1.400                     | 1.800  | 0.055                | 0.071 |
| A1     | 0.700                     | 0.900  | 0.028                | 0.035 |
| b1     | 0.380                     | 0.550  | 0.015                | 0.022 |
| C      | 0.360                     | 0.510  | 0.014                | 0.020 |
| D      | 5.050                     | 5.350  | 0.202                | 0.214 |
| D1     | 4.550                     | 4.850  | 0.128                | 0.194 |
| E      | 3.450                     | 3.750  | 0.136                | 0.148 |
| e      | 1.270 TYP.                |        | 0.050 TYP.           |       |
| L      | 14.300                    | 14.700 | 0.572                | 0.588 |
| θ      | 10°TYP.                   |        | 10°TYP.              |       |



**Shaoxing Devechip Microelectronics Co., Ltd.**

<http://www.sdc-semi.com/>

#### IMPORTANT NOTICE

Information in this document is provided solely in connection with Shaoxing Devechip Microelectronics Co., Ltd. (abbr. SDC) products. SDC reserves the right to make changes, corrections, modifications or improvements, to this document, and the products and services described herein at anytime, without notice. SDC does not assume any responsibility for use of any its products for any particular purpose, nor does SDC assume any liability arising out of the application or use of any its products or circuits. SDC does not convey any license under its patent rights or other rights nor the rights of others.

© 2014 Devechip Microelectronics - All rights reserved

---

#### Contact us:

##### Headquarters of Shaoxing

Address: Tian Mu Road, No13,

Shaoxing city, Zhejiang province, China

Zip code: 312000

Tel: (86) 0575-8861 6750

Fax: (86) 0575-8862 2882

##### Shenzhen Branch

Address: 22A, Shangbu building, Nan Yuan Road, No.68,

Futian District, Shenzhen city, Guangdong province, China

Zip code: 518031

Tel: (86) 0755-8366 1155

Fax: (86) 0755-8301 8528