FEATURES

- * Ultrafast with Soft Recovery
- (Trr < 40ns)
- * Low Forward Voltage ($V_F=0.98V$ at $I_F=20A$)

APPLICATIONS

- * Power Switching Circuits
- * Output rectifiers
- * Freewheeling Diodes
- * Switching Mode Power Supply

POWER RECTIFIER



MAXIMUM RATINGS

Rating	Symbol	Value	Units	
Peak Repetitive Reverse Voltage	V _{RRM}	200	V	
Average Rectified Forward Current, T_C =100 °C	I _{F(AV)}	20	А	
Non-repetitive Peak Surge Current	I _{FSM}	200	А	
(Half-wave, Single Phase, 60Hz)				
Operating Junction and Storage Temperature	T _J , T _{STG}	-65 ~ 150	°C	

THERMAL CHARACTERISTICS

	Thermal Resistance - Junction to Case	$R_{ ext{ heta}JC}$	2.0	°C/W
--	---------------------------------------	---------------------	-----	------



POWER RECTIFIER

ELECTRICAL CHARACTERISTICS

Characteristics	Symbol	Min	Тур	Max	Units
Maximum Instantaneous Forward Voltage (1)	V _F				
$(I_F = 20A, T_C = 100 \ ^{\circ}C)$		-	-	1.0	V
(I _F = 20A, T _C = 25 °C)		-	-	1.2	
Maximum Instantaneous Reverse Current (1)	I _R				
(Rated DC Voltage, $T_C = 100 \ ^{\circ}C$)		-	-	200	μA
(Rated DC Voltage, $T_C = 25 \ ^{\circ}C$)		-	-	20	
Maximum Reverse Recovery Time	trr	-	-	40	ns
(I _F = 20A, di/dt = -200A/µs)	Irr	-	-	4.0	А
	Qrr	-	-	80	nQ
Avalanche Energy	W _{AVL}	0.5	-	-	mJ

(1) Pulse Test : Pulse Width = 300 $\mu s,$ Duty Cycle $\leq 2.0\%$



POWER RECTIFIER







Fig.3 Typical Capacitance







Fig.4 Typical Reverse Recovery Time vs. di/dt



POWER RECTIFIER







Fig.6 Typical Stored Charge vs. di/dt



TRADEMARKS

The following are registered and unregistered trademarks Fairchild Semiconductor owns or is authorized to use and is not intended to be an exhaustive list of all such trademarks.

ACExTM CoolFETTM CROSSVOLTTM E²CMOSTM FACTTM FACT Quiet SeriesTM FAST[®] FAST[®] FASTrTM GTOTM HiSeCTM ISOPLANAR[™] MICROWIRE[™] POP[™] PowerTrench[™] QS[™] Quiet Series[™] SuperSOT[™]-3 SuperSOT[™]-6 SuperSOT[™]-6 SuperSOT[™]-8 TinyLogic[™]

DISCLAIMER

FAIRCHILD SEMICONDUCTOR RESERVES THE RIGHT TO MAKE CHANGES WITHOUT FURTHER NOTICE TO ANY PRODUCTS HEREIN TO IMPROVE RELIABILITY, FUNCTION OR DESIGN. FAIRCHILD DOES NOT ASSUME ANY LIABILITY ARISING OUT OF THE APPLICATION OR USE OF ANY PRODUCT OR CIRCUIT DESCRIBED HEREIN; NEITHER DOES IT CONVEY ANY LICENSE UNDER ITS PATENT RIGHTS, NOR THE RIGHTS OF OTHERS.

LIFE SUPPORT POLICY

FAIRCHILD'S PRODUCTS ARE NOT AUTHORIZED FOR USE AS CRITICAL COMPONENTS IN LIFE SUPPORT DEVICES OR SYSTEMS WITHOUT THE EXPRESS WRITTEN APPROVAL OF FAIRCHILD SEMICONDUCTOR CORPORATION. As used herein:

1. Life support devices or systems are devices or systems which, (a) are intended for surgical implant into the body, or (b) support or sustain life, or (c) whose failure to perform when properly used in accordance with instructions for use provided in the labeling, can be reasonably expected to result in significant injury to the user. 2. A critical component is any component of a life support device or system whose failure to perform can be reasonably expected to cause the failure of the life support device or system, or to affect its safety or effectiveness.

PRODUCT STATUS DEFINITIONS

Definition of Terms

Datasheet Identification	Product Status	Definition
Advance Information	Formative or In Design	This datasheet contains the design specifications for product development. Specifications may change in any manner without notice.
Preliminary	First Production	This datasheet contains preliminary data, and supplementary data will be published at a later date. Fairchild Semiconductor reserves the right to make changes at any time without notice in order to improve design.
No Identification Needed	Full Production	This datasheet contains final specifications. Fairchild Semiconductor reserves the right to make changes at any time without notice in order to improve design.
Obsolete	Not In Production	This datasheet contains specifications on a product that has been discontinued by Fairchild semiconductor. The datasheet is printed for reference information only.