

SDM2F100G04GS

Fast Soft Recovery Diode Module

General Description

FRD module devices are optimized to reduce losses and EMI/RFI in high frequency power conditioning electrical systems.


These diode modules are ideally suited for power converters, motors drives and other applications where switching losses are significant portion of the total losses

Features

- ❑ Repetitive Reverse Voltage : $V_{RRM} = 400V$
- ❑ Low Forward Voltage Drop : $V_F(\text{typ.}) = 1.25V$
- ❑ Average Forward Current : $I_F(\text{AV.}) = 100A$ @ $T_C = 100^\circ C$
- ❑ Fast Reverse Recovery Time : $t_{rr}(\text{typ.}) = 55 \text{ ns}$ @ 100A
- ❑ Extensive Characterization of Recovery Parameters
- ❑ Reduced EMI and RFI
- ❑ Isolation Type Package

Applications

- ❑ High Speed & High Power Converters, Welders.
- ❑ Various Switching and Telecommunication Power Supply.



Please see the package Out line information

Absolute Maximum Ratings @ $T_C=25^\circ C$ (Per Leg)

Symbol	Parameter	Value	Unit
V_{RRM}	Repetitive Peak Reverse Voltage	400	V
V_R	Reverse DC Voltage	320	V
$I_{F(AV)}$	Average Forward Current	$T_C = 100^\circ C$, Per Diode	100
		$T_C = 100^\circ C$, Per Module	200
I_{FSM}	No Repetitive Surge Forward Current (1/2 cycle, sine)	2000	A
I^2t	I^2t For Fusing (60Hz, sine, $t=8.3ms$, $T_J = 25^\circ C$)	$16.7 * 10^3$	A ² s
T_J	Junction Temperature	-40 to +150	$^\circ C$
T_{STG}	Storage Temperature	-40 to +125	$^\circ C$
V_{ISOL}	Isolation Voltage (@ AC 1minutes)	2500	V

Electrical Characteristics $T_C=25^{\circ}\text{C}$ unless otherwise specified

Symbol	Parameter	Test Conditions	Min	Typ	Max	Unit	
V_R	Cathode Anode Breakdown Voltage	$I_R = 100\mu\text{A}$	400	--	--	V	
I_R	Repetitive Peak Reverse Current	$V_R = 400\text{V}, T_C = 100^{\circ}\text{C}$	--	--	1	mA	
V_{FM}	Maximum Forward Voltage	$I_F = 100\text{A}$	$T_C = 25^{\circ}\text{C}$	--	1.25	1.5	V
			$T_C = 100^{\circ}\text{C}$	--	1.15	--	
t_{rr}	Reverse Recovery Time	$V_R = 30\text{V},$ $I_F = 1\text{A},$ $di/dt = -200\text{A}/\mu\text{s}$	$T_C = 25^{\circ}\text{C}$	--	45	60	ns
t_{rr}	Reverse Recovery Time	$V_R = 200\text{V},$ $I_F = 100\text{A},$ $di/dt = -200\text{A}/\mu\text{s}$	$T_C = 25^{\circ}\text{C}$	--	55	--	ns
			$T_C = 100^{\circ}\text{C}$	--	90	--	

Thermal Mechanical Specifications

Symbol	Parameter	Test Conditions	Min	Typ	Max	Unit
$R_{\theta JC}$	Thermal Resistance(Isolation)	Junction-to-Case	--	--	0.34	$^{\circ}\text{C}/\text{W}$
-	Torque	Mounting Torque	1.45			N·m
-	Torque	Terminal Torque (M4)	1.45			N·m
L x W x H	Dimensions	Typical, see outline drawing	50 x 30 x 17			mm
m	Mass		--	30	--	g

Characterization curves




Figure 1. Typical Forward Voltage Drop vs. Instantaneous Forward Current




Figure 2. Typical Reverse Recovery Time vs. $-di/dt$




Figure 3. Transient Thermal Impedance (Z_{thjc}) Characteristics




Figure 4. Forward Current Derating Curve

Package Out line Information

SOT-227L



Dimensions in mm

