



Solid State Devices, Inc.

14701 Firestone Blvd * La Mirada, Ca 90638
 Phone: (562) 404-4474 * Fax: (562) 404-1773
 ssdi@ssdi-power.com * www.ssdi-power.com

SDR705 thru SDR720


**70A, 50nsec, 50-200 V
 Ultra Fast Recovery Rectifier**

Designer's Data Sheet	
Part Number/Ordering Information ^{1/}	
SDR	Screening ^{2/} <u> </u> = Not Screened TX = TX Level TXV = TXV Level S = S Level
	Family/Voltage 705 = 50V 710 = 100V 715 = 150V 720 = 200V

- Features:**
- Ultra Fast Recovery: 50nsec Maximum
 - Low Forward Voltage Drop
 - High Surge Current Capability
 - PIV to 200 Volts
 - Hermetically Sealed
 - For High Efficiency Applications
 - TX, TXV, and S-Level Screening Available ^{2/}
 - For Reverse Polarity see Data Sheet RU0059 (SDR803R thru SDR806R)

Maximum Ratings ^{4/}	Symbol	Value	Units
Peak Repetitive Reverse Voltage and DC Blocking Voltage	SDR705 V_{RRM} SDR710 V_{RWM} SDR715 V_R SDR720	50 100 150 200	Volts
Average Rectified Forward Current (Resistive Load, 60 Hz Sine Wave, $T_A = 25^\circ C$)	I_o	70	Amps
Peak Surge Current (8.3 ms Pulse, Half Sine Wave, $T_A = 25^\circ C$)	I_{FSM}	750	Amps
Operating & Storage Temperature	T_{OP} & T_{STG}	-55 to +175	$^\circ C$
Thermal Resistance (Junction to Case)	$R_{\theta JC}$	1.0	$^\circ C/W$

- Notes:**
 1/ For ordering information, Price, Operating Curves, and Availability- Contact Factory.
 2/ Screened to MIL-PRF-19500.
 3/ Recovery Conditions: $I_F = 500$ mA, $I_R = 1$ Amp, $I_{RR} = 250$ mA.
 4/ Unless Otherwise Specified, All Maximum Ratings/Electrical Characteristics @25°C.



NOTE: All specifications are subject to change without notification. SCDD's for these devices should be reviewed by SSDI prior to release.

DATA SHEET #: RU0057B

DOC



Solid State Devices, Inc.

14701 Firestone Blvd * La Mirada, CA 90638


Phone: (562) 404-4474 * Fax: (562) 404-1773

ssdi@ssdi-power.com * www.ssdi-power.com

SDR705 thru SDR720

Electrical Characteristics ^{4/}	Symbol	Value	Units
Maximum Instantaneous Forward Voltage Drop ($I_F = 70\text{Adc}$, $T_A = 25\text{ }^\circ\text{C}$, 300-500 μs Pulse)	V_{F1}	0.975	V_{DC}
Maximum Instantaneous Forward Voltage Drop ($I_F = 70\text{Adc}$, $T_A = -55\text{ }^\circ\text{C}$, 300-500 μs Pulse)	V_{F2}	1.40	V_{DC}
Maximum Reverse Leakage Current (Rated V_R , 300 μs minimum pulse)	$T_A = 25\text{ }^\circ\text{C}$ I_{R1}	25	μA
	$T_A = 100\text{ }^\circ\text{C}$ I_{R2}	6	mA
Maximum Reverse Recovery Time ($I_F = 500\text{ mA}$, $I_R = 1\text{ Amp}$, $I_{RR} = 250\text{ mA}$)	$T_A = 25\text{ }^\circ\text{C}$ t_{RR}	50	nsec
Maximum Junction Capacitance ($V_R = 10V_{DC}$, $T_A = 25^\circ\text{C}$, $f = 1\text{MHz}$)	C_J	700	pF

DO-5 Outline:



NOTE: All specifications are subject to change without notification. SCD's for these devices should be reviewed by SSDI prior to release.

DATA SHEET #: RU0057B

DOC