


# Preliminary



**SF2095B**

**380.00 MHz  
SAW Filter**



**SMP-03**

- **Low Insertion Loss**
- **5.0 X 7.0 mm Surface-Mount Case**
- **Differential Input and Output or Single Ended Input and Output**
- **Complies with Directive 2002/95/EC (RoHS)**



## Absolute Maximum Ratings

Rating	Value	Units
Maximum Incident Power in Passband	+13	dBm
Max. DC voltage between any 2 terminals	30	VDC
Storage Temperature Range	-40 to +85	°C
Suitable for lead-free soldering - Max Soldering Temperature	260°C for 30 s	

## Electrical Characteristics

Characteristic	Sym	Notes	Min	Typ	Max	Units
Nominal Center Frequency	$f_c$	1	379.9	380.00	380.1	MHz
Source Impedance (single ended)				50		$\Omega$
Load Impedance (single ended)				50		$\Omega$
Insertion Loss					13	dB
1 dB Bandwidth	$BW_1$		2.5	2.55	2.6	MHz
3 dB Bandwidth	$BW_3$			2.7	2.75	MHz
30 dB Bandwidth	$BW_{30}$				4.0	MHz
40 dB Bandwidth	$BW_{40}$				5.0	MHz
Passband Ripple	CF $\pm 0.875$ MHz				0.5	dB
Group Delay Variation					150	ns
Ultimate Rejection	CF $\pm 1.75$ MHz		30			dB
	CF $\pm 3$ MHz		50			dB
Maximum Peak RF Input Power					13	dBm
Maximum RF Input Power Over Life					10	dBm
Matching to 50 $\Omega$ Single Ended Impedance			External L-C			
Temperature Range	Operating		-40		85	°C
	Storage		-40		85	
Frequency Temperature Coefficient	FTC			0.032		ppm/°C <sup>2</sup>
Case Style			SMP-03 7 x 5 mm Nominal Footprint			
Lid Symbolization (YY=year, WW=week, S=shift)			RFM SF2095B YYWWS			

## Notes:

1. Unless noted otherwise, all specifications apply over the operating temperature range with filter soldered to the specified demonstration board with impedance matching to 50  $\Omega$  and measured with 50  $\Omega$  network analyzer.
2. Rejection is measured as attenuation below the minimum IL point in the passband. Rejection in final user application is dependent on PCB layout and external impedance matching design. See Application Note No. 42 for details.
3. The design, manufacturing process, and specifications of this filter are subject to change.
4. The turnover temperature,  $T_o$ , is the temperature of maximum (or turnover) frequency,  $f_o$ . The nominal frequency at any case temperature,  $T_c$ , may be calculated from:  

$$f = f_o [1 - FTC(T_o - T_c)]^2$$
5. Tape and Reel Standard ANSI / EIA 481.
6. Either Port 1 or Port 2 may be used for either input or output in the design. However, impedances and impedance matching may vary between Port 1 and Port 2, so that the filter must always be installed in one direction per the circuit design.
7. US and international patents may apply.
8. RFM, stylized RFM logo, and RF Monolithics, Inc. are registered trademarks of RF Monolithics, Inc.
9. ©Copyright 1999, RF Monolithics, Inc.
10. Electrostatic Sensitive Device. Observe precautions for handling.