


SUPER FAST GLASS PASSIVATED RECTIFIERS

FEATURES:

- Plastic package has Underwriters Laboratory Flammability Classification 94V-0
- High reliability
- Low forward voltage drop
- High surge current capability
- High temperature soldering guaranteed :
250°C /10 second,0.25"(6.35mm)from case

MECHANICAL DATA

Case : JEDEC ITO-220AC molded plastic
 Terminals : Leads solderable per MIL-STD-750 Method 2026
 Position : As marked
 Mouncting Position : Any
 Mouncting Torquce : 5 in - lbs.max
 Weight : 0.08 ounce,2.24grams



Dimensions in inches and (millimeters)

MAXIMUM RATINGS AND ELECTRICAL CHARACTERISTICS

Rating at 25 °C ambient temperature unless otherwise specified.

Single phase half wave, 60 Hz resistive or inductive load.

For capacitive load, derate current by 20%.

Characteristic	Symbol	SFF 8005	SFF 801	SFF 802	SFF 803	SFF 804	SFF 806	Units
Maximum recurrent peak reverse voltage	V _{RRM}	50	100	200	300	400	600	Volts
Maximum RMS voltage	V _{RMS}	35	70	140	210	280	420	Volts
Maximum DC blocking voltage	V _{DC}	50	100	200	300	400	600	Volts
Maximum average forward rectified current at T _c =100°C	I _(AV)	8.0						Amps
Peak forward surge current 8.3ms single half sine-wave superimposed on rated load (JEDEC Method)(Per leg)	I _{FSM}	125						Amps
Maximum instantaneous forward voltage (Per leg) IF=8.0A	V _F	1.0			1.30		1.70	Volts
Maximum DC reverse current (Per leg) T _c =25 °C at rated DC blocking voltage T _c =125°C	I _R	10.0 500.0						μ A
Typical reverse recovery time(Per leg)(NOTE 1)	T _{RR}	35						nS
Typical junction capacition (Per leg)(NOTE 2)	C _J	80				60		P _F
Operating temperature range	T _J	-55to+150						°C
Storage temperature range	T _{Stg}	-55to+150						°C

NOTES:

(1)Reverse Recovery Test CONDITION : $I_F=0.5A$, $I_R=1.0A$, $I_{RR}=0.25A$

(2)Measured at 1MHZ and reverse Voltage of 4.0V

