



## SOFT RECOVERY FAST SWITCHING RECTIFIER

**SFR101 THRU SFR107**

**VOLTAGE RANGE  
CURRENT**


**50 to 1000 Volts  
1.0Ampere**

### FEATURES

- Low coat construction
- Fast switching for high efficiency.
- Low reverse leakage
- High forward surge current capability
- High temperature soldering guaranteed:  
260°C/10 secods/.375”(9.5mm)lead length at 5 lbs(2.3kg) tension

### MECHANICAL DATA

- Case: Transfer molded plastic
- Epoxy: UL94V-O rate flame retardant
- Polarity: Color band denotes cathode end
- Lead: Plated axial lead, solderable per MIL-STD-202E method 208C
- Mounting position: Any
- Weight: 0.012ounce, 0.33 grams



**DO-41**

Dimensions in inches and (millimeters)

### MAXIMUM RATINGS AND ELECTRICAL CHARACTERISTICS

- Ratings at 25°C ambient temperature unless otherwise specified
- Single Phase, half wave, 60Hz, resistive or inductive load
- For capacitive load derate current by 20%

	SYMBOLS	SFR 101	SFR 102	SFR 103	SFR 104	SFR 105	SFR 106	SFR 107	UNITS
Maximum Repetitive Peak Reverse Voltage	$V_{RRM}$	50	100	200	400	600	800	1000	Volts
Maximum RMS Voltage	$V_{RMS}$	35	70	140	280	420	560	700	Volts
Maximum DC Blocking Voltage	$V_{DC}$	50	100	200	400	600	800	1000	Volts
Maximum Average Forward Rectified Current 0.375”(9.5mm) lead length at $T_A=55^{\circ}C$	$I_{(AV)}$	1.0							Amp
Peak Forward Surge Current 8.3mS single half sine wave superimposed on rated load (JEDEC method)	$I_{FSM}$	30							Amps
Maximum Instantaneous Forward Voltage @ 1.0A	$V_F$	1.3							Volts
Maximum DC Reverse Current at Rated DC Blocking Voltage	$T_A = 25^{\circ}C$	10							$\mu A$
	$T_A = 100^{\circ}C$	200							
Maximum Reverse Recovery Time (Note 3) $T_J=25^{\circ}C$	$t_{rr}$	100			150	200		ns	
Typical Junction Capacitance (Note 1)	$C_J$	15							pF
Typical Thermal Resistance (Note 2)	$R_{\theta JA}$	50							$^{\circ}C/W$
Operating Junction Temperature Range	$T_J$	(-55 to +150)							$^{\circ}C$
Storage Temperature Range	$T_{STG}$	(-55 to +150)							$^{\circ}C$

#### Notes:

1. Measured at 1.0MHz and Applied Reverse Voltage of 4.0Volts.
2. Thermal Resistance from junction to Ambient at .375”(9.5mm)lead length, P.C.board mounted.
3. Reverse Recovery Test Conditions:  $I_f=0.5mA, I_r=1.0mA, I_{rr}=0.25A$



# SOFT RECOVERY FAST SWITCHING RECTIFIER

## SFR101 THRU SFR107

VOLTAGE RANGE  
CURRENT

50 to 1000 Volts  
1.0Ampere

## RATING AND CHARACTERISTIC CURVES SFR101 THRU SFR107

FIG.1-TYPICAL FORWARD CURRENT DERATING CURVE




FIG.2-MAXIMUM NON-REPETITIVE PEAK FORWARD SURGE CURRENT




FIG.3-TYPICAL INSTANTANEOUS FORWARD CHARACTERISTICS




FIG.4-TYPICAL REVERSE CHARACTERISTICS




FIG.5-TYPICAL JUNCTION CAPACITANCE





FIG.6-TEST CIRCUIT DIAGRAM AND REVERSE RECOVERY TIME CHARACTERISTIC



NOTE: 1. Rise Time = 7ns max. Input Impedance = 1 megohm, 22pF  
2. Rise time = 10ns max. Source Impedance = 50 ohms