



# SFR151 THRU SFR157

1.5 AMPS. SOFT FAST RECOVERY RECTIFIERS

## VOLTAGE RANGE

50 to 1000 Volts

CURRENT

1.5 Amperes


## FEATURES

- \* Low forward voltage drop
- \* High current capability
- \* High reliability
- \* High surge current capability

## MECHANICAL DATA

- \* Case: Molded plastic
- \* Epoxy: UL 94V-0 rate flame retardant
- \* Lead: Axial leads, solderable per MIL-STD-202, method 208 guaranteed
- \* Polarity: Color band denotes cathode end
- \* Mounting Position: Any
- \* Weight: 0.40 grams

## DO-15



## MAXIMUM RATINGS AND ELECTRICAL CHARACTERISTICS

Rating at 25°C ambient temperature unless otherwise specified.

Single phase, half wave, 60 Hz, resistive or inductive load.

For capacitive load, derate current by 20%


TYPE NUMBER	SYMBOLS	SFR 151	SFR 152	SFR 153	SFR 154	SFR 155	SFR 156	SFR 157	UNITS
Maximum Recurrent Peak Reverse Voltage	$V_{RRM}$	50	100	200	400	600	800	1000	V
Maximum RMS Voltage	$V_{RMS}$	35	70	140	280	420	560	700	V
Maximum D. C Blocking Voltage	$V_{DC}$	50	100	200	400	600	800	1000	V
Maximum Average Forward Rectified Current .375" (9.5mm) lead length @ $T_A = 55^\circ C$	$I_{F(AV)}$	1.5							A
Peak Forward Surge Current, 8.3 ms single half sine-wave superimposed on rated load (JEDEC method)	$I_{FSM}$	50							A
Maximum Instantaneous Forward Voltage at 1.5A	$V_F$	1.2							V
Maximum D. C Reverse Current @ $T_A = 25^\circ C$ at Rated D. C Blocking Voltage @ $T_A = 100^\circ C$	$I_R$	5.0 100							$\mu A$ $\mu A$
Maximum Reverse Recovery Time (Note 1)	$T_{RR}$	120				200	350		nS
Typical Junction Capacitance (Note 2)	$C_J$	30							pF
Operating Temperature Range	$T_J$	- 65 to + 125							$^\circ C$
Storage Temperature Range	$T_{STG}$	- 65 to + 150							$^\circ C$

NOTES: 1. Reverse Recovery Test Conditions:  $I_F = 0.5A$ ,  $I_R = 1.0A$ ,  $I_{RR} = 0.25A$ .


2. Measured at 1 MHz and applied reverse voltage of 4.0V D. C.

## RATINGS AND CHARACTERISTIC CURVES (SFR151 THRU SFR157)


**FIG.1-TYPICAL FORWARD CURRENT DERATING CURVE**




**FIG.2-MAXIMUM NON-REPETITIVE FORWARD SURGE CURRENT**



**FIG.3-TYPICAL FORWARD CHARACTERISTICS**



**FIG.4-TYPICAL JUNCTION CAPACITANCE**



**FIG.5 TEST CIRCUIT DIAGRAM AND REVERSE RECOVERY TIME CHARACTERISTICS**

