

2 AMP PNP



Sorted by I_c , then V_{CE0}

Ratings based on 25°C case temperature unless otherwise specified

Part Number	I_c max (A)	V_{CE0} max (V)	h_{FE} min	h_{FE} max	@ I_c (A)	$V_{CE(sat)}$ max (V)	@ I_c (A)	f_T min (MHz)	P_T max * $T_c=100^\circ\text{C}$ (W)	Package
2N3205	2	40	20	60	Note 1	0.4	Note 1	Note 1	40	TO-59
2N3208	2	40	20	60	Note 1	0.4	Note 1	Note 1	8	TO-5
2N4387	2	40	25	100	0.5	3	1	25	20	TO-66
2N5323	2	50	40	250	Note 1	1.2	Note 1	Note 1	10	TO-5
2N3206	2	60	20	60	Note 1	0.4	Note 1	Note 1	40	TO-59
2N3740	2	60	30	100	0.25	0.6	1	4	25	TO-66
2N4388	2	60	25	100	0.5	3	1	25	20	TO-66
2N5597	2	60	70	200	1	0.85	2	35	20	TO-66
SFT5333A	2	70	40	250	2	1	2	85	15	TO-5
SFT5333S.22	2	70	40	250	1	1	2	85	15	SMD.22; SMD.22L
2N5322	2	75	30	130	Note 1	0.5	Note 1	Note 1	10	TO-5
2N4999	2	80	30	90	1	0.46	1	30	35	TO-59
2N5001	2	80	70	200	1	0.46	1	35	35	TO-59
2N5147	2	80	30	90	1	0.85	2	30	7	TO-39
2N5149	2	80	70	200	1	0.85	2	35	7	TO-39
2N5333	2	80	30	120	1	1	2	30	15*	TO-5
2N5599	2	80	30	90	Note 1	0.85	Note 1	Note 1	20	TO-66
2N5601	2	80	70	200	Note 1	0.85	Note 1	Note 1	20	TO-66
2N3207	2	100	20	60	Note 1	0.4	Note 1	Note 1	40	TO-59
2N5603	2	100	30	90	Note 1	0.85	Note 1	Note 1	20	TO-66
2N6211	2	225	30	175	1	1.4	1	Note 1	35	TO-66
2N6421	2	250	8	80	Note 1	0.75	Note 1	Note 1	35	TO-66
2N6212	2	300	30	175	1	1.6	1	Note 1	35	TO-66
2N6422	2	300	8	80	Note 1	0.75	Note 1	Note 1	35	TO-66
2N6423	2	300	10	100	Note 1	1	Note 1	Note 1	35	TO-66
2N6213	2	350	30	150	1	2	1	Note 1	35	TO-66
2N6214	2	400	10	100	Note 1	0.5	Note 1	Note 1	35	TO-66
SFT1192	2	400	80	Note 1	1	1	0.5	50	6	TO-5
SFT1192/59	2	400	40	Note 1	0.5	2	0.5	50	20	TO-59
SFT1192S.5	2	400	40	Note 1	0.5	1	0.5	50	5	SMD.5
SFX1192	2	500	40	Note 1	0.5	1	0.5	50	6	TO-5

Note 1: Contact factory for values and more information.

Hermetic Packaging

