

SG12232P (122 DOTS X 32 DOTS)

液晶之友 电话: 020-33819057

Http://www.lcdfriends.com

FEATURE

- ◆ BUILT-IN CONTROLLER (SED1520 OR EQUIVALENT)
- ◆ +5 V POWER SUPPLY
- ◆ 1/32 DUTY CYCLE
- ◆ 8-BIT PARALLEL INTERFACE
- ◆ EDGE LIGHTING TYPE LED RGB

MECHANICAL DATA

ITEM	DIMENSIONS	UNIT
Module Size (W x H x T)	117.0 x 39.0 x 12.7	mm
Viewing Area (W x H)	84.0 x 27.0	mm
Active Area (W x H)	79.62 x 20.76	mm
Dot Size (W x H)	0.61 x 0.61	mm
Dot Pitch (W x H)	0.65 x 0.65	mm

INTERFACE PIN CONNECTIONS

NO.	SYMBOL	LEVEL	FUNCTION
1	Vss	0V	Power Supply Ground
2	VDD	5V	Power Supply Voltage
3	Vo	-	Contrast Adjustment Voltage
4	Ao	H/L	Data Type Select Signal
5	R/W	H/L	H : Read / L : Write
6	E1	H,H→L	Chip Select Singal for IC1
7	E2	H,H→L	Chip Select Singal for IC2
8~15	DB0~DB7	H/L	Data Bus Line
16	/RES	L	Reset Signal
17	A	4.2V	LED Power (+)
18	K1	L	Red LED power supply
19	K2	L	Green LED power supply
20	K3	L	Blue LED power supply


ABSOLUTE MAXIMUM RATINGS


ITEM	SYMBOL	MIN.	TYP.	MAX.	UNIT
Supply Voltage For Logic	VDD-Vss	0	-	7	V
Supply Voltage For LCD Drive	VDD-Vo	0	-	12	V
Input Voltage	Vi	Vss	-	VDD	V

ELECTRICAL CHARACTERISTICS

ITEM		SYMBOL	CONDITION	MIN.	TYP.	MAX.	UNIT
Supply Voltage For Logic		VDD-VSS	-	4.5	5	5.5	V
Supply Voltage For LCD		VDD-Vo	VDD=5V Ta=25°C	4.4	4.8	5.2	V
Supply Current		IDD	VDD=5V	-	2.5	4.5	mA
Input	"HIGH" Level	VIH	-	2.2	-	VDD	V
Voltage	"LOW" Level	VIL	-	-	-	0.6	V
Output	"HIGH" Level	VOH	-	2.4	-	-	V
Voltage	"LOW" Level	VOL	-	-	-	0.4	V

EXTERNAL DIMENSIONS






SG12232P (122 DOTS X 32 DOTS)

TIMING CHARACTERISTICS

ITEM		SYMBOL	MIN.	TYP.	MAX.	UNIT.
System Cycle Time		t_{CYC6}	1000	-	-	ns
Address Set-up Time		t_{AW6}	20	-	-	ns
Address Hold Time		t_{AH6}	10	-	-	ns
Data Set-up Time		t_{DS6}	80	-	-	ns
Data Hold Time		t_{DH6}	10	-	-	ns
Output Disable Time		t_{OH6}	10	-	60	ns
Access Time		t_{ACC6}	-	-	90	ns
Enable Pulse Width	Read	t_{EW}	100	-	-	ns
	Write		80	-	-	ns



BLOCK DIAGRAM

