

High Frequency Crystal Oscillator

SG – 615PCN

Products number

Q33615N4xxxxx00

- Reflowable and high density mounting type SMD package
- Operable 3.3V
- Out put frequencies from 26.0001 MHz to 67.000 MHz (3rd O/T)
- Output enable(OE : P type) function allow more low current consumption.(OUT:High Impedance)

Specifications

1. Absolute Maximum Ratings

Item	Symbol	Spec.	Remarks
Storage Temperature	T _{STG}	-55 °C to +125 °C	Stored as bare product
Maximum supply voltage	V _{DD}	-0.5 V to 7.0 V	
Maximum input voltage	V _{IN}	-0.5 V to V _{DD} +0.5 V	

2. Operating Conditions

Item	Symbol	Spec.	Remarks
Operating Temperature	T _{OPR}	-40 °C ~ +85 °C	
Operating voltage	V _{DD}	3.0 V ~ 3.6 V	
Input voltage	V _{IN}	GND ~ V _{DD}	
Output load condition	CL	15 pF	

3. Frequency Characteristics

Item	Symbol	Spec.	Remarks
Output frequency range*	f _o	26.0001 MHz ~ 66.6667 MHz	V _{DD} =3.0 V ~ 3.6 V
Frequency stability	f / f _o	B: $\pm 50 \times 10^{-6}$, C: $\pm 100 \times 10^{-6}$	-20 °C ~ +70 °C
		M: $\pm 100 \times 10^{-6}$	-40 °C ~ +85 °C
Aging	f _a	$\pm 5 \times 10^{-6}$ Max.	


*Note :

Please contact to EPSON about Standard Frequency.

4. Characteristics

Item	Symbol	Spec.	Remarks
Current consumption	I _{OP}	30 mA Max.	CL=15 pF(67MHz)
Disable current	I _{OE}	15 mA Max.	OE=GND, OUT= High Impedance
OE input voltage	V _{IH}	70 %V _{DD} Min.	
	V _{IL}	30 %V _{DD} Max.	
OE input current	I _{IH}	10 μA Max.	OE = V _{DD}
	I _{IL}	10 μA Max.	OE =GND
Duty	T _w / T	45 %~ 55 %	50%V _{DD} , CL= 15 pF
Output voltage	V _{OH}	2.2 V Min.	V _{DD} =2.7 V, I _{OH} =- 8 mA
	V _{OL}	0.4 V Max.	V _{DD} =2.7 V, I _{OL} = 8 mA
Output rise time	t _r	7.0 ns Max.	10 % to 90 %V _{DD} CL ≤15 pF
Output fall time	t _f	7.0 ns Max.	90 % to 10 %V _{DD} CL ≤15 pF
Oscillation start up time	t _{osc}	10 ms Max.	

5. External Dimensions & Recommended soldering pattern (Unit : mm)



NOTICE

- No part of this material may be reproduced or duplicated in any form or any means without the written permission of Seiko Epson.
- Seiko Epson reserves the right to make changes to this material without notice.
- Seiko Epson does not assume any liability of any kind arising out of any inaccuracies contained in this material or due to its application or use in any product or circuit and, further, there is no representation that this material is applicable to products requiring high level reliability, such as, medical products.
- Moreover, no license to any intellectual property rights is granted by implication or otherwise, and there is no representation or warranty that anything made in accordance with this material will be free from any patent or copyright infringement of a third party.
- This material of portions thereof may contain technology or the subject relating to strategic products under the control of the Foreign Exchange and Foreign Trade Law of Japan and may require an export license from the Ministry of international Trade and industry or other approval from another government agency.

© SEIKO EPSON CORPORATION 2001

SEIKO EPSON CORPORATION

ELECTRONIC DEVICE MARKETING DEPARTMENT

EPSON ELECTRONICS AMERICA, INC.

150 River Oaks Parkway, San Jose, CA 95134, U.S.A.

Phone: (1)800-228-3964 (Toll free) : (1)408-922-0200 Fax: (1)408-922-0238

EPSON EUROPE ELECTRONICS GmbH

Riesstrasse 15, 80992 Munich Germany

Phone: (49)-(0)89-14005-0 Fax: (49)-(0)89-14005-110

EPSON (CHINA) CO., LTD.

28F, Beijing Silver Tower 2# North RD DongSangHuan ChaoYang District, Beijing, China

Phone: (86) 10-6410-6655 Fax: (86) 10-6410-7319

EPSON HONG KONG LTD.

20/F., Harbour Centre, 25 Harbour Road, Wanchai, Hong kong

Phone: (852) 2585-4600 Fax: (852) 2827-2152

EPSON TAIWAN TECHNOLOGY & TRADING LTD.

10F, No.287, Nanking East Road, Sec.3, Taipei

Phone: (886) 2-2717-7360 Fax: (886)2-2718-9366

EPSON SINGAPORE PTE. LTD.

No.1, Temasek Avenue #36-00, Millenia Tower, Singapore 039192

Phone: (65) 337-7911 Fax: (65) 334-2716

SEIKO EPSON CORPORATION KOREA Office

50F, KLI 63 Building,60 Yoido-dong, Youngdeungpo-Ku, Seoul, 150-763, Korea

Phone: (82) 2-784-6027 Fax: (82) 2-767-3677

Electronic devices information on WWW server

<http://www.epson.co.jp/device/>



Issued on jun.,2001