

GENERAL DESCRIPTION

The SGM7SZ245S is an octal bus transceiver with 3-state outputs, which can accept supply voltage range from 1.8V to 5.5V. The device is mainly used for asynchronous communication between data buses. The control function can minimize external timing requirements to the greatest extent possible.

The An and Bn are 8-bit data input-output ports. DIR is the direction control input and \overline{OE} is the output enable input. When DIR is set high, it allows transmission from An to Bn. When DIR is set low, it allows transmission from Bn to An. \overline{OE} can be used to make the outputs disabled so that the buses are effectively isolated.

The SGM7SZ245S is available in Green TSSOP-20, TQFN-3×3-20L and TQFN-5.5×3.5-24L packages. It operates over an ambient temperature range of -40°C to +125°C.

FUNCTION TABLE


CONTROL INPUT		INPUT/OUTPUT	
\overline{OE}	DIR	An	Bn
L	L	An = Bn	Inputs
L	H	Inputs	Bn = An
H	X	Z	Z

H = High Voltage Level
 L = Low Voltage Level
 Z = High-Impedance State
 X = Don't Care

FEATURES

- **Wide Supply Voltage Range: 1.8V to 5.5V**
- **Input and Output Interface Capability to 5.5V System Environment**
- **+7.8mA/-7.8mA Output Current at $V_{CC} = 5.0V$**
- **3-State Outputs Drive Bus Lines Directly**
- **-40°C to +125°C Operating Temperature Range**
- **Available in Green TSSOP-20, TQFN-3×3-20L and TQFN-5.5×3.5-24L Packages**

LOGIC DIAGRAM




PACKAGE/ORDERING INFORMATION

MODEL	PACKAGE DESCRIPTION	SPECIFIED TEMPERATURE RANGE	ORDERING NUMBER	PACKAGE MARKING	PACKING OPTION
SGM7SZ245S	TSSOP-20	-40°C to +125°C	SGM7SZ245SXTS20G/TR	SGM06NXTS20 XXXXX	Tape and Reel, 4000
	TQFN-3×3-20L	-40°C to +125°C	SGM7SZ245SXTQG20G/TR	SGM 06OQG XXXXX	Tape and Reel, 4000
	TQFN-5.5×3.5-24L	-40°C to +125°C	SGM7SZ245SXTQQ24G/TR	SGM7SZ245S XTQQ XXXXX	Tape and Reel, 3000

MARKING INFORMATION

NOTE: XXXXX = Date Code, Trace Code and Vendor Code.

XXXXX



Green (RoHS & HSF): SG Micro Corp defines "Green" to mean Pb-Free (RoHS compatible) and free of halogen substances. If you have additional comments or questions, please contact your SGMICRO representative directly.

ABSOLUTE MAXIMUM RATINGS ⁽¹⁾

Supply Voltage Range, V_{CC}	-0.3V to 6.0V
Input Voltage, V_I ⁽²⁾	-0.3V to 6.0V
Output Voltage, V_O ⁽²⁾	
High-State or Low-State.....	-0.3V to MIN(6.0V, $V_{CC} + 0.3V$)
3-State Mode	-0.3V to 6.0V
Input Clamp Current, I_{IK} ($V_I < 0V$)	-20mA
Output Clamp Current, I_{OK} ($V_O < 0V$)	-20mA
Continuous Output Current, I_O ($V_O = 0V$ to V_{CC})	±40mA
Continuous Current through V_{CC} or GND.....	±70mA
Junction Temperature ⁽³⁾	+150°C
Storage Temperature Range	-65°C to +150°C
Lead Temperature (Soldering, 10s).....	+260°C
ESD Susceptibility	
HBM.....	2000V
CDM	1000V

RECOMMENDED OPERATING CONDITIONS

Supply Voltage Range, V_{CC}	1.8V to 5.5V
Input Voltage Range, V_I	0V to 5.5V
Output Voltage, V_O	
High-State or Low-State.....	0V to V_{CC}
3-State Mode	0V to 5.5V
Operating Temperature Range	-40°C to +125°C

OVERSTRESS CAUTION

1. Stresses beyond those listed in Absolute Maximum Ratings may cause permanent damage to the device. Exposure to absolute maximum rating conditions for extended periods may affect reliability. Functional operation of the device at any conditions beyond those indicated in the Recommended Operating Conditions section is not implied.
2. The input and output negative voltage ratings may be exceeded if the input and output clamp current ratings are observed.
3. The performance capability of a high-performance integrated circuit in conjunction with its thermal environment can create junction temperatures which are detrimental to reliability.




ESD SENSITIVITY CAUTION

This integrated circuit can be damaged if ESD protections are not considered carefully. SGMICRO recommends that all integrated circuits be handled with appropriate precautions. Failure to observe proper handling and installation procedures can cause damage. ESD damage can range from subtle performance degradation to complete device failure. Precision integrated circuits may be more susceptible to damage because even small parametric changes could cause the device not to meet the published specifications.

DISCLAIMER

SG Micro Corp reserves the right to make any change in circuit design, or specifications without prior notice.

PIN CONFIGURATIONS



PIN DESCRIPTION

PIN			NAME	FUNCTION
TSSOP-20	TQFN-3×3-20L	TQFN-5.5×3.5-24L		
1	18	2	DIR	Direction Control Input.
2, 3, 4, 5	19, 20, 1, 2	3, 4, 5, 6	A1, A2, A3, A4	Data Inputs/Outputs.
6, 7, 8, 9	3, 4, 5, 6	7, 8, 9, 10	A5, A6, A7, A8	Data Inputs/Outputs.
10	7	11	GND	Ground.
11, 12, 13, 14	8, 9, 10, 11	14, 15, 16, 17	B8, B7, B6, B5	Data Inputs/Outputs.
15, 16, 17, 18	12, 13, 14, 15	18, 19, 20, 21	B4, B3, B2, B1	Data Inputs/Outputs.
19	16	22	\overline{OE}	Output Enable Input (Active Low).
20	17	23	V _{CC}	Supply Voltage. 1.8V ≤ V _{CC} ≤ 5.5V
–	–	1, 12, 13, 24	NC	No Connection.
–	Exposed Pad	Exposed Pad	GND	Connect it to GND internally. This pad is not an electrical connection point.

ELECTRICAL CHARACTERISTICS(Full = -40°C to +125°C, all typical values are measured at T_A = +25°C, unless otherwise noted.)

PARAMETER	SYMBOL	CONDITIONS	TEMP	MIN	TYP	MAX	UNITS	
High-Level Input Voltage	V _{IH}	V _{CC} = 1.8V	Full	1.20			V	
		V _{CC} = 3.3V	Full	1.75				
		V _{CC} = 5.0V	Full	2.20				
Low-Level Input Voltage	V _{IL}	V _{CC} = 1.8V	Full			0.40	V	
		V _{CC} = 3.3V	Full			0.65		
		V _{CC} = 5.0V	Full			0.65		
High-Level Output Voltage	V _{OH}	V _I = V _{IH}	V _{CC} = 1.8V, I _{OH} = -20μA	Full	1.75	1.795	V	
			V _{CC} = 3.3V, I _{OH} = -20μA	Full	3.25	3.295		
			V _{CC} = 5.0V, I _{OH} = -20μA	Full	4.95	4.995		
			V _{CC} = 3.3V, I _{OH} = -6mA	Full	3.20	3.260		
			V _{CC} = 5.0V, I _{OH} = -7.8mA	Full	4.88	4.960		
Low-Level Output Voltage	V _{OL}	V _I = V _{IL}	V _{CC} = 1.8V, I _{OL} = 20μA	Full		0.005	V	
			V _{CC} = 3.3V, I _{OL} = 20μA	Full		0.005		0.05
			V _{CC} = 5.0V, I _{OL} = 20μA	Full		0.005		0.05
			V _{CC} = 3.3V, I _{OL} = 6mA	Full		0.045		0.115
			V _{CC} = 5.0V, I _{OL} = 7.8mA	Full		0.050		0.14
Input Leakage Current	I _I	Control inputs, V _{CC} = 5.5V, V _I = V _{CC} or 0V	Full		±0.01	±1	μA	
Off-State Output Current	I _{OZ}	A or B ports, V _{CC} = 5.5V, V _O = V _{CC} or 0V	Full		±0.01	±10	μA	
Supply Current	I _{CC}	V _{CC} = 5.5V, V _I = V _{CC} or 0V, I _O = 0A	Full		0.01	10	μA	
Power-Off Leakage Current	I _{OFF}	V _{CC} = 0V, V _I or V _O = 0V to 5.5V	Full		±0.01	±10	μA	
Input Capacitance	C _I	Control inputs, V _{CC} = 1.8V to 5.5V	+25°C		10.5		pF	
Input/Output Capacitance	C _{IO}		+25°C		10		pF	

DYNAMIC CHARACTERISTICS

(See Figure 1 for test circuit. Full = -40°C to +125°C, all typical values are measured at T_A = +25°C, unless otherwise noted.)

PARAMETER	SYMBOL	CONDITIONS	TEMP	MIN ⁽¹⁾	TYP	MAX ⁽¹⁾	UNITS	
Propagation Delay ⁽²⁾	t _{PD}	An or Bn to Bn or An, C _L = 50pF	V _{CC} = 1.8V	Full	0.5	13.1	32	ns
			V _{CC} = 3.3V	Full	0.1	5.5	10.0	
			V _{CC} = 5.0V	Full	0.1	4.4	8.0	
		An or Bn to Bn or An, C _L = 150pF	V _{CC} = 1.8V	Full	0.5	14.2	35	
			V _{CC} = 3.3V	Full	0.1	6.1	13.0	
			V _{CC} = 5.0V	Full	0.1	4.9	10.0	
Enable Time ⁽²⁾	t _{EN}	OE̅ to An or Bn, C _L = 50pF	V _{CC} = 1.8V	Full	0.5	19.0	40	ns
			V _{CC} = 3.3V	Full	0.1	7.3	13.0	
			V _{CC} = 5.0V	Full	0.1	5.5	10.0	
		OE̅ to An or Bn, C _L = 150pF	V _{CC} = 1.8V	Full	0.5	20	43	
			V _{CC} = 3.3V	Full	0.1	7.8	15.0	
			V _{CC} = 5.0V	Full	0.1	6.0	11.0	
Disable Time ⁽²⁾	t _{DIS}	OE̅ to An or Bn, C _L = 50pF	V _{CC} = 1.8V	Full	0.5	20	39	ns
			V _{CC} = 3.3V	Full	0.5	12.3	25	
			V _{CC} = 5.0V	Full	0.1	10.8	21	
		OE̅ to An or Bn, C _L = 150pF	V _{CC} = 1.8V	Full	0.5	28.4	60	
			V _{CC} = 3.3V	Full	0.5	19.8	42	
			V _{CC} = 5.0V	Full	0.5	18.7	38	
Output Rise and Fall Times	t _R , t _F	C _L = 15pF	V _{CC} = 1.8V	Full	0.1	1.8	5.5	ns
			V _{CC} = 3.3V	Full	0.1	0.9	2.0	
			V _{CC} = 5.0V	Full	0.1	0.8	1.4	
		C _L = 30pF	V _{CC} = 1.8V	Full	0.1	1.9	6.5	
			V _{CC} = 3.3V	Full	0.1	0.9	2.5	
			V _{CC} = 5.0V	Full	0.1	0.9	1.8	
		C _L = 50pF	V _{CC} = 1.8V	Full	0.1	2.2	7.5	
			V _{CC} = 3.3V	Full	0.1	2.6	5.0	
			V _{CC} = 5.0V	Full	0.1	1.2	2.3	
Power Dissipation Capacitance ⁽³⁾	C _{PD}	No load	+25°C		26.5		pF	

NOTES:

- Specified by design and characterization, not production tested.
- t_{PD} is the same as t_{PLH} and t_{PHL}. t_{DIS} is the same as t_{PLZ} and t_{PHZ}. t_{EN} is the same as t_{PZL} and t_{PZH}.
- C_{PD} is used to determine the dynamic power dissipation (P_D in μW).

$$P_D = C_{PD} \times V_{CC}^2 \times f_i \times N + \Sigma(C_L \times V_{CC}^2 \times f_o)$$

where:

f_i = Input frequency in MHz.

f_o = Output frequency in MHz.


C_L = Output load capacitance in pF.

V_{CC} = Supply voltage in Volts.

N = Number of inputs switching.

Σ(C_L × V_{CC}² × f_o) = Sum of outputs.

TEST CIRCUIT



Test conditions are given in Table 1.

Definitions for test circuit:

R_L : Load resistance.

C_L : Load capacitance (includes jig and probe).

R_T : Termination resistance (equals to output impedance Z_O of the pulse generator).


S1: Test selection switch.

Figure 1. Test Circuit for Measuring Switching Times

Table 1. Test Conditions

SUPPLY VOLTAGE	INPUT		LOAD		S1 POSITION		
V_{CC}	V_I	t_R, t_F	C_L	R_L	t_{PHL}, t_{PLH}	t_{PZH}, t_{PHZ}	t_{PZL}, t_{PLZ}
1.8V to 5.5V	V_{CC}	$\leq 2.5\text{ns}$	50pF, 150pF	1k Ω	Open	GND	V_{CC}

WAVEFORMS




Test conditions are given in Table 1.

Measurement points are given in Table 2.

Logic levels: V_{OL} and V_{OH} are typical output voltage levels that occur with the output load.

Figure 2. Input (An, Bn) to Output (Bn, An) Propagation Delay Times



Test conditions are given in Table 1.

Measurement points are given in Table 2.

Logic levels: V_{OL} and V_{OH} are typical output voltage levels that occur with the output load.

Figure 3. Enable and Disable Times

Table 2. Measurement Points

SUPPLY VOLTAGE	INPUT		OUTPUT		
V_{CC}	V_I	$V_M^{(1)}$	V_M	V_X	V_Y
1.8V to 5.5V	V_{CC}	$0.5 \times V_{CC}$	$0.5 \times V_{CC}$	$V_{OL} + 0.3V$	$V_{OH} - 0.3V$

NOTE:

1. The measurement points should be V_{IH} or V_{IL} when the input rising or falling time exceeds 2.5ns.



REVISION HISTORY

NOTE: Page numbers for previous revisions may differ from page numbers in the current version.


Changes from Original (JULY 2023) to REV.A	Page
Changed from product preview to production data.....	All

PACKAGE OUTLINE DIMENSIONS

TSSOP-20



RECOMMENDED LAND PATTERN (Unit: mm)




Symbol	Dimensions In Millimeters		
	MIN	MOD	MAX
A	-	-	1.200
A1	0.050	-	0.150
A2	0.800	-	1.050
b	0.190	-	0.300
c	0.090	-	0.200
D	6.400	-	6.600
E	4.300	-	4.500
E1	6.200	-	6.600
e	0.650 BSC		
L	0.450	-	0.750
H	0.250 TYP		
θ	0°	-	8°
ccc	0.100		

NOTES:


1. Body dimensions do not include mode flash or protrusion.
2. This drawing is subject to change without notice.
3. Reference JEDEC MO-153.

PACKAGE OUTLINE DIMENSIONS


TQFN-3×3-20L




TOP VIEW



BOTTOM VIEW



SIDE VIEW




RECOMMENDED LAND PATTERN (Unit: mm)


Symbol	Dimensions In Millimeters		Dimensions In Inches	
	MIN	MAX	MIN	MAX
A	0.700	0.800	0.028	0.031
A1	0.000	0.050	0.000	0.002
A2	0.203 REF		0.008 REF	
D	2.924	3.076	0.115	0.121
D1	1.400	1.600	0.055	0.063
E	2.924	3.076	0.115	0.121
E1	1.400	1.600	0.055	0.063
k	0.200 MIN		0.008 MIN	
b	0.150	0.250	0.006	0.010
e	0.400 TYP		0.016 TYP	
L	0.324	0.476	0.013	0.019

PACKAGE OUTLINE DIMENSIONS


TQFN-5.5×3.5-24L




TOP VIEW



BOTTOM VIEW



SIDE VIEW



RECOMMENDED LAND PATTERN (Unit: mm)

Symbol	Dimensions In Millimeters		Dimensions In Inches	
	MIN	MAX	MIN	MAX
A	0.700	0.800	0.028	0.031
A1	0.000	0.050	0.000	0.002
A2	0.203 REF		0.008 REF	
D	3.400	3.600	0.134	0.142
D1	1.950	2.150	0.077	0.085
E	5.400	5.600	0.213	0.220
E1	3.950	4.150	0.156	0.163
k	0.325 REF		0.013 REF	
b	0.200	0.300	0.008	0.012
b1	0.150	0.250	0.006	0.010
L	0.300	0.500	0.012	0.020
e	0.500 BSC		0.020 BSC	
e1	1.500 BSC		0.059 BSC	

TAPE AND REEL INFORMATION

REEL DIMENSIONS



TAPE DIMENSIONS



NOTE: The picture is only for reference. Please make the object as the standard.

KEY PARAMETER LIST OF TAPE AND REEL

Package Type	Reel Diameter	Reel Width W1 (mm)	A0 (mm)	B0 (mm)	K0 (mm)	P0 (mm)	P1 (mm)	P2 (mm)	W (mm)	Pin1 Quadrant
TSSOP-20	13"	16.4	6.80	6.90	1.50	4.0	8.0	2.0	16.0	Q1
TQFN-3×3-20L	13"	12.4	3.30	3.30	1.10	4.0	8.0	2.0	12.0	Q2
TQFN-5.5×3.5-24L	13"	12.4	3.80	5.80	1.00	4.0	8.0	2.0	12.0	Q1

DD0001

PACKAGE INFORMATION

CARTON BOX DIMENSIONS



NOTE: The picture is only for reference. Please make the object as the standard.

KEY PARAMETER LIST OF CARTON BOX

Reel Type	Length (mm)	Width (mm)	Height (mm)	Pizza/Carton
13"	386	280	370	5

DD0002