

Features



- Halogen Free
- AEC-Q101 Qualified
- Low $R_{DS(ON)}$
- Epoxy Meets UL 94 V-0 Flammability Rating
- Moisture Sensitivity Level 1
- Lead Free Finish/RoHS Compliant ("P" Suffix Designates RoHS Compliant. See Ordering Information)

Maximum Ratings

- Operating Junction Temperature Range: -55°C to $+150^{\circ}\text{C}$
- Storage Temperature: -55°C to $+150^{\circ}\text{C}$
- Thermal Resistance: 90°C/W Junction to Ambient^(Note 1)


Parameter	Symbol	Rating	Unit
Drain-Source Voltage	V_{DS}	-20	V
Gate-Source Voltage	V_{GS}	± 10	V
Drain Current-Continuous	I_D	-4.2	A
Drain Current-Pulse ^(Note 2)	I_{DM}	-21	A
Power Dissipation	P_D	1.4	W

Internal Structure and Marking Code




P-Channel MOSFET

SOT-23



DIM	INCHES		MM		NOTE
	MIN	MAX	MIN	MAX	
A	0.110	0.120	2.80	3.04	
B	0.083	0.104	2.10	2.64	
C	0.047	0.055	1.20	1.40	
D	0.034	0.041	0.85	1.05	
E	0.067	0.083	1.70	2.10	
F	0.018	0.024	0.45	0.60	
G	0.0004	0.006	0.01	0.15	
H	0.035	0.043	0.90	1.10	
J	0.003	0.007	0.08	0.18	
K	0.012	0.020	0.30	0.51	
L	0.007	0.020	0.20	0.50	

Suggested Solder Pad Layout



ELECTRICAL CHARACTERISTICS (Ta=25°C unless otherwise specified)

Parameter	Symbol	Test conditions	Min	Typ	Max	Unit
Static Characteristics						
Drain-Source Breakdown Voltage	$V_{(BR)DSS}$	$V_{GS}=0V, I_D=-250\mu A$	-20			V
Gate-Threshold Voltage	$V_{GS(th)}$	$V_{DS}=V_{GS}, I_D=-250\mu A$	-0.5	-0.65	-0.9	V
Gate-Body Leakage Current	I_{GSS}	$V_{GS}=\pm 10V, V_{DS}=0V$			± 100	nA
Zero Gate Voltage Drain Current	I_{DSS}	$V_{DS}=-20V, V_{GS}=0V$			-1	μA
Drain-Source On-Resistance ^(Note 3)	$R_{DS(on)}$	$V_{GS}=-4.5V, I_D=-2.7A$		35	60	m Ω
		$V_{GS}=-2.5V, I_D=-2.7A$		46	80	
		$V_{GS}=-1.8V, I_D=-2.7A$		90		
Body Diode Voltage	V_{SD}	$I_S=-5.4A, V_{GS}=0V$			-1.2	V
Dynamic Characteristics						
Input Capacitance ^(Note 1,4)	C_{iss}	$V_{DS}=-10V, V_{GS}=0V, f=1MHz$		1010		pF
Output Capacitance ^(Note 1,4)	C_{oss}			130		
Reverse Transfer Capacitance ^(Note 1,4)	C_{rss}			109		
Total Gate Charge ^(Note 1)	Q_g	$V_{DS}=-10V, V_{GS}=-4.5V, I_D=-4A$		10.98		nC
Gate-Source Chage ^(Note 1)	Q_{gs}			2.17		
Gage-Drain Charge ^(Note 1)	Q_{gd}			2.54		
Reverse Recovery Chrage	Q_{rr}	$I_F=-4A, di/dt=100A/us$		4.38		nC
Reverse Recovery Time	t_{rr}			24.8		ns
Turn-On Delay Time ^(Note 1,4)	$t_{d(on)}$	$V_{DD}=-4V, V_{GEN}=-4.5V, R_L=1.2\Omega, I_D=-3.3A, R_G=1\Omega$		8.4		ns
Turn-On Rise Time ^(Note 1,4)	t_r			36.2		
Turn-Off Delay Time ^(Note 1,4)	$t_{d(off)}$			76.8		
Turn-Off Fall Time ^(Note 1,4)	t_f			56.2		

Note:

1. Guaranteed by Design, Not Subject to Production Testing.
2. Repetitive Rating: Pulse Width Limited by Max. Junction Temperature.
3. Pulse Test: Pulse Width $\leq 300\mu s$, Duty Cycle $\leq 2\%$.
4. These Parameters Have No Way to Verify.

Curve Characteristics

Fig. 1 - On-Resistance Characteristics




Fig. 2 - Drain Current Characteristics




Fig. 3 - Output Characteristics




Fig. 4 - On-Resistance Characteristics




Fig. 5 - Safe Operation Area





Fig. 6 - Threshold Voltage



Ordering Information

Device	Packing
Part Number-TP	Tape&Reel:3Kpcs/Reel

IMPORTANT NOTICE

Micro Commercial Components Corp. reserves the right to make changes without further notice to any product herein to make corrections, modifications , enhancements , improvements , or other changes . **Micro Commercial Components Corp** . does not assume any liability arising out of the application or use of any product described herein; neither does it convey any license under its patent rights ,nor the rights of others . The user of products in such applications shall assume all risks of such use and will agree to hold **Micro Commercial Components Corp** . and all the companies whose products are represented on our website, harmless against all damages.

LIFE SUPPORT

MCC's products are not authorized for use as critical components in life support devices or systems without the express written approval of Micro Commercial Components Corporation.

CUSTOMER AWARENESS

Counterfeiting of semiconductor parts is a growing problem in the industry. Micro Commercial Components (MCC) is taking strong measures to protect ourselves and our customers from the proliferation of counterfeit parts. MCC strongly encourages customers to purchase MCC parts either directly from MCC or from Authorized MCC Distributors who are listed by country on our web page cited below. Products customers buy either from MCC directly or from Authorized MCC Distributors are genuine parts, have full traceability, meet MCC's quality standards for handling and storage. **MCC will not provide any warranty coverage or other assistance for parts bought from Unauthorized Sources.** MCC is committed to combat this global problem and encourage our customers to do their part in stopping this practice by buying direct or from authorized distributors.