

SIL06 Series

Single output

NEW Product

- **Ultra wide trim range 0.9V to 3.3V/5.0V**
- **Current sink capability for termination application**
- **Horizontal and vertical-mount options available**
- **High power density design means reduced board space requirement**
- **Power good output signal (open collector)**
- **Operating ambient temperature up to +80°C with suitable derating and forced air cooling**
- **Remote ON/OFF (active high)**
- **0A minimum load**
- **Input under-voltage lockout**
- **Over-current and short-circuit protection**



The SIL06 Series is a new high density open frame non-isolated converter for space sensitive applications. Each model has a wide input range (4.5 - 5.5VDC or 10.2 - 13.8VDC) and offer a wide 0.9 - 5V output voltage range with a 6A load. An external resistor adjusts the output voltage from its pre-set value of 0.9V to any value up to the 5V maximum. Typical efficiencies for the models are 89% for the 5V input version and 91% for the 12V input version. The SIL06 series offers remote ON/OFF and over-current protection as standard. With full international safety approval including EN60950 and UL/cUL60950, the SIL06 reduces compliance costs and time to market.

2 YEAR WARRANTY

All specifications are typical at nominal input, full load at 25°C unless otherwise stated

SPECIFICATIONS

OUTPUT SPECIFICATIONS

Voltage adjustability (See Note 7)	5V input models 12V input models	0.9V to 3.3V 0.9V to 5.0V
Output setpoint accuracy	With 1.0% trim resistors	±2.5%
Line regulation	Low line to high line	±0.2% max.
Load regulation	Full load to min. load	±0.5% max.
Min./max. load		0A/6A
Overshoot (at turn on)	5V input models 12V input models	3.0% max. 1.0% max.
Undershoot		100mV max.
Ripple and noise	5Hz to 20MHz (See Note 2)	See table
Transient response (See Note 1)	Deviation	75mV 150µs recovery to within regulation band

INPUT SPECIFICATIONS

Input voltage range	5V input model 12V input model	4.5 to 5.5VDC 10.2 to 13.8VDC
Input current	No load Remote OFF	50mA 5mA
Input current (max.) (See Note 9)	5V input model 12V input model	5.1A @ I _o max. 1.6A @ I _o max.
Input reflected ripple (See Note 2)	5V input model 12V input model	52mA (pk-pk) 56mA (pk-pk)
Remote ON/OFF Logic compatibility		Active high ON >2.4VDC OFF <0.8VDC
Start-up time (See Note 3)	Power up Remote ON/OFF	<20ms <20ms

INPUT SPECIFICATIONS Contd.

Turn ON threshold	5Vin model 12Vin model	4.5V 9.0V
Turn OFF threshold	5Vin model 12Vin model	4.3V 7.5V

GENERAL SPECIFICATIONS

Efficiency		See table
Switching frequency	Fixed	200kHz
Approvals and standards (See Note 4)		TÜV Product Service IEC60950, UL/cUL60950
Material flammability		UL94V-0
Weight		9.3g (0.3oz)
MTBF	MIL-HDBK-217F	1,307,257 hours
Representative model:	12V model @ 40°C 100% load, ground benign Bellcore 332	7,562,142 hours

ENVIRONMENTAL SPECIFICATIONS

Thermal performance (See Note 10)	Operating ambient, temperature Non-operating	0°C to +80°C -40°C to +125°C
Altitude derating (above sea level)	3,000m (9,843 ft) 10,000m (32,808 ft)	20% 50%

SIL06 Series

Single Output

DC/DC CONVERTERS 6A Non-isolated DC/DC Converters

2

For the most current data and application support visit www.artesyn.com/powergroup/products.htm

NEW Product

OUTPUT POWER (MAX.)	INPUT VOLTAGE	OVP	OUTPUT VOLTAGE ⁽¹²⁾	OUTPUT CURRENT (MIN.)	OUTPUT CURRENT (MAX.)	EFFICIENCY (TYP.)	REGULATION		MODEL NUMBER ⁽⁵⁾
							LINE	LOAD	
20W	4.5-5.5VDC	N/A	0.9V - 3.3V	0A	6A	89%	±0.2%	±0.5%	SIL06-05SADJ-V
30W	10.2-13.8VDC	N/A	0.9V - 5.0V	0A	6A	91%	±0.2%	±0.5%	SIL06-12SADJ-V

www.DataSheet.com

- 1 $di/dt = 10A/\mu s$, $V_{in} = \text{Nom}$, $T_c = 25^\circ C$, load change = 0.5 I_o max. to 0.75 I_o max. and 0.75 I_o max. to 0.5 I_o max.
- 2 Measured with external filter. See Application Note 131 for details.
- 3 Power up is the time from application of DC input to Power Good enabled. Remote ON/OFF is from ON/OFF asserted high to Power Good enabled
- 4 This product is only for inclusion by professional installers within other equipment and must not be operated as a stand alone product.
- 5 The standard unit with the suffix '-V' is for vertical mounting. To order a unit with horizontal mounting, please add the suffix '-H' to the model number, e.g. SIL06-05SADJ-H.
- 6 Measured as per recommended set-up. $C_{in} = 270\mu F$ (20m Ω esr max.). $C_{out} = 680\mu F$ (10m Ω esr max.).
- 7 Uses external resistor from trim to output ground. Minimum value 485 Ω for 5V model, 280 Ω for 12V model. See Applications Note 131 for details.
- 8 Signal line assumed <3m.
- 9 External input fusing recommended.
- 10 See Application Note 131 for operation above 50°C.
- 11 See Application Note 131 for more details.
- 12 These models have a wide trim output. 5Vin has an output of 0.9V to 3.3V and 12 Vin has an output of 0.9V to 5V. An external resistor adjusts the output voltage.

Ripple and Noise Specification

Model	Output Voltage	Pk - Pk	RMS
5V input models	0.9 to 2.5V	30mV	15mV
	3.3V	40mV	15mV
12V input models	0.9 to 2.5V	40mV	20mV
	3.3 to 5V	50mV	20mV

PROTECTION

Short-circuit protection Hiccup, non-latching

RECOMMENDED SYSTEM CAPACITANCE

Input capacitance (See Note 11) 270 μF /20m Ω esr max.

Output capacitance (See Note 11) 680 μF /10m Ω esr max.

CAUTION: High internal temperatures. Ensure that unit is not user accessible.

PIN CONNECTIONS

PIN NUMBER	FUNCTION
1	Vout
2	Trim
3	Ground
4	Power Good
5	Remote ON/OFF
6	Vin
7	Mechanical support
8	Mechanical support
9	Mechanical support on horizontal version only

International Safety Standard Approvals (pending)



TÜV

Please consult our website for the following items: ✓ Application Note ✓ Longform Data Sheet

www.artesyn.com www.DataSheet4U.com

SIL06 Series

Single Output




Figure 1: Mechanical Drawing - Horizontal Mount Version




Figure 2: Mechanical Drawing - Vertical Mount Version