

DESCRIPTION


The sidac is a silicon bilateral voltage triggered switch with greater power-handling capabilities than standard diacs. Upon application of a voltage exceeding the sidac breakover voltage point, the sidac switches on through a negative resistance region to a low on-state voltage. Conduction continues until the current is interrupted or drops below the minimum holding current of the device.

FEATURES

- > Excellent capability of absorbing transient surge
- > Quick response to surge voltage(ns Level)
- > Glass-passivated junctions
- > High voltage lcmp ignitors

APPLICATIONS

- > High voltage lcmp ignitors
- > Natural gas ignitors
- > Gas oil ignitors
- > High-voltage power supplies
- > Xenon ignitors
- > Overvoltage protector
- > Pulse generators
- > Fluorescent lighting ignitors HID lighting ignitors




ABSOLUTE MAXIMUM RATINGS (T_A=25°C, RH=45%-75%, unless otherwise noted)

Parameter	Symbol	Value	Unit
Storage temperature range	T _{stg}	-40 to +125	°C
Operating junction temperature range	T _j	-40 to +125	°C
On-state RMS Current	I _T	1	A
Maximum surge on - state current non-repetitive one cycle peak value (50Hz)	I _{TSM}	16.7	A
Critical rate-of-rise of on-state current	di _T /dt	80	A



ELECTRICAL CHARACTERISTICS ($T_A=25\text{ }^{\circ}\text{C}$)

Symbol	Parameter
V_{DRM}	Peak off -state voltage
I_{DRM}	Off-state current
V_S	Switching voltage
I_S	Switching current
R_S	Switching resistance
V_T	On-state voltage
I_H	Holding current
V_{BO}	Breakover Voltage
I_{BO}	Breakover current

V-I Curve

ELECTRICAL CHARACTERISTICS ($T_A=25\text{ }^{\circ}\text{C}$, continued)

Part Number	$I_{\text{DRM}}@V_{\text{DRM}}$		V_{BO}		I_{BO}	$V_T@I_T=1\text{A}$	I_H	R_S	Marking
	μA	V	V		μA	V	mA	$k\Omega$	
	max	min	min	max	max	max	min	min	
SK0900G	1	70	80	97	50	2	10	0.1	DB090
SK1050G	1	90	95	113	50	2	10	0.1	DB105
SK1200G	1	100	110	125	50	2	10	0.1	DB120
SK1300G	1	110	120	138	50	2	10	0.1	DB130
SK1400G	1	120	130	146	50	2	10	0.1	DB140
SK1500G	1	130	140	170	50	2	10	0.1	DB150
SK1800G	1	160	170	195	50	2	10	0.1	DB180
SK2000G	1	180	190	215	50	2	10	0.1	DB200BW
SK2200G	1	190	205	230	50	2	10	0.1	DB220BW
SK2400G	1	200	220	250	50	2	10	0.1	DB240BW
SK2600G	1	220	240	270	50	2	10	0.1	DB260BW



SOLDERING PARAMETERS

Reflow Condition		Pb -Free assembly (see FIG. 2)
Pre Heat	-Temperature Min ($T_{s(min)}$)	+150 °C
	-Temperature Max($T_{s(max)}$)	+200 °C
	-Time (Min to Max) (t_s)	60-180 secs.
Average ramp up rate (Liquid us Temp (T_L) to peak)		3 °C/sec. Max
$T_{s(max)}$ to T_L - Ramp - up Rate		3 °C/sec. Max
Reflow	-Temperature(T_L) (Liquid us)	+217 °C
	-Temperature(t_L)	60-150 secs.
PeakTemp (T_p)		+260(+0/-5) °C
Time within 5 °C of actual PeakTemp (t_p)		8-15 secs.
Ramp - down Rate		6 °C/sec. Max
Time 25 °C to PeakTemp (T_p)		8 min. Max
Do not exceed		+260 °C

FIG.1: Maximum allowable ambient temperature versus On-state current




FIG.2: Reflow condition




FIG.3:Normalized Vs change vs. junction temperature





FIG.4:Normalized DC holding current vs. case temperature



PACKAGE MECHANICAL DATA

Ref.	Dimensions			
	Inches		Millimeters	
	Min.	Max.	Min.	Max.
A	1.000	-	25.40	-
B	0.228	0.300	5.80	7.62
C	0.027	0.035	0.69	0.89
D	0.118	0.140	3.00	3.60

ORDERING INFORMATION

Part Number	Case Type	Quantity	Packing Option
SKxxxxG	DO -15/DO -204AC	2000	Box

CONTACT US

Headquarters

A Building Caohejing I&E Park Pujiang Minhang Shanghai
China

Hotline

400-021-5756

Web

<http://www.semiware.com.cn>

By Telephone

General: 86-21-3463-7173

Sales: 86-21-3463-7172

Customer Service: 86-21-3463-7173-8810

Technical Support: 86-21-3463-7173-8805

By Email

Sales: sales08@semiware.com.cn

Customer Service: cs01@semiware.com.cn

Technical Support: fae01@semiware.com.cn

By Fax

General: 86-21-3965-0654

Sales: 86-21-3463-7458

COPYRIGHT ©Semiware 2009 - This literature is subject to all applicable copyright laws and is not for resale in any manner.

SPECIFICATIONS: Semiware reserves the right to change the electrical and or mechanical characteristics described herein without notice.

DESIGN CHANGES : Semiware reserves the right to discontinue product lines without notice and that the final judgement concerning selection and specifications is the buyer's and that in furnishing engineering and technical assistance.Semiware assumes no responsibility with respect to the selection or specifications of such products.Semiware makes no warranty, representation or guarantee regarding the suitability of its products for any particular purpose, nor does Semiware assume any liability arising out of the application or use of any product or circuit and specifically disclaims any and all liability without limitation special,consequential or incidental damages.

LIFE SUPPORT POLICY: Semiware products are not authorized for use in life support systems without written consent from the factory.

