


SK35DGD12T4Tp



SEMISTOP® 4 Press-Fit

3-phase bridge rectifier +
3-phase bridge inverter


SK35DGD12T4Tp

Features

- One screw mounting module
- Solder free mounting with Press-Fit terminals
- Fully compatible with other SEMISTOP® Press-Fit types
- Improved thermal performances by aluminium oxide substrate
- Trench4 IGBT technology
- CAL4F technology FWD
- Integrated NTC temperature sensor
- UL recognized, file no. E 63 532

Typical Applications*

- Motor drives



DGD-T


Absolute Maximum Ratings			
Symbol	Conditions	Values	Unit
IGBT 1			
V_{CES}	$T_j = 25\text{ °C}$	1200	V
I_C	$T_j = 150\text{ °C}$	$T_s = 25\text{ °C}$	46
		$T_s = 70\text{ °C}$	35
I_C	$T_j = 175\text{ °C}$	$T_s = 25\text{ °C}$	51
		$T_s = 70\text{ °C}$	41
I_{Cnom}		35	A
I_{CRM}	$I_{CRM} = 3 \times I_{Cnom}$	105	A
V_{GES}		-20 ... 20	V
t_{psc}	$V_{CC} = 800\text{ V}$ $V_{GE} \leq 15\text{ V}$ $V_{CES} \leq 1200\text{ V}$	$T_j = 150\text{ °C}$	10
T_j		-40 ... 175	°C

Absolute Maximum Ratings			
Symbol	Conditions	Values	Unit
Diode 1			
V_{RRM}	$T_j = 25\text{ °C}$	1600	V
I_F	$T_j = 150\text{ °C}$	$T_s = 25\text{ °C}$	52
		$T_s = 70\text{ °C}$	39
I_F	$T_j = 150\text{ °C}$	$T_s = 25\text{ °C}$	52
		$T_s = 70\text{ °C}$	39
I_{Fnom}		35	A
I_{FSM}	10 ms sin 180°	$T_j = 25\text{ °C}$	370
		$T_j = 150\text{ °C}$	270
i^2t	10 ms, sin 180°, $T_j = 150\text{ °C}$	364	A ² s
T_j		-40 ... 150	°C

Absolute Maximum Ratings			
Symbol	Conditions	Values	Unit
Diode 2			
V_{RRM}	$T_j = 25\text{ °C}$	1200	V
I_F	$T_j = 150\text{ °C}$	$T_s = 25\text{ °C}$	39
		$T_s = 70\text{ °C}$	30
I_F	$T_j = 175\text{ °C}$	$T_s = 25\text{ °C}$	44
		$T_s = 70\text{ °C}$	35
I_{Fnom}		35	A
I_{FRM}	$I_{FRM} = 2 \times I_{Fnom}$	70	A
I_{FSM}	10 ms, sin 180°, $T_j = 150\text{ °C}$	170	A
T_j		-40 ... 175	°C

Absolute Maximum Ratings			
Symbol	Conditions	Values	Unit
Module			
$I_{t(RMS)}$	$T_{terminal} = 100\text{ °C}$, $T_s = 60\text{ °C}$, per pin	40	A
T_{stg}		-40 ... 125	°C
V_{isol}	AC, sinusoidal, t = 1 min	2500	V

SK35DGD12T4Tp



SEMISTOP® 4 Press-Fit

3-phase bridge rectifier + 3-phase bridge inverter

SK35DGD12T4Tp

Features


- One screw mounting module
- Solder free mounting with Press-Fit terminals
- Fully compatible with other SEMISTOP® Press-Fit types
- Improved thermal performances by aluminium oxide substrate
- Trench4 IGBT technology
- CAL4F technology FWD
- Integrated NTC temperature sensor
- UL recognized, file no. E 63 532

Typical Applications*

- Motor drives


Characteristics						
Symbol	Conditions		min.	typ.	max.	Unit
IGBT 1						
$V_{CE(sat)}$	$I_C = 35\text{ A}$ $V_{GE} = 15\text{ V}$ chiplevel	$T_j = 25\text{ °C}$	1.85	2.10		V
		$T_j = 150\text{ °C}$	2.25	2.45		V
V_{CE0}	chiplevel	$T_j = 25\text{ °C}$	0.80	0.90		V
		$T_j = 150\text{ °C}$	0.70	0.80		V
r_{CE}	$V_{GE} = 15\text{ V}$ chiplevel	$T_j = 25\text{ °C}$	30	34		mΩ
		$T_j = 150\text{ °C}$	44	47		mΩ
$V_{GE(th)}$	$V_{GE} = V_{CE}, I_C = 1.2\text{ mA}$		5	5.8	6.5	V
I_{CES}	$V_{GE} = 0\text{ V}$ $V_{CE} = 1200\text{ V}$	$T_j = 25\text{ °C}$	-		1	mA
			-			mA
C_{ies}	$V_{CE} = 25\text{ V}$ $V_{GE} = 0\text{ V}$	$f = 1\text{ MHz}$		1.95		nF
C_{oes}		$f = 1\text{ MHz}$		0.155		nF
C_{res}		$f = 1\text{ MHz}$		0.115		nF
Q_G	$V_{GE} = -8V...+15V$			200		nC
R_{Gint}	$T_j = 25\text{ °C}$			0		Ω
$t_{d(on)}$	$V_{CC} = 600\text{ V}$	$T_j = 150\text{ °C}$		28		ns
t_r	$I_C = 35\text{ A}$	$T_j = 150\text{ °C}$		25		ns
E_{on}	$R_{G\ on} = 22\text{ Ω}$ $R_{G\ off} = 22\text{ Ω}$	$T_j = 150\text{ °C}$		3.27		mJ
$t_{d(off)}$	$di/dt_{on} = 2900\text{ A/μs}$	$T_j = 150\text{ °C}$		303		ns
t_f	$di/dt_{off} = 2900\text{ A/μs}$	$T_j = 150\text{ °C}$		70		ns
E_{off}	$V_{GE\ neg} = -15\text{ V}$ $V_{GE\ pos} = 15\text{ V}$	$T_j = 150\text{ °C}$		3.3		mJ
$R_{th(j-s)}$	per IGBT			0.9		K/W

Characteristics						
Symbol	Conditions		min.	typ.	max.	Unit
Diode 1						
V_F	$I_F = 35\text{ A}$	$T_j = 25\text{ °C}$		1.20	1.60	V
		chiplevel	$T_j = 125\text{ °C}$		1.19	1.56
V_{F0}	chiplevel	$T_j = 25\text{ °C}$		0.88	0.98	V
		$T_j = 125\text{ °C}$		0.73	0.83	V
r_F	chiplevel	$T_j = 25\text{ °C}$		9.2	18	mΩ
		$T_j = 125\text{ °C}$		13	21	mΩ
I_{RRM}	$I_F = 35\text{ A}$			-		A
Q_{rr}				-		μC
E_{rr}				-		mJ
$R_{th(j-s)}$	per Diode			1.25		K/W



DGD-T

SK35DGD12T4Tp



SEMITOP® 4 Press-Fit

3-phase bridge rectifier +
3-phase bridge inverter

SK35DGD12T4Tp

Features

- One screw mounting module
- Solder free mounting with Press-Fit terminals
- Fully compatible with other SEMITOP® Press-Fit types
- Improved thermal performances by aluminium oxide substrate
- Trench4 IGBT technology
- CAL4F technology FWD
- Integrated NTC temperature sensor
- UL recognized, file no. E 63 532


Typical Applications*

- Motor drives

Characteristics						
Symbol	Conditions		min.	typ.	max.	Unit
Diode 2						
V_F	$I_F = 35\text{ A}$	$T_j = 25\text{ °C}$		2.30	2.62	V
		chipelevel	$T_j = 150\text{ °C}$	2.29	2.62	V
V_{F0}	chipelevel	$T_j = 25\text{ °C}$		1.30	1.50	V
		$T_j = 150\text{ °C}$		0.90	1.10	V
r_F	chipelevel	$T_j = 25\text{ °C}$		29	32	mΩ
		$T_j = 150\text{ °C}$		40	43	mΩ
I_{RRM}	$I_F = 35\text{ A}$	$T_j = 150\text{ °C}$		30		A
Q_{rr}	$di/dt_{off} = 2900\text{ A/}\mu\text{s}$	$T_j = 150\text{ °C}$		2		μC
E_{rr}	$V_{GE} = -15\text{ V}$	$T_j = 150\text{ °C}$		1.46		mJ
$R_{th(j-s)}$	per Diode			1.2		K/W

Characteristics						
Symbol	Conditions		min.	typ.	max.	Unit
Module						
M_s	to heatsink		2.5		2.75	Nm
w	weight			60		g

Characteristics						
Symbol	Conditions		min.	typ.	max.	Unit
Temperature Sensor						
R_{100}	$T_r = 100\text{ °C}$			$493 \pm 5\%$		Ω
$B_{100/125}$	$R_{(T)} = R_{100} \exp[B_{100/125}(1/T - 1/T_{100})]$; T[K];			$3550 \pm 2\%$		K



DGD-T




Fig. 1 : Typ. Diode1 forward characteristic, incl. $R_{CC'+EE'}$




Fig. 2: Typ. IGBT output characteristic, incl. $R_{CC'+EE'}$




Fig. 3: Rated IGBT current vs. temperature $I_c = f(T_s)$




Fig. 4: Typ. turn-on /-off energy = $f(I_c)$




Fig. 5: Typ. turn-on /-off energy = $f(R_G)$




Fig.6: Typ. transfer characteristic




Fig. 7: Typ. IGBT gate charge characteristic




Fig. 8: Typ. switching times vs. I_C




Fig. 9: Typ. switching times vs. gate resistor R_G




Fig. 10: Transient thermal impedance vs. time





Fig. 11: Typ. CAL diode2 forward charact., incl. $R_{CC+EE'}$

SK35DGD12T4Tp

dimensions in mm
tolerance system: ISO 2768-m




Suggested drilled hole diameter for terminal pins in the circuit board:

- minimum: 1.575mm
- typical: 1.6mm
- maximum: 1.625mm

Suggested hole diameter for the mounting pins in the circuit board: 3.6mm

These documents are SEMIKRON properties. SEMIKRON reserves all copyrights.
All copying and transmitting of this information requires written permission.
For the case of industrial property rights, SEMIKRON reserves all rights.

SEMITOP 4 Press-Fit



DGD-T

This is an electrostatic discharge sensitive device (ESDS), international standard IEC 60747-1, chapter IX.

***IMPORTANT INFORMATION AND WARNINGS**

The specifications of SEMIKRON products may not be considered as guarantee or assurance of product characteristics ("Beschaffenheitsgarantie"). The specifications of SEMIKRON products describe only the usual characteristics of products to be expected in typical applications, which may still vary depending on the specific application. Therefore, products must be tested for the respective application in advance. Application adjustments may be necessary. The user of SEMIKRON products is responsible for the safety of their applications embedding SEMIKRON products and must take adequate safety measures to prevent the applications from causing a physical injury, fire or other problem if any of SEMIKRON products become faulty. The user is responsible to make sure that the application design is compliant with all applicable laws, regulations, norms and standards. Except as otherwise explicitly approved by SEMIKRON in a written document signed by authorized representatives of SEMIKRON, SEMIKRON products may not be used in any applications where a failure of the product or any consequences of the use thereof can reasonably be expected to result in personal injury. No representation or warranty is given and no liability is assumed with respect to the accuracy, completeness and/or use of any information herein, including without limitation, warranties of non-infringement of intellectual property rights of any third party. SEMIKRON does not assume any liability arising out of the applications or use of any product; neither does it convey any license under its patent rights, copyrights, trade secrets or other intellectual property rights, nor the rights of others. SEMIKRON makes no representation or warranty of non-infringement or alleged non-infringement of intellectual property rights of any third party which may arise from applications. Due to technical requirements our products may contain dangerous substances. For information on the types in question please contact the nearest SEMIKRON sales office. This document supersedes and replaces all information previously supplied and may be superseded by updates. SEMIKRON reserves the right to make changes.