

# SK 55 B 06 F



SEMITOP® 2

## Bridge Rectifier

### SK 55 B 06 F


Preliminary Data

#### Features

- Compact design
- One screw mounting
- Heat transfer and insulation through direct copper bonded aluminium oxide ceramic (DCB)
- Fast and soft recovery CAL (Controlled Axial Lifetime) diode
- UL recognized, file no. E 63 532

#### Typical Applications

- General power switching applications
- UPS
- SMPS



B

$V_{RSM}$ V	$V_{RRM}, V_{DRM}$ V	$I_D = 54$ A (full conduction) ( $T_s = 80$ °C)
	600	SK 55 B 06 F

Symbol	Conditions	Values	Units
$I_D$	$T_s = 80$ °C	54	A
$I_{RRM}$	$T_{vj} = 125$ °C (See Fig. 6)	30	A
$Q_{rr}$	$T_{vj} = 25$ (125) °C (See Fig. 6)	typ. 1 (3)	μC
$I_R$	$T_{vj} = 25$ (125) °C; $V_R = V_{RRM}$	0,1 (4)	mA
$I_{FSM}$	$T_{vj} = 150$ °C; 10 ms	440	A
$i^2t$	$T_{vj} =$ °C; ms	970	A <sup>2</sup> s
	$T_{vj} = 150$ °C; 10 ms		A <sup>2</sup> s
	$T_{vj} =$ °C; ms		
$V_F$	$T_{vj} = 25$ °C; $I_F = 50$ A	max. 1,7	V
$V_{(TO)}$	$T_{vj} = 125$ °C	max. 0,9	V
$r_T$	$T_{vj} = 125$ °C	max. 16	mΩ
$I_{RD}$	$T_{vj} =$ °C; $V_{DD} = V_{DRM}$ ; $V_{RD} = V_{RRM}$		mA
			mA
$R_{th(j-s)}$	per diode	1,2	K/W
	per module	0,3	K/W
$T_{solder}$	terminals, 10s	260	°C
$T_{vj}$		-40...+150	°C
$T_{stg}$		-40...+125	°C
$V_{isol}$	a. c. 50 Hz; r.m.s.; 1 s / 1 min.	3000 ( 2500 )	V
$M_s$	mounting torque to heatsink	2	Nm
$M_t$			
m	approx. weight	19	g
Case	SEMITOP® 2	T 6	




Fig. 1 Power dissipation vs. Output current




Fig. 2 Surge overload current vs. time




Fig. 3 Forward characteristics of single diode




Fig. 4 Thermal transient impedance vs. time






Fig. 5 Typ. reverse recovery charge  $Q_{rr} = f(di_F/dt)$

**Measurement conditions for switching parameters:**

**$I_F = 50A$**   
 **$V_R = 300V$**   
 **$-di/dt = 500A/\mu s$**

Fig. 6

Dimensions in mm



This technical information specifies semiconductor devices but promises no characteristics. No warranty or guarantee expressed or implied is made regarding delivery, performance or suitability.