

■ Features


- Electrostatic discharge (ESD) test under IEC6100-4-2 standard >16KV(SKL12B~SKL16B). standard >10KV(SKL110B~SKL120B).
- Low profile surface mounted application in order to optimize board space.
- Low power loss, high efficiency.
- High current capability, low forward voltage drop.
- Ultra high-speed switching.
- Silicon epitaxial planar chip, metal silicon junction.
- Suffix "G" indicates Halogen-free part, ex.SKL12BG.
- Lead-free parts meet environmental standards of MIL-STD-19500 /228

■ Mechanical data

- Epoxy:UL94-V0 rated flame retardant
- Case : Molded plastic, DO-214AA / SMB
- Terminals : Solder plated, solderable per MIL-STD-750, Method 2026
- Polarity : Indicated by cathode band
- Weight : 0.003 ounce, 0.091 gram

■ Outline

SMB(DO-214AA)



Dimensions in inches and (millimeters)

■ Maximum ratings and electrical characteristics

Rating at 25°C ambient temperature unless otherwise specified. Single phase, half wave, 60Hz, resistive or inductive load. For capacitive load, derate current by 20%.

| Parameter | Conditions | Symbol | MIN. | TYP. | MAX. | UNIT |
|----------------------------|--|-----------|------|------|------|------|
| Forward rectified current | See Fig.1 | I_o | | | 1.0 | A |
| Forward surge current | 8.3ms single half sine-wave superimposed on rate load (JEDEC method) | I_{FSM} | | | 50 | A |
| Reverse current | $V_R = V_{RRM}$ $T_A = 25^\circ\text{C}$ | I_R | | | 0.5 | mA |
| | $V_R = V_{RRM}$ $T_A = 100^\circ\text{C}$ | | | | 20 | |
| Diode junction capacitance | f=1MHz and applied 4V DC reverse voltage | C_j | | 120 | | pF |
| Thermal resistance | Junction to ambient | R_{BJA} | | 88 | | °C/W |
| Storage temperature | | T_{STG} | -55 | | +175 | °C |

| Symbol | Marking code | Max. repetitive peak reverse voltage V_{RRM} (V) | Max. RMS voltage V_{RMS} (V) | Max. DC blocking voltage V_R (V) | Max. forward voltage @1A, $T_A = 25^\circ\text{C}$ V_F (V) | Operating temperature T_J (°C) |
|---------|--------------|--|--------------------------------|------------------------------------|--|----------------------------------|
| SKL12B | KL12 | 20 | 14 | 20 | 0.40 | -50 ~ +150 |
| SKL14B | KL14 | 40 | 28 | 40 | 0.45 | |
| SKL16B | KL16 | 60 | 42 | 60 | 0.55 | |
| SKL110B | KL110 | 100 | 70 | 100 | 0.75 | |
| SKL115B | KL115 | 150 | 105 | 150 | 0.82 | -50 ~ +175 |
| SKL120B | KL120 | 200 | 140 | 200 | 0.85 | |

Rating and characteristic curves

FIG.1-TYPICAL FORWARD CURRENT DERATING CURVE




FIG.2-TYPICAL FORWARD CHARACTERISTICS




FIG.3-MAXIMUM NON-REPETITIVE FORWARD SURGE CURRENT




FIG.5 - TYPICAL REVERSE CHARACTERISTICS






FIG.4-TYPICAL JUNCTION CAPACITANCE



■ SMB foot print



| A | B | C |
|--------------|--------------|--------------|
| 0.091 (2.30) | 0.098 (2.50) | 0.071 (1.80) |

Dimensions in inches and (millimeters)

- CITC reserves the right to make changes to this document and its products and specifications at any time without notice.
- Customers should obtain and confirm the latest product information and specifications before final design, purchase or use.
- CITC makes no warranty, representation or guarantee regarding the suitability of its products for any particular purpose, nor does CITC assume any liability for application assistance or customer product design.
- CITC does not warrant or accept any liability with products which are purchased or used for any unintended or unauthorized application.
- No license is granted by implication or otherwise under any intellectual property rights of CITC.
- CITC products are not authorized for use as critical components in life support devices or systems without express written approval of CITC.