

SKN 600, SKR 600



Stud Diode

V_{RSM} V	V_{RRM} V	$I_{FRMS} = 950$ A (maximum value for continuous operation) $I_{FAV} = 600$ A (sin. 180; $T_c = 105$ °C)	
400	400	SKN 600/04	SKR 600/04
800	800	SKN 600/08	SKR 600/08
1200	1200	SKN 600/12	SKR 600/12
1600	1600	SKN 600/16	SKR 600/16

Rectifier Diode

SKN 600
SKR 600

Features

- Reverse voltages up to 1600 V
- Hermetic metal cases with glass insulator
- Threaded stud M24 x 1,5 mm (3/4 16 UNF 2A and M20 x 1,5 mm available)²⁾
- Optional silicone sleeve (red for SKN and blue for SKR)
- **SKN**: anode to stud
- **SKR**: cathode to stud

Typical Applications *

- All purpose high power rectifier diodes
- Cooling via heatsinks
- Non-controllable and half-controllable rectifiers
- Free-wheeling diodes
- Recommended snubber network:
RC: 1,0 μ F, 20 Ω ($P_R = 2$ W),
 R_p : 25 K Ω ($P_R = 20$ W)

1) Mounting with grease-like thermal compound or joint contact compound

2) M24x1,5 is standard; "UNF" should be added in description for 3/4 - 16 UNF 2A thread, while "M20" should be added in description for M20x1,5 thread

Symbol	Condition	Values	Units
I_{FAV}	sin. 180 ; $T_c = 105$ (125) °C	600 (475)	A
I_{FSM}	$T_{vj} = 25^\circ$ C ; 10 ms $T_{vj} = 180^\circ$ C ; 10 ms	14000 12000	A A
i^2t	$T_{vj} = 25^\circ$ C ; 8,3...10 ms $T_{vj} = 180^\circ$ C ; 8,3...10 ms	980000 720000	A ² s A ² s
V_F $V_{(TO)}$ r_T I_{RD} Q_{rr}	$T_{vj} = 25^\circ$ C, $I_F = 1500$ A $T_{vj} = 180^\circ$ C $T_{vj} = 180^\circ$ C $T_{vj} = 180^\circ$ C ; $V_R = V_{RRM}$ $T_{vj} = 160^\circ$ C, $-di_F/dt = 10$ A/ μ s	max. 1,33 max. 0,8 max. 0,3 max. 100 typ. 330	V V m Ω mA μ C
$R_{th(i-c)}$ $R_{th(c-s)}$ T_{vj} T_{stg}		0,1 0,015 -40...+180 -55...+180	K/W K/W °C °C
V_{isol} M_s a m	M24 x 1,5mm (lubricated) ¹⁾ 3/4 – 16 UNF (lubricated) ¹⁾ M20 x 1,5mm (lubricated) ¹⁾ approx.	- 60 (48) 30 (24) 40 (32) 5 * 9,81 500	V~ Nm Nm Nm m/s ² g
Case		E16	









SKN



SKR

SKN 600, SKR 600





Case E16 (IEC 60191: A 22 B)

*IMPORTANT INFORMATION AND WARNINGS

The specifications of SEMİKRON products may not be considered as guarantee or assurance of product characteristics ("Beschaffenheitsgarantie"). The specifications of SEMİKRON products describe only the usual characteristics of products to be expected in typical applications, which may still vary depending on the specific application. Therefore, products must be tested for the respective application in advance. Application adjustments may be necessary. The user of SEMİKRON products is responsible for the safety of their applications embedding SEMİKRON products and must take adequate safety measures to prevent the applications from causing a physical injury, fire or other problem if any of SEMİKRON products become faulty. The user is responsible to make sure that the application design is compliant with all applicable laws, regulations, norms and standards. Except as otherwise explicitly approved by SEMİKRON in a written document signed by authorized representatives of SEMİKRON, SEMİKRON products may not be used in any applications where a failure of the product or any consequences of the use thereof can reasonably be expected to result in personal injury. No representation or warranty is given and no liability is assumed with respect to the accuracy, completeness and/or use of any information herein, including without limitation, warranties of non-infringement of intellectual property rights of any third party. SEMİKRON does not assume any liability arising out of the applications or use of any product; neither does it convey any license under its patent rights, copyrights, trade secrets or other intellectual property rights, nor the rights of others. SEMİKRON makes no representation or warranty of non-infringement or alleged noninfringement of intellectual property rights of any third party which may arise from applications. Due to technical requirements our products may contain dangerous substances. For information on the types in question please contact the nearest SEMİKRON sales office. This document supersedes and replaces all information previously supplied and may be superseded by updates. SEMİKRON reserves the right to make changes.