


SKiIP39MLIB12F4V1



MiniSKiIP® 3

IGBT module

SKiIP39MLIB12F4V1

Target Data

Features


- Robust and soft freewheeling diodes in CAL technology for outer IGBTs
- Highly efficient rectifier diodes for inner IGBTs
- CAL diodes in neutral clamping path
- Highly reliable spring contacts for electrical connections
- 1200V Trench4 Fast technology in outer position
- 1200V Trench4 technology in inner position
- Integrated NTC temperature sensor
- UL recognized, file no. E63532

Typical Applications

- UPS
- Solar
- Suitable for NPC 3-level configuration featuring 1500V_{DC} bus

Remarks*


- IGBT1: outer IGBT of NPC configuration assembly T1/T4
- IGBT2: inner IGBT of NPC configuration assembly T2/T3
- Diode1: antiparallel diode of IGBT1 D1/D4
- Diode2: antiparallel diode of IGBT2 D2/D3
- Diode5: CAL clamping diode of NPC configuration assembly D5/D6



MLIB

Absolute Maximum Ratings			
Symbol	Conditions	Values	Unit
IGBT1			
V _{CES}	T _j = 25 °C	1200	V
I _C	T _j = 175 °C	T _s = 25 °C	409
		T _s = 70 °C	328
I _{Cnom}		400	A
I _{CRM}	I _{CRM} = 3 × I _{Cnom}	1200	A
V _{GES}		-20 ... 20	V
t _{psc}	V _{CC} = 800 V, V _{GE} ≤ 15 V, T _j = 150 °C, V _{CES} ≤ 1200 V	10	µs
T _j		-40 ... 175	°C
IGBT2			
V _{CES}	T _j = 25 °C	1200	V
I _C	T _j = 175 °C	T _s = 25 °C	348
		T _s = 70 °C	282
I _{Cnom}		300	A
I _{CRM}	I _{CRM} = 3 × I _{Cnom}	900	A
V _{GES}		-20 ... 20	V
t _{psc}	V _{CC} = 800 V, V _{GE} ≤ 15 V, T _j = 150 °C, V _{CES} ≤ 1200 V	10	µs
T _j		-40 ... 175	°C
Diode1			
V _{R RM}	T _j = 25 °C	1200	V
I _F	T _j = 175 °C	T _s = 25 °C	193
		T _s = 70 °C	153
I _{Fnom}		200	A
I _{FRM}	I _{FRM} = 2 × I _{Fnom}	400	A
I _{FSM}	10 ms, sin 180°, T _j = 25 °C	990	A
T _j		-40 ... 175	°C
Diode2			
V _{R RM}	T _j = 25 °C	1200	V
I _F	T _j = 150 °C	T _s = 25 °C	241
		T _s = 70 °C	177
I _{Fnom}		150	A
I _{FRM}		-	A
I _{FSM}	10 ms, sin 180°, T _j = 25 °C	1800	A
T _j		-40 ... 150	°C
Diode5			
V _{R RM}	T _j = 25 °C	1200	V
I _F	T _j = 175 °C	T _s = 25 °C	320
		T _s = 70 °C	252
I _{Fnom}		375	A
I _{FRM}	I _{FRM} = 2 × I _{Fnom}	750	A
I _{FSM}	10 ms, sin 180°, T _j = 25 °C	1720	A
T _j		-40 ... 175	°C
Module			
I _{t(RMS)}	20 A per spring	t.b.d.	A
T _{stg}		-40 ... 125	°C
V _{isol}	AC sinus 50 Hz, t = 1 min	2500	V

SKiiP39MLIB12F4V1



MiniSKiiP® 3

IGBT module

SKiiP39MLIB12F4V1

Target Data

Features

- Robust and soft freewheeling diodes in CAL technology for outer IGBTs
- Highly efficient rectifier diodes for inner IGBTs
- CAL diodes in neutral clamping path
- Highly reliable spring contacts for electrical connections
- 1200V Trench4 Fast technology in outer position
- 1200V Trench4 technology in inner position
- Integrated NTC temperature sensor
- UL recognized, file no. E63532


Typical Applications

- UPS
- Solar
- Suitable for NPC 3-level configuration featuring 1500V_{DC} bus

Remarks*


- IGBT1: outer IGBT of NPC configuration assembly T1/T4
- IGBT2: inner IGBT of NPC configuration assembly T2/T3
- Diode1: antiparallel diode of IGBT1 D1/D4
- Diode2: antiparallel diode of IGBT2 D2/D3
- Diode5: CAL clamping diode of NPC configuration assembly D5/D6

Characteristics						
Symbol	Conditions		min.	typ.	max.	Unit
IGBT1						
V _{CE(sat)}	I _C = 400 A V _{GE} = 15 V chipelevel	T _J = 25 °C		2.05	2.42	V
		T _J = 150 °C		2.59	2.96	V
V _{CE0}	chipelevel	T _J = 25 °C		1.10	1.28	V
		T _J = 150 °C		0.95	1.13	V
r _{CE}	V _{GE} = 15 V chipelevel	T _J = 25 °C		2.4	2.9	mΩ
		T _J = 150 °C		4.1	4.6	mΩ
V _{GE(th)}	V _{GE} = V _{CE} , I _C = 15.2 mA		5.2	5.8	6.4	V
I _{CES}	V _{GE} = 0 V, V _{CE} = 1200 V, T _J = 25 °C				0.3	mA
C _{ies}	V _{CE} = 25 V V _{GE} = 0 V	f = 1 MHz		24.60		nF
C _{oes}		f = 1 MHz		1.62		nF
C _{res}		f = 1 MHz		1.38		nF
Q _G	V _{GE} = -8 V ... +15 V			2268		nC
R _{Gint}	T _J = 25 °C			0		Ω
t _{d(on)}	V _{CE} = 600 V	T _J = 150 °C		-		ns
t _r	I _C = 400 A	T _J = 150 °C		-		ns
E _{on}	V _{GE} = +15/-15 V	T _J = 150 °C		-		mJ
t _{d(off)}		T _J = 150 °C		-		ns
t _f		T _J = 150 °C		-		ns
E _{off}		T _J = 150 °C		-		mJ
R _{th(j-s)}	per IGBT, λ _{paste} =0.8 W/(K*m)			0.118		K/W
IGBT2						
V _{CE(sat)}	I _C = 300 A V _{GE} = 15 V chipelevel	T _J = 25 °C		1.80	2.05	V
		T _J = 150 °C		2.20	2.40	V
V _{CE0}	chipelevel	T _J = 25 °C		0.80	0.90	V
		T _J = 150 °C		0.70	0.80	V
r _{CE}	V _{GE} = 15 V chipelevel	T _J = 25 °C		3.3	3.8	mΩ
		T _J = 150 °C		5.0	5.3	mΩ
V _{GE(th)}	V _{GE} = V _{CE} , I _C = 11.4 mA		5	5.8	6.5	V
I _{CES}	V _{GE} = 0 V, V _{CE} = 1200 V, T _J = 25 °C				0.6	mA
C _{ies}	V _{CE} = 25 V V _{GE} = 0 V	f = 1 MHz		18.45		nF
C _{oes}		f = 1 MHz		1.22		nF
C _{res}		f = 1 MHz		1.04		nF
Q _G	V _{GE} = - 8 V...+ 15 V			1695		nC
R _{Gint}	T _J = 25 °C			2.5		Ω
t _{d(on)}	V _{CE} = 600 V	T _J = 150 °C		-		ns
t _r	I _C = 300 A	T _J = 150 °C		-		ns
E _{on}	V _{GE} = +15/-15 V	T _J = 150 °C		-		mJ
t _{d(off)}		T _J = 150 °C		-		ns
t _f		T _J = 150 °C		-		ns
E _{off}		T _J = 150 °C		-		mJ
R _{th(j-s)}	per IGBT, λ _{paste} =0.8 W/(K*m)			0.157		K/W



MLIB

SKiIP39MLIB12F4V1



MiniSKiIP® 3

IGBT module

SKiIP39MLIB12F4V1

Target Data

Features

- Robust and soft freewheeling diodes in CAL technology for outer IGBTs
- Highly efficient rectifier diodes for inner IGBTs
- CAL diodes in neutral clamping path
- Highly reliable spring contacts for electrical connections
- 1200V Trench4 Fast technology in outer position
- 1200V Trench4 technology in inner position
- Integrated NTC temperature sensor
- UL recognized, file no. E63532


Typical Applications

- UPS
- Solar
- Suitable for NPC 3-level configuration featuring 1500V_{DC} bus

Remarks*


- IGBT1: outer IGBT of NPC configuration assembly T1/T4
- IGBT2: inner IGBT of NPC configuration assembly T2/T3
- Diode1: antiparallel diode of IGBT1 D1/D4
- Diode2: antiparallel diode of IGBT2 D2/D3
- Diode5: CAL clamping diode of NPC configuration assembly D5/D6

Characteristics			min.	typ.	max.	Unit
Symbol	Conditions					
Diode1						
$V_F = V_{EC}$	$I_F = 200\text{ A}$ $V_{GE} = 0\text{ V}$ chipelevel	$T_j = 25\text{ °C}$		2.20	2.52	V
		$T_j = 150\text{ °C}$		2.15	2.47	V
V_{F0}	chipelevel	$T_j = 25\text{ °C}$		1.30	1.50	V
		$T_j = 150\text{ °C}$		0.90	1.10	V
r_F	chipelevel	$T_j = 25\text{ °C}$		4.5	5.1	mΩ
		$T_j = 150\text{ °C}$		6.3	6.9	mΩ
I_{RRM}	$I_F = 200\text{ A}$	$T_j = 150\text{ °C}$		-	-	A
Q_{rr}	$V_R = 600\text{ V}$	$T_j = 150\text{ °C}$		-	-	μC
E_{rr}	$V_{GE} = +15/-15\text{ V}$	$T_j = 150\text{ °C}$		-	-	mJ
$R_{th(j-s)}$	per Diode, $\lambda_{paste}=0.8\text{ W/(K}^*\text{m)}$			0.342	-	K/W
Diode2						
$V_F = V_{EC}$	$I_F = 150\text{ A}$ $V_{GE} = 0\text{ V}$ chipelevel	$T_j = 25\text{ °C}$		1.08	1.36	V
		$T_j = 125\text{ °C}$		1.01	1.28	V
V_{F0}	chipelevel	$T_j = 25\text{ °C}$		0.88	0.98	V
		$T_j = 125\text{ °C}$		0.73	0.83	V
r_F	chipelevel	$T_j = 25\text{ °C}$		1.33	2.6	mΩ
		$T_j = 125\text{ °C}$		1.89	3.0	mΩ
I_{RRM}	$I_F = 150\text{ A}$	$T_j = 150\text{ °C}$		-	-	A
Q_{rr}	$V_R = 600\text{ V}$	$T_j = 150\text{ °C}$		-	-	μC
$E_{rr} \text{ } ^{1)}$	$V_{GE} = +15/-15\text{ V}$	$T_j = 150\text{ °C}$		-	-	mJ
$R_{th(j-s)}$	per Diode, $\lambda_{paste}=0.8\text{ W/(K}^*\text{m)}$			0.336	-	K/W
Diode5						
$V_F = V_{EC}$	$I_F = 375\text{ A}$ $V_{GE} = 0\text{ V}$ chipelevel	$T_j = 25\text{ °C}$		2.17	2.49	V
		$T_j = 150\text{ °C}$		2.11	2.42	V
V_{F0}	chipelevel	$T_j = 25\text{ °C}$		1.30	1.50	V
		$T_j = 150\text{ °C}$		0.90	1.10	V
r_F	chipelevel	$T_j = 25\text{ °C}$		2.3	2.6	mΩ
		$T_j = 150\text{ °C}$		3.2	3.5	mΩ
I_{RRM}	$I_F = 150\text{ A}$					A
Q_{rr}	$V_R = 600\text{ V}$					μC
E_{rr}	$V_{GE} = +15/-15\text{ V}$					mJ
$R_{th(j-s)}$	per Diode, $\lambda_{paste}=0.8\text{ W/(K}^*\text{m)}$			0.227	-	K/W



MLIB

SKiP39MLIB12F4V1



MiniSKiP® 3

IGBT module

SKiP39MLIB12F4V1

Target Data

Features

- Robust and soft freewheeling diodes in CAL technology for outer IGBTs
- Highly efficient rectifier diodes for inner IGBTs
- CAL diodes in neutral clamping path
- Highly reliable spring contacts for electrical connections
- 1200V Trench4 Fast technology in outer position
- 1200V Trench4 technology in inner position
- Integrated NTC temperature sensor
- UL recognized, file no. E63532


Typical Applications

- UPS
- Solar
- Suitable for NPC 3-level configuration featuring 1500V_{DC} bus

Remarks*


- IGBT1: outer IGBT of NPC configuration assembly T1/T4
- IGBT2: inner IGBT of NPC configuration assembly T2/T3
- Diode1: antiparallel diode of IGBT1 D1/D4
- Diode2: antiparallel diode of IGBT2 D2/D3
- Diode5: CAL clamping diode of NPC configuration assembly D5/D6

Characteristics					
Symbol	Conditions	min.	typ.	max.	Unit
Module					
L _{SCE1}			-		nH
L _{SCE2}			-		nH
R _{CC'+EE'}			-		mΩ
	T _s = 25 °C		-		mΩ
M _s	to heat sink	2		2.5	Nm
M _t					Nm
	to heat sink				Nm
W			82		g
Temperature Sensor					
R ₁₀₀	T _c =100°C (R ₂₅ =5 kΩ)		493 ± 5%		Ω
B _{100/125}	R _(T) =R ₁₀₀ exp[B _{100/125} (1/T-1/T ₁₀₀)]; T[K];		3550 ± 2%		K



MLIB

SKiIP39MLIB12F4V1






For mounting please follow the assembly instruction

requirement for PCB Design:
The MiniSKiIP area shall be covered with a maximum of circuit paths. This ensures a uniform area pressure

measure: mm
tolerance: +/- 0,2


standard pressure part
pressure part is no part of MiniSKiIP Dual and must be ordered separately



Accessible for mounting of SMD (max. height 3.5) on PCB by customer. Except pressure areas and blocked areas!

requirement for PCB design:
The pressure pin areas and more than 80% of the pressure edge areas must be on the same level and covered with circuit path. This ensures a uniform area pressure.
measure: mm
tolerance: +/- 0,2

pinout, dimensions



pinout

This is an electrostatic discharge sensitive device (ESDS), international standard IEC 60747-1, chapter IX.

***IMPORTANT INFORMATION AND WARNINGS**

The specifications of SEMIKRON products may not be considered as guarantee or assurance of product characteristics ("Beschaffenheitsgarantie"). The specifications of SEMIKRON products describe only the usual characteristics of products to be expected in typical applications, which may still vary depending on the specific application. Therefore, products must be tested for the respective application in advance. Application adjustments may be necessary. The user of SEMIKRON products is responsible for the safety of their applications embedding SEMIKRON products and must take adequate safety measures to prevent the applications from causing a physical injury, fire or other problem if any of SEMIKRON products become faulty. The user is responsible to make sure that the application design is compliant with all applicable laws, regulations, norms and standards. Except as otherwise explicitly approved by SEMIKRON in a written document signed by authorized representatives of SEMIKRON, SEMIKRON products may not be used in any applications where a failure of the product or any consequences of the use thereof can reasonably be expected to result in personal injury. No representation or warranty is given and no liability is assumed with respect to the accuracy, completeness and/or use of any information herein, including without limitation, warranties of non-infringement of intellectual property rights of any third party. SEMIKRON does not assume any liability arising out of the applications or use of any product; neither does it convey any license under its patent rights, copyrights, trade secrets or other intellectual property rights, nor the rights of others. SEMIKRON makes no representation or warranty of non-infringement or alleged non-infringement of intellectual property rights of any third party which may arise from applications. Due to technical requirements our products may contain dangerous substances. For information on the types in question please contact the nearest SEMIKRON sales office. This document supersedes and replaces all information previously supplied and may be superseded by updates. SEMIKRON reserves the right to make changes.