


NEW!

Shielded Power Inductors – SLR1050



- Tight DCR tolerance for inductor-DCR-based current sensing circuits
- Three versions for optimal efficiency and accuracy
- Excellent current handling
- 10.2 × 7.0 × 4.95 mm surface mount package
- Designed for use in multi-phase VRM/VRD/EVRD regulators

Core material Ferrite

Weight 1.2 – 1.4 g

Environmental RoHS compliant, halogen free

Terminations RoHS compliant matte tin over nickel over copper.

Ambient temperature –40°C to +85°C with Irms current

Maximum part temperature +125°C (ambient + temp rise). [Derating](#).

Storage temperature Component: –40°C to +125°C.

Tape and reel packaging: –40°C to +80°C

Resistance to soldering heat Max three 40 second reflows at +260°C, parts cooled to room temperature between cycles

Moisture Sensitivity Level (MSL) 1 (unlimited floor life at <30°C / 85% relative humidity)

Failures in Time (FIT) / Mean Time Between Failures (MTBF)

38 per billion hours / 26,315,789 hours, calculated per Telcordia SR-332

Packaging 250/7" reel; 1000/13" reel; Plastic tape: 24 mm wide, 0.4 mm thick, 12 mm pocket spacing, 5.03 mm pocket depth

PCB washing Tested to MIL-STD-202 Method 215 plus an additional aqueous wash. See [Doc787 PCB Washing.pdf](#).

Part number ¹	Inductance ² ±10% (nH)	DCR (mOhms)	SRF typ (MHz)	Isat (A) ³			Irms (A) ⁴	
				at 25°C	at 100°C	at 125°C	20°C rise	40°C rise
Lowest DCR								
SLR1050A-850KE_	85	0.39 ±7.7%	210	86	68.0	60.5	56.7	77.1
SLR1050A-101KE_	100	0.39 ±7.7%	200	78	61.5	55.0	56.7	77.1
SLR1050A-121KE_	120	0.39 ±7.7%	180	65	51.0	48.0	56.7	77.1
SLR1050A-151KE_	150	0.39 ±7.7%	90	51	38.0	36.0	56.7	77.1
SLR1050A-221KE_	220	0.39 ±7.7%	65	35	25.5	23.5	56.7	77.1
Balanced DCR/tolerance								
SLR1050B-850KE_	85	0.47 ±6.7%	210	86	68.0	60.5	48.8	67.2
SLR1050B-101KE_	100	0.47 ±6.7%	200	78	61.5	55.0	48.8	67.2
SLR1050B-121KE_	120	0.47 ±6.7%	180	65	51.0	48.0	48.8	67.2
SLR1050B-151KE_	150	0.47 ±6.7%	90	51	38.0	36.0	48.8	67.2
SLR1050B-221KE_	220	0.47 ±6.7%	65	35	25.5	23.5	48.8	67.2
Tightest DCR tolerance								
SLR1050C-850KE_	85	0.55 ±5.4%	210	86	68.0	60.5	46.7	65.0
SLR1050C-101KE_	100	0.55 ±5.4%	200	78	61.5	55.0	46.7	65.0
SLR1050C-121KE_	120	0.55 ±5.4%	180	65	51.0	48.0	46.7	65.0
SLR1050C-151KE_	150	0.55 ±5.4%	90	51	38.0	36.0	46.7	65.0
SLR1050C-221KE_	220	0.55 ±5.4%	65	35	25.5	23.5	46.7	65.0

1. When ordering, please specify **version** and **packaging** codes:

SLR1050C-221KEC

Version A = Lowest DCR; B = Balanced DCR/DCR tol;
C = Tightest DCR tolerance

Packaging: C = 7" machine-ready reel. EIA-481 embossed plastic tape (250 parts per full reel).

B = Less than full reel. In tape, but not machine ready. To have a leader and trailer added (\$25 charge), use code letter C instead.

D = 13" machine-ready reel. EIA-481 embossed plastic tape. Factory order only, not stocked (1000 parts per full reel).

2. Inductance at 100 kHz, 0.1 Vrms, 0 Adc.

3. DC current at 25°C that causes an inductance drop of 20% (typ) from its value without current. [Click for temperature derating information](#).

4. Current that causes the specified temperature rise from 25°C ambient. This information is for reference only and does not represent absolute maximum ratings. [Click for temperature derating information](#).

5. Electrical specifications at 25°C.

Refer to Doc 362 "Soldering Surface Mount Components" before soldering.

Irms Testing

Irms testing was performed on 0.75 inch wide × 0.25 inch thick copper traces in still air.

Temperature rise is highly dependent on many factors including pcb land pattern, trace size, and proximity to other components. Therefore temperature rise should be verified in application conditions.



www.coilcraft.com

US +1-847-639-6400 sales@coilcraft.com
UK +44-1236-730595 sales@coilcraft-europe.com
Taiwan +886-2-2264 3646 sales@coilcraft.com.tw
China +86-21-6218 8074 sales@coilcraft.com.cn
Singapore +65-6484 8412 sales@coilcraft.com.sg

Document 1255-1 Revised 02/09/16


© Coilcraft Inc. 2016

This product may not be used in medical or high risk applications without prior Coilcraft approval. Specification subject to change without notice. Please check web site for latest information.






NEW!

SLR1050 Shielded Power Inductors

L vs Current



L vs Frequency


www.coilcraft.com

US +1-847-639-6400 sales@coilcraft.com
UK +44-1236-730595 sales@coilcraft-europe.com
Taiwan +886-2-2264 3646 sales@coilcraft.com.tw
China +86-21-6218 8074 sales@coilcraft.com.cn
Singapore + 65-6484 8412 sales@coilcraft.com.sg

Document 1255-2 Revised 02/09/16





© Coilcraft Inc. 2016

This product may not be used in medical or high risk applications without prior Coilcraft approval. Specification subject to change without notice. Please check web site for latest information.

NEW!

SLR1050 Shielded Power Inductors

Typical Temperature Rise (from 25°C)



Dimensions are in $\frac{\text{inches}}{\text{mm}}$

Recommended Land Pattern

