

**SM520A****GENERAL PURPOSE RECTIFIER**


Rev.2.1

DESCRIPTION:

- ✧ Plastic package has underwriters laboratories flammability classification 94V-0
- ✧ For surface mounted applications in order to optimize board space
- ✧ Glass passivated chip junction
- ✧ Lead free in compliance with EU RoHS 2011/65/EU directive
- ✧ Low forward voltage drop
- ✧ Easy pick and place

MECHANICAL DATA

- ✧ Case: JEDEC DO-214AC Molded plastic
- ✧ Terminals: Solder plated, solderable per MIL-STD-750, method 2026
- ✧ Polarity: Color band denotes cathode end
- ✧ Weight: 0.0673 gram

**ABSOLUTE MAXIMUM RATING AND ELECTRICAL CHARACTERISTICS**

(Rating at 25°C ambient temperature unless otherwise specified.)

Parameter		Symbol	SM520A	Unit
Maximum repetitive peak reverse voltage		V_{RRM}	2000	V
Maximum non-repetitive peak reverse voltage		V_{RSM}	2100	V
Maximum RMS voltage		V_{RMS}	1400	V
Maximum DC blocking voltage		V_{DC}	2000	V
Maximum average forward current at $T_L=100^\circ\text{C}$		$I_{F(AV)}$	1	A
Peak forward surge current: 8.3ms single half sine-wave superimposed on rated load (JEDEC method)		I_{FSM}	30	A
Maximum forward voltage @ $I_F=1\text{A}$		V_F	1.15	V
Maximum DC reverse current at rated DC blocking voltage	$T_j=25^\circ\text{C}$	I_R	5	μA
	$T_j=150^\circ\text{C}$		400	μA
Typical junction capacitance $V_R=4.0\text{V}$, $f=1\text{MHz}$		C_J	8	pF
Operating junction and storage temperature range		T_j, T_{stg}	-60 to +150	$^\circ\text{C}$

THERMAL RESISTANCES

Symbol	Parameter	SM520A	Unit
$R_{th(j-a)}$	Junction to ambient (note1)	75	$^{\circ}\text{C/W}$

Note1: Thermal resistance from junction to ambient mounted on P.C.B. with 4.0 mm x 4.0 mm copper pad areas.

MARKING



SM	Surface Mount
5	$I_{F(AV)}=1\text{A}$
20	$V_{RRM}:2000\text{V}$
A	Chip size "A"


$\underline{x}H1$: Month, 1、2、3 ~ 9、A、B、C

$3\underline{x}1$:

2018	2019	2020	2021	2022	2023	2024
H	I	J	K	L	M	N
2025	2026	2027	2028	2029	2030	...
O	P	Q	R	S	T	...

$3H\underline{x}$: Batch number


PACKAGE MECHANICAL DATA



DO-214AC (SMA)

Ref.	Dimensions			
	Millimeters		Inches	
	Min.	Max.	Min.	Max.
A	2.60	3.00	0.102	0.118
B	4.15	4.65	0.163	0.183
C	1.25	1.65	0.049	0.065
D	0.95	1.52	0.037	0.060
E	4.90	5.30	0.193	0.209
F	0.051	0.203	0.002	0.008
G	0.15	0.31	0.006	0.012
H	2.00	2.44	0.079	0.096
J	2.00		0.079	
K		2.30		0.091
L	1.80		0.071	

TAPE AND REEL SPECIFICATION-SMA



Ref.	Dimensions	
	Millimeters	Inches
A0	2.79 ± 0.3	0.110 ± 0.012
B0	5.33 ± 0.3	0.210 ± 0.012
C	330.0	13.0
D0	1.55 ± 0.1	0.061 ± 0.004
E	1.75 ± 0.2	0.069 ± 0.008
E1	13.3 ± 0.3	0.524 ± 0.012
F	5.5 ± 0.2	0.217 ± 0.008
P0	4.00 ± 0.2	0.157 ± 0.008
P1	4.00 ± 0.2	0.157 ± 0.008
P2	2.00 ± 0.2	0.079 ± 0.008
W	12.0 ± 0.2	0.472 ± 0.008
W1	15.7 ± 2.0	0.618 ± 0.079

OUTLINE	UNIT WEIGHT (g/PCS) typ.	REEL (PCS)	PER CARTON (PCS)	REEL DIAMETERS (mm)
TAPING	0.0673	7,500	120,000	330

CHARACTERISTICS CURVE

FIG.1: Typical forward characteristics (25°C)




FIG.2: Typical reverse characteristics




FIG.3: Maximum non-repetitive peak forward surge current





FIG.4: Forward current derating curve



Information furnished in this document is believed to be accurate and reliable. However, Jiangsu JieJie Microelectronics Co.,Ltd assumes no responsibility for the consequences of use without consideration for such information nor use beyond it.

Information mentioned in this document is subject to change without notice, apart from that when an agreement is signed, Jiangsu JieJie complies with the agreement.

Products and information provided in this document have no infringement of patents. Jiangsu JieJie assumes no responsibility for any infringement of other rights of third parties which may result from the use of such products and information.

This document is the 2.1st version which is made in 21-Mar.-2018. This document supersedes and replaces all information previously supplied.



is a registered trademark of Jiangsu JieJie Microelectronics Co.,Ltd.

Copyright ©2018 Jiangsu JieJie Microelectronics Co.,Ltd. Printed All rights reserved.