

Common-Drain Dual N-Channel MOSFET

DESCRIPTION

SMC8810 is the Dual N-Channel enhancement mode power field effect transistors are using trench DMOS technology. This advanced trench technology to provide excellent $R_{DS(ON)}$. These devices are well suited for high efficiency fast switching applications, low in-line power loss are needed in small outline surface mount package.

PART NUMBER INFORMATION

SMC 8810 W - TR G
 a b c d e

a : Company name.
 b : Product Serial number.
 c : Package code W:TSSOP-8
 d : Handling code TR:Tape&Reel
 e : Green produce code G:RoHS Compliant

FEATURES

$V_{DS} = 20V$, $I_D = 7.6A$

$R_{DS(ON)} = 14.0m\Omega(Typ.)@V_{GS}=4.5V$

$R_{DS(ON)} = 14.5m\Omega(Typ.)@V_{GS}=4.0V$

$R_{DS(ON)} = 15.5m\Omega(Typ.)@V_{GS}=3.2V$


$R_{DS(ON)} = 17.8m\Omega(Typ.)@V_{GS}=2.5V$

$R_{DS(ON)} = 24.5m\Omega(Typ.)@V_{GS}=1.8V$

- ◆ Super high density cell design for extremely low $R_{DS(ON)}$
- ◆ Exceptional on-resistance and Maximum DC current capability

APPLICATIONS

- ◆ Power Management in Notebook Computer
- ◆ Portable Equipment and Battery Powered.



TSSOP-8

ABSOLUTE MAXIMUM RATINGS ($T_A = 25^\circ C$ Unless otherwise noted)

Symbol	Parameter	Rating	Units
V_{DSS}	Drain-Source Voltage	20	V
V_{GSS}	Gate-Source Voltage	± 12	V
I_D	Continuous Drain Current	$T_A=25^\circ C$ $T_A=70^\circ C$	7.6 6.1 A A
I_{DM}	Pulsed Drain Current ^A	30	A
P_D	Power Dissipation ^B	$T_A=25^\circ C$ $T_A=70^\circ C$	1.4 0.9 W W
T_J	Operation Junction Temperature	-55/150	$^\circ C$
T_{STG}	Storage Temperature Range	-55/150	$^\circ C$

THERMAL RESISTANCE

Symbol	Parameter	Typ	Max	Units
$R_{\theta JA}$	Thermal Resistance Junction to Ambient ^B	$t \leq 10s$	90	$^\circ C/W$
	Thermal Resistance Junction to Ambient ^{BC}	Steady-State	120	

ELECTRICAL CHARACTERISTICS ($T_A = 25^\circ\text{C}$ Unless otherwise noted)







Symbol	Parameter	Condition	Min	Typ	Max	Unit
Static Parameters						
BV _{DSS}	Drain-Source Breakdown Voltage	V _{GS} =0V, I _D =250μA	20			V
V _{GS(th)}	Gate Threshold Voltage	V _{DS} =V _{GS} , I _D =250μA	0.4	0.6	1.0	V
I _{GSS}	Gate Leakage Current	V _{DS} =0V, V _{GS} =±12V			±10	μA
I _{DSS}	Zero Gate Voltage Drain Current	V _{DS} =20V, V _{GS} =0V, T _J =25°C			1	μA
		V _{DS} =16V,V _{GS} =0V, T _J =75°C			10	
R _{DS(ON)}	Drain-source On-Resistance	V _{GS} =4.5V,I _D =7.6A		14	16	mΩ
		V _{GS} =4.0V,I _D =7.0A		14.5	17	
		V _{GS} =3.2V,I _D =6.5A		15.5	18	
		V _{GS} =2.5V,I _D =5.5A		17.8	21	
		V _{GS} =1.8V,I _D =4.0A		24.5	29	
G _{fs}	Forward Transconductance	V _{DS} =5V,I _D =8A		25		S
Diode Characteristics						
V _{SD}	Diode Forward Voltage	I _S =1A,V _{GS} =0V			1	V
I _S	Continuous Source Current				3.8	A
Dynamic Parameters						
Q _g	Total Gate Charge	V _{DS} =10V, V _{GS} =4.5V, I _D =7.6A		7	9.8	nC
Q _{gs}	Gate-Source Charge			0.6	0.8	
Q _{gd}	Gate-Drain Charge			2.2	3.1	
C _{iss}	Input Capacitance	V _{DS} =10V, V _{GS} =0V, f =1MHz		790		pF
C _{oss}	Output Capacitance			110		
C _{rss}	Reverse Transfer Capacitance			68		
t _{d(on)}	Turn-On Time	V _{DD} =10V, V _{GEN} =4.5V, R _G =6Ω, I _D =1A		5.4	10	nS
t _r				14	27	
t _{d(off)}	Turn-Off Time			18	34	
t _f				4	8	

Note: Absolute maximum ratings are those values beyond which the device could be permanently damaged.






- Pulsed width limited by maximum junction temperature, T_{J(MAX)}=150 $^\circ$ C.
- Measure the value in a still air environment at T_A=25 $^\circ$ C, using an installation mounted on a 1 in2 FR-4 board, maximum junction temperature T_{J(MAX)}=150 $^\circ$ C.
- T_{J(MAX)}=150 $^\circ$ C, using junction-to-case thermal resistance (R_{jc}) is more useful in additional heat sinking is used.

The products and product specifications contained herein are subject to change without notice to improve performance characteristics. Consult us, or our representatives before use, to confirm that the information in this datasheet is up to date. We assume no responsibility for any infringement of patents, patent rights, or other rights arising from the use of any information and circuitry in this datasheet.


TYPICAL CHARACTERISTICS



TYPICAL CHARACTERISTICS




Gate Chrgc Waveform



Switching Time Waveform

TSSOP-8 PACKAGE DIMENSIONS



Symbol	Dimensions In Millimeters		Dimensions In Inches	
	Min.	Max.	Min.	Max.
A		1.200		0.047
A1	0.050	0.150	0.002	0.006
A2	0.800	1.050	0.031	0.041
b	0.190	0.300	0.007	0.012
c	0.090	0.200	0.004	0.008
D	2.900	3.100	0.114	0.122
E	6.200	6.600	0.244	0.260
E1	4.300	4.500	0.169	0.177
e	0.650 REF		0.026 REF	
L	0.450	0.750	0.018	0.030
θ	0°	8°	0°	8°