


SWITCHING TYPE POWER SUPPLY APPLICATIONS.

## FEATURES

- Low Profile Surface Mount Package.
- Low Power Loss, High Efficiency.
- For Use in Low Voltage, High Frequency inverters, Free Wheeling, and Polarity Protection Applications.

## APPLICATION


- Switching Power Supply.
- DC/DC Converter.
- Home Appliances, Office Equipment.
- Telecommunication.
- Qualified to AEC-Q101.



## MAXIMUM RATING (Ta=25 °C)

CHARACTERISTIC	SYMBOL	RATING	UNIT
Maximum Repetitive Peak Reverse Voltage	$V_{RRM}$		V
Average Output Rectified Current	$I_O$		A
Peak One Cycle Surge Forward Current (Non-Repetitive 60Hz)	$I_{FSM}$	100	A
Junction Temperature	$T_j$	100 ~ 150	°C
Storage Temperature Range	$T_{stg}$	-40 ~ 150	°C

## Marking




## ELECTRICAL CHARACTERISTICS (Ta=25 °C)


CHARACTERISTIC	SYMBOL	TEST CONDITION	MIN.	TYP.	MAX.	UNIT
Peak Forward Voltage	$V_{FM}$	$I_{FM}=3A$	-	-	0.5	V
Repetitive Peak Reverse Current	$I_{RRM}$	$V_{RRM}$ =Rated, $T_j=25$	-	-	0.1	mA
		$V_{RRM}$ =Rated, $T_j=100$	-	-	10	mA
Total Capacitance	$C_T$	$V_R=4V$ , $f=1MHz$	-	-	250	pF
Thermal Resistance	$R_{th(j-l)}$	Junction to lead	-	-	10	/W
	$R_{th(j-a)}$	Junction to ambient	-	-	50	/W

# SMCB34


$I_F - V_F$




$P_F - I_F$



SURGE FORWARD CURRENT  
(NON-REPEATABLE)



$T_j - I_F$



$I_R - V_R$

