



**SMDJ****TVS****SURFACE MOUNT TRANSIENT
VOLTAGE SUPPRESSORS****DESCRIPTION**

The UTC **SMDJ** is a surface mount transient voltage suppressors, it uses UTC's advanced technology to provide customers with low leakage and very fast response time, etc.

FEATURES

- * Excellent clamping capability
- * Low leakage
- * Very fast response time

SYMBOL


SMC
(JEDEC DO-214AB)

ORDERING INFORMATION

Ordering Number		Package	Pin Assignment		Packing
Lead Free	Halogen Free		1	2	
SMDJXXAL-SMC-R	SMDJXXAG-SMC-R	SMC	K	A	Tape Reel

Note: Pin Assignment: K: Cathode A: Anode

SMDJXXAL-SMC-R	(1)Packing Type	(1) R: Tape Reel
	(2)Package Type	(2) SMC: SMC
	(3)Halogen Free	(3) L: Lead Free, G: Halogen Free
	(4)Category	(4) A: 5% uni-directional
	(5)Output Voltage Code	(5) xx: refer to ELECTRICAL CHARACTERISTICS

MARKING

■ **ABSOLUTE MAXIMUM RATING** ($T_A=25^{\circ}\text{C}$ unless otherwise noted)

PARAMETER	SYMBOL	RATINGS	UNIT
Peak Power Dissipation with a 10/1000 μs Waveform (Note 2)	P_{PP}	3000	W
Peak Pulse Current with a 10/1000 μs Waveform (Note 2)	I_{PP}	See ELECTRICAL CHARACTERISTICS Table	A
Power Dissipation On Infinite Heatsink at $T_L = 75^{\circ}\text{C}$	P_D	6.0	W
Peak Forward Surge Current, 8.3 ms Single Half Sine-wave Unidirectional Only (Note 3)	I_{FSM}	300	A
Maximum Instantaneous Forward Voltage at 50 A for Unidirectional Only (Note 4)	V_F	3.5/5.0	V
Operating Junction Temperature	T_J	-55 ~ +150	$^{\circ}\text{C}$
Storage Temperature	T_{STG}	-55 ~ +150	$^{\circ}\text{C}$

Notes: 1. Absolute maximum ratings are those values beyond which the device could be permanently damaged.

Absolute maximum ratings are stress ratings only and functional device operation is not implied.

2. Non-repetitive current pulse and derated above $T_A=25^{\circ}\text{C}$

3. Measured on 8.3ms single half sine-wave or equivalent square wave, duty cycle=4 pulses per minute maximum.

4. $V_F<3.5\text{V}$ for devices of $V_{BR}<200\text{V}$ and $V_F<5.0\text{V}$ for devices of $V_{BR}>201\text{V}$.

■ **ELECTRICAL CHARACTERISTICS** ($T_A=25^{\circ}\text{C}$, unless otherwise noted)

PART NUMBER (Uni)	BREAKDOWN VOLTAGE $V_{BR} @ I_T$			MAXIMUM REVERSE LEAKAGE I_R @ V_{RWM} (μA)	WORKING PEAK REVERSE VOLTAGE V_{RWM} (V)	MAXIMUM REVERSE SURGE CURRENT I_{PP} (A)	MAXIMUM CLAMPING VOLTAGE $V_C @ I_{PP}$ (V)
	MIN (V)	MAX (V)	I_T (mA)				
SMDJ24A	26.70	29.50	5	2	24.0	77.12	38.9
SMDJ28A	31.10	34.40	5	2	28.0	66.08	45
SMDJ33A	36.70	40.60	5	2	33.0	56.29	53.3

■ **TYPICAL CHARACTERISTICS** ($T_A = 25^\circ\text{C}$, unless otherwise noted)

Fig 1. Pulse Derating Curve




Fig 2. Maximum Non-Repetitive Surge Current




Fig 3. Steady State Power Derating Curve




Fig 4. Peak Pulse Power Rating Curve





Fig 5. Pulse Waveform



UTC assumes no responsibility for equipment failures that result from using products at values that exceed, even momentarily, rated values (such as maximum ratings, operating condition ranges, or other parameters) listed in products specifications of any and all UTC products described or contained herein. UTC products are not designed for use in life support appliances, devices or systems where malfunction of these products can be reasonably expected to result in personal injury. Reproduction in whole or in part is prohibited without the prior written consent of the copyright owner. The information presented in this document does not form part of any quotation or contract, is believed to be accurate and reliable and may be changed without notice.