

SWITCHING TYPE POWER SUPPLY APPLICATIONS.

FEATURES


- Low Profile Surface Mount Package.
- Low Power Loss, High Efficiency.
- Low Forward Voltage.

APPLICATION

- Switching Power Supply.
- Reversed Battery Connection Protection.
- DC/DC Converter.
- Cellular Phones.

MAXIMUM RATING (Ta=25 °C)

CHARACTERISTIC	SYMBOL	RATING	UNIT
Maximum Repetitive Peak Reverse Voltage	V_{RRM}	30	V
Average Output Rectified Current	I_{A}	2	A
Peak One Cycle Surge Forward Current (Non-Repetitive 60Hz)	I_{FSM}	33	A
Junction Temperature	T_j	40	°C
Storage Temperature Range	T_{stg}	-40 ~ 150	°C



Lot No. _____

Type Name **B23**

ELECTRICAL CHARACTERISTICS (Ta=25 °C)

CHARACTERISTIC	SYMBOL	TEST CONDITION	MIN.	TYP.	MAX.	UNIT
Peak Forward Voltage	V_{FM}	$I_{FM}=2A$	-	-	0.42	V
Repetitive Peak Reverse Current	I_{RRM}	V_{RRM} =Rated	-	-	1.0	mA
Thermal Resistance	$R_{th(j-l)}$	Junction to lead	-	-	20	/W
	$R_{th(j-a)}$	Junction to ambient (on a ceramic board)	-	-	70	
	$R_{th(j-a)}$	Junction to ambient (on a grass-epoxy board)	-	-	135	

SMFB23

