


FEATURES


- Drain-Source Withstand Voltage: 40V
- Max. $R_{DS(on)}$: 1.7m Ω @ $V_{GS}=10V$
- Automotive applications
- AEC-Q101 Qualified
- Excellent ON resistance
- General footprint package PDFN5 \times 6-8L
- 100% Rg and Avalanche tested


PRODUCT APPEARANCEPDFN5 \times 6-8L**DESCRIPTION**

The SNM041R7DNAQ is N-Channel enhancement MOS Field Effect Transistor. Uses advanced trench technology and design to provide excellent $R_{DS(ON)}$ with low gate charge. This device is suitable for use in high performance automotive DC-DC conversion, power switch and charging circuit. Standard Product SNM041R7DNAQ is in compliance with RoHS.

Applications:

- Automotive systems
- DC/DC converters
- Power supply converters circuit
- Load/Power Switching for portable device

PIN CONFIGURATION

MARKING


WLSI = Company (Group) Code
 04454 = Device Code
 DN = Special Code
 M = Month
 W = Week

LIMITING VALUES

Parameter	Symbol	Condition	Value	Unit
Drain-Source Voltage	V_{DS}		40	V
Gate-Source Voltage	V_{GS}		± 20	V
Continuous Drain Current ⁽⁴⁾	I_D	$T_C=25^{\circ}C$	189	A
		$T_C=100^{\circ}C$	133	A
Pulsed Drain Current ⁽³⁾	I_{DM}		513	A
Continuous Drain Current	I_D	$T_A=25^{\circ}C$	33	A
		$T_A=100^{\circ}C$	23	A
Avalanche Energy $L=0.3mH$	E_{AS}		342	mJ
Power Dissipation ⁽²⁾	P_D	$T_C=25^{\circ}C$	107	W
		$T_C=100^{\circ}C$	54	W
Power Dissipation ⁽¹⁾	P_D	$T_C=25^{\circ}C$	3.3	W
		$T_C=100^{\circ}C$	1.6	W
Operating Junction Temperature	T_J		-55 to 175	$^{\circ}C$
Storage Temperature Range	T_{STG}		-55 to 175	$^{\circ}C$

THERMAL RESISTANCE RATINGS

Single Operation					
Parameter		Symbol	Typical	Maximum	Unit
Junction-to-Ambient Thermal Resistance ⁽¹⁾	Steady State	R _{θJA}	38	45.6	°C/W
Junction-to-Case Thermal Resistance ⁽²⁾	Steady State	R _{θJC}	1.0	1.4	

ELECTRONICS CHARACTERISTICS

Parameter	Symbol	Conditions	Min	Typ	Max	Unit
OFF CHARACTERISTICS						
Drain-to-Source Breakdown Voltage	BV _{DSS}	V _{GS} =0 V, I _D = 250μA	40			V
Drain-to-Source Breakdown Voltage Temperature Coefficient	BV _{DSS} /T _J			17.8		mV/°C
Zero Gate Voltage Drain Current	I _{DSS}	V _{DS} =40V, V _{GS} = 0V, T _J =25°C			1	μA
		V _{DS} =40V, V _{GS} = 0V, T _J =125°C			100	μA
Gate-to-source Leakage Current	I _{GSS}	V _{DS} =0 V, V _{GS} = ±20V			±100	nA
ON CHARACTERISTICS						
Gate Threshold Voltage	V _{GS(TH)}	V _{GS} =V _{DS} , I _D = 250μA	2.4	3.0	3.6	V
Threshold Temperature Coefficient	V _{GS(TH)} /T _J			-7.7		mV/°C
Drain-to-source On-resistance ⁽⁴⁾	R _{DS(on)}	V _{GS} =10V, I _D =60A		1.35	1.7	mΩ
CHARGES, CAPACITANCES AND GATE RESISTANCE						
Input Capacitance	C _{ISS}	V _{GS} = 0V, f = 1.0MHz, V _{DS} =25 V		5206		pF
Output Capacitance	C _{OSS}			1297		
Reverse Transfer Capacitance	C _{RSS}			33		
Total Gate Charge ⁽⁵⁾	Q _{G(TOT)}	V _{GS} =10V, V _{DS} = 32V, I _D =60 A		64.3		nC
Gate-to-Source Charge ⁽⁵⁾	Q _{GS}			23.7		
Gate-to-Drain Charge ⁽⁵⁾	Q _{GD}			10.7		

Parameter	Symbol	Conditions	Min	Typ	Max	Unit
Gate Resistance	R_g	$f=1\text{MHz}$		1.1		Ω
SWITCHING CHARACTERISTICS ⁽⁵⁾						
Turn-On Delay Time	$t_d(\text{ON})$	$V_{GS}=10\text{V},$ $V_{DS}=32\text{V},$ $I_D=60\text{A}, R_G=5\Omega$		21.4		ns
Rise Time	t_r			80.4		
Turn-Off Delay Time	$t_d(\text{OFF})$			42.2		
Fall Time	t_f			35.4		
Body Diode Reverse Recovery Time	t_{rr}	$I_F=60\text{A},$ $dI/dt=100\text{A}/\mu\text{s}$		52.0		ns
Body Diode Reverse Recovery Charge	Q_{rr}	$I_F=60\text{A},$ $dI/dt=100\text{A}/\mu\text{s}$		65.8		nC
BODY DIODE CHARACTERISTICS						
Forward Voltage ⁽⁴⁾	V_{SD}	$V_{GS}=0\text{V}, I_S=60\text{A}$	0.5	0.8	1.2	V


($T_J=25^\circ\text{C}$, unless otherwise noted.)

Note:


- (1) FR-4 board ($38\text{mm} \times 38\text{mm} \times 1.6\text{mm}$, $70\mu\text{m}$ Copper) partially covered with copper (645mm^2 area). The power dissipation P_{DSM} is based on Junction-to-Ambient thermal resistance value and the $T_{J(\text{MAX})}=175^\circ\text{C}$. The value is only for reference, any application depends on the user's specific board design.
- (2) The power dissipation P_D is based on $T_{J(\text{MAX})}=175^\circ\text{C}$, using junction-to-case thermal resistance, and is more useful in setting the upper dissipation limit for cases where additional heat sinking is used.
- (3) Repetitive rating, pulsed, duty cycle $\sim 1\%$, keep initial $T_J=25^\circ\text{C}$, the maximum allowed junction temperature of 175°C .
- (4) The static characteristics are obtained using $\sim 380\mu\text{s}$ pulses, duty cycle $\sim 1\%$.
- (5) The parameter is not subject to production test – verified by design / characterization.

TYPICAL CHARACTERISTICS


Ta=25°C, unless otherwise noted.




Output Characteristics ⁽⁴⁾(4)




Transfer Characteristics ⁽⁴⁾




On-Resistance vs. Drain Current ⁽⁴⁾









On-Resistance vs. Gate-to-Source Voltage ⁽⁴⁾






On-Resistance vs. Junction Temperature ⁽⁴⁾







Threshold Voltage vs. Temperature





Capacitance

Body Diode Forward Voltage ⁽⁴⁾

Single Pulse power

Safe Operating Area

Gate Charge Characteristics

Drain Current vs. Drain Voltage


Avalanche characteristics

Transient Thermal Response (Junction-to-Case)

Transient Thermal Response (Junction-to-Ambient)

PDFN5×6-8L DIMENSIONS
PACKAGE SIZE

Symbol	Min.	Typ.	Max.
A	0.85	0.95	1.00
A1	0.00	-	0.05
A3	-	0.2 Ref	-
b	0.30	0.40	0.50
D	5.20BSC		
E	5.55BSC		
e	1.27 BSC		
D1	4.25	4.35	4.45
E1	5.95	6.05	6.15
E2	3.525	3.625	3.725
E3	1.175	1.275	1.375
L	0.45	0.55	0.65
L1	0	-	0.15
L2	0.68 Ref		
θ	0 °	-	10 °



TAPE AND REEL INFORMATION
Reel Dimensions

Tape Dimensions

Quadrant Assignments For PIN1 Orientation In Tape


User Direction of Feed

RD	Reel Dimension	<input type="checkbox"/> 7inch	<input checked="" type="checkbox"/> 13inch		
W	Overall width of the carrier tape	<input type="checkbox"/> 8mm	<input checked="" type="checkbox"/> 12mm		
P1	Pitch between successive cavity centers	<input type="checkbox"/> 2mm	<input type="checkbox"/> 4mm	<input checked="" type="checkbox"/> 8mm	
Pin1	Pin1 Quadrant	<input checked="" type="checkbox"/> Q1	<input type="checkbox"/> Q2	<input type="checkbox"/> Q3	<input type="checkbox"/> Q4

ORDERING INFORMATION

TYPE NUMBER	PACKAGE	PACKING
SNM041R7DNAQ-8/TR	PDFN5×6-8L	Tape and reel

PDFN5×6-8L is packed with 5000 pieces/disc in braided packaging.

Important statement

SIT reserves the right to change the above-mentioned information without prior notice.

Draft

REVISION HISTORY

Version number	Datasheet status	Revision date
V0.2	Draft version.	May 2024

Draft