

SNOA - SNOM

PRV : 50 - 1000 Volts

Io : 1.5 Amperes

FEATURES :

- * High current capability
- * High surge current capability
- * High reliability
- * Low reverse current
- * Low forward voltage drop
- * **Pb / RoHS Free**

MECHANICAL DATA :

- * Case : SMA Molded plastic
- * Epoxy : UL94V-O rate flame retardant
- * Lead : Lead Formed for Surface Mount
- * Polarity : Color band denotes cathode end
- * Mounting position : Any
- * Weight : 0.067 gram

MAXIMUM RATINGS AND ELECTRICAL CHARACTERISTICS

Rating at 25 °C ambient temperature unless otherwise specifie.

Single phase, half wave, 60 Hz, resistive or inductive load

For capacitive load, derate current by 20%


RATING	SYMBOL	SNOA	SNOB	SNOD	SNOE	SNOG	SNOH	SNOJ	SNOK	SNOM	UNIT
Maximum Repetitive Peak Reverse Voltage	V_{RRM}	50	100	200	300	400	500	600	800	1000	V
Maximum RMS Voltage	V_{RMS}	35	70	140	210	280	350	420	560	700	V
Maximum DC Blocking Voltage	V_{DC}	50	100	200	300	400	500	600	800	1000	V
Maximum Average Forward Current $T_a = 70^{\circ}C$	I_F	1.5									A
Peak Forward Surge Current 8.3ms Single half sine wave Superimposed on rated load (JEDEC Method)	I_{FSM}	50									A
Maximum Forward Voltage at $I_F = 1.5$ Amps.	V_F	1.1									V
Maximum DC Reverse Current $T_a = 25^{\circ}C$	I_R	5.0									μA
at rated DC Blocking Voltage $T_a = 100^{\circ}C$	$I_{R(H)}$	50									μA
Typical Junction Capacitance (Note1)	C_J	30									pF
Junction Temperature Range	T_J	- 65 to + 150									$^{\circ}C$
Storage Temperature Range	T_{STG}	- 65 to + 150									$^{\circ}C$

Note :

(1) Measured at 1.0 MHz and applied reverse voltage of 4.0 Vdc

SURFACE MOUNT RECTIFIERS

SMA (DO-214AC)



RATING AND CHARACTERISTIC CURVES (SNOA - SNOM)

FIG.1 - DERATING CURVE FOR OUTPUT RECTIFIED CURRENT




FIG.2 - MAXIMUM NON-REPETITIVE PEAK FORWARD SURGE CURRENT




FIG.3 - TYPICAL FORWARD CHARACTERISTICS




FIG.4 - TYPICAL REVERSE CHARACTERISTICS

