


SOD123W

Reel pack, SMD, 7" Q1/T1-Q2/T3 standard product orientation Orderable part number ending ,115 or X Ordering code (12NC) ending 115

Rev. 1 — 18 February 2015

Packing information

1. Packing method





Reel pack, SMD, 7"
Q1/T1-Q2/T3 standard product orientation
Orderable part number ending ,115 or X
Ordering code (12NC) ending 115


Table 1. Dimensions and quantities

Reel dimensions	SPQ/PQ		Outer box dimensions
d × w (mm) [1]	(pcs) [2]		I × w × h (mm)
180 × 8	3000	1	185 × 185 × 16

- [1] d = reel diameter; w = tape width.
- [2] Packing quantity dependent on specific product type.

 View ordering and availability details at NXP order portal, or contact your local NXP representative.

2. Product orientation



3. Carrier tape dimensions




Table 2. Carrier tape dimensions

In accordance with IEC 60286-3.

A ₀ (mm)	B ₀ (mm)	K ₀ (mm)	T (mm)	P ₁ (mm)	W (mm)
2.05 ± 0.1	3.72 ± 0.05	1.25 ± 0.1	0.3 ± 0.05	4 ± 0.1	8 ± 0.1

Reel pack, SMD, 7"
Q1/T1-Q2/T3 standard product orientation
Orderable part number ending ,115 or X
Ordering code (12NC) ending 115

4. Reel dimensions




Table 3. Reel dimensions In accordance with IEC 60286-3.

A [nom] (mm)	W2 [max] (mm)		•	D [min] (mm)
180	14.4	1.5	12.8	20.2

Reel pack, SMD, 7" Q1/T1-Q2/T3 standard product orientation Orderable part number ending ,115 or X Ordering code (12NC) ending 115

5. Barcode label






Table 4. Barcode label dimensions

	Reel barcode label I × w (mm)
100 × 75	36 × 75

Reel pack, SMD, 7"
Q1/T1-Q2/T3 standard product orientation
Orderable part number ending ,115 or X
Ordering code (12NC) ending 115

6. Revision history

Table 5. Revision history

Document ID	Release date	Packing document status	Change notice	Supersedes
SOD123W_115	20150218	Packing information	-	-