



GLASS PASSIVATED SILICON RECTIFIER

VOLTAGE 400 Volts CURRENT 8 Ampere

SPAC804F

FEATURES

- * Low leakage
- * Low forward voltage drop
- * High current capability
- * High surge capability
- * High reliability

MECHANICAL DATA


- * Case: Slim PAQ
- * Epoxy: Device has UL flammability classification 94V-O
- * Lead: MIL-STD-202E method 208C guaranteed
- * Mounting position: Any

MAXIMUM RATINGS AND ELECTRICAL CHARACTERISTICS

Ratings at 25 °C ambient temperature unless otherwise specified.
resistive or inductive load.



SlimPAQ



Dimensions in inches and (millimeters)

MAXIMUM RATINGS (@ TA=25 °C unless otherwise noted)

RATINGS	SYMBOL	SPAC804F	UNITS
Maximum Recurrent Peak Reverse Voltage	V_{RRM}	400	Volts
Maximum RMS Voltage	V_{RMS}	280	Volts
Maximum DC Blocking Voltage	V_{DC}	400	Volts
Maximum Average Forward Rectified Current at $T_C = 125^\circ\text{C}$	I_O	8	Amps
Peak Forward Surge Current 8.3 ms single half sine-wave superimposed on rated load (JEDEC method)	I_{FSM}	125	Amps
Typical Current Square Time	I^2T	64.8	A^2S
Typical Thermal Resistance (Note 1)	$R_{\theta JC}$	6.25	$^\circ\text{C/W}$
	$R_{\theta JA}$	12.5	
	$R_{\theta JL}$	3.1	
Typical Junction Capacitance (Note 2)	C_J	40	pF
Operating and Storage Temperature Range	T_J, T_{STG}	-55 to + 175	$^\circ\text{C}$

ELECTRICAL CHARACTERISTICS (@TA=25 °C unless otherwise noted)

CHARACTERISTICS	SYMBOL	SPAC804F	UNITS
Maximum Instantaneous Forward Voltage at 8 A DC	V_F	1.1	Volts
Maximum DC Reverse Current at Rated DC Blocking Voltage	@ $T_A = 25^\circ\text{C}$	10	μAmps
	@ $T_A = 100^\circ\text{C}$	100	

NOTES : 1. Thermal Resistance : Heat-sink case mounted or if PCB mounted.
 2. Measured at 1 MHz and applied reverse voltage of 4.0 volts.
 3. "Fully ROHS compliant", "100% Sn plating (Pb-free)".
 4. Suffix "R" for Reverse Polarity.
 5. Available in Halogen-free epoxy by adding suffix -HF after the part nbr.

2010-05
REV: B

RATING AND CHARACTERISTICS CURVES (SPAC804F)




FIG.1 TYPICAL FORWARD CURRENT DERATING CURVE




FIG.2 TYPICAL INSTANTANEOUS FORWARD CHARACTERISTICS




FIG.3 TYPICAL REVERSE CHARACTERISTICS




FIG.4 TYPICAL JUNCTION CAPACITANCE




FIG.5 MAXIMUM NON-REPETITIVE FORWARD SURGE CURRENT

DISCLAIMER NOTICE

Rectron Inc reserves the right to make changes without notice to any product specification herein, to make corrections, modifications, enhancements or other changes. Rectron Inc or anyone on its behalf assumes no responsibility or liability for any errors or inaccuracies. Data sheet specifications and its information contained are intended to provide a product description only. "Typical" parameters which may be included on RECTRON data sheets and/ or specifications can and do vary in different applications and actual performance may vary over time. Rectron Inc does not assume any liability arising out of the application or use of any product or circuit.

Rectron products are not designed, intended or authorized for use in medical, life-saving implant or other applications intended for life-sustaining or other related applications where a failure or malfunction of component or circuitry may directly or indirectly cause injury or threaten a life without expressed written approval of Rectron Inc. Customers using or selling Rectron components for use in such applications do so at their own risk and shall agree to fully indemnify Rectron Inc and its subsidiaries harmless against all claims, damages and expenditures.