


SPAL1210	Silicon Rectifier Diodes R-7 Package		Silicon Rectifier Diodes 12 Amperes 1000 Volts																													
Features <ul style="list-style-type: none"> • Low forward voltage drop. • High current capability • High surge capability • High reliability • Ideal for solar panel PV application such as By-Pass diode 		 <p>R-7</p> <p>COLOR BAND DENOTES CATHODE</p> <table border="1" data-bbox="1144 1024 1377 1096"> <thead> <tr> <th rowspan="2">DIM</th> <th colspan="2">INCHES</th> <th colspan="2">MILLIMETERS</th> </tr> <tr> <th>MIN</th> <th>MAX</th> <th>MIN</th> <th>MAX</th> </tr> </thead> <tbody> <tr> <td>A</td> <td>0.291</td> <td>0.299</td> <td>7.40</td> <td>7.60</td> </tr> <tr> <td>B</td> <td>0.311</td> <td>0.319</td> <td>7.90</td> <td>8.10</td> </tr> <tr> <td>D</td> <td>0.059</td> <td>0.063</td> <td>1.50</td> <td>1.60</td> </tr> <tr> <td>K</td> <td>1.000</td> <td>---</td> <td>25.40</td> <td>---</td> </tr> </tbody> </table>		DIM	INCHES		MILLIMETERS		MIN	MAX	MIN	MAX	A	0.291	0.299	7.40	7.60	B	0.311	0.319	7.90	8.10	D	0.059	0.063	1.50	1.60	K	1.000	---	25.40	---
DIM	INCHES		MILLIMETERS																													
	MIN	MAX	MIN	MAX																												
A	0.291	0.299	7.40	7.60																												
B	0.311	0.319	7.90	8.10																												
D	0.059	0.063	1.50	1.60																												
K	1.000	---	25.40	---																												
Mechanical Data <ul style="list-style-type: none"> • Cases: R-7 Axial-Leaded, Molded Plastic • Plastic package has Underwriters Laboratory Flammability Classification 94V-0 • Terminals : All Terminal Leads are Readily Solderable • Lead Temperature for Soldering Purposes: 260°C Max. for 10 Seconds • Weight : 2.10 grams 																																
Maximum Ratings and Electrical Characteristics (Ta = 25°C unless otherwise noted)																																
Parameter	Symbols	SPAL1210	Units																													
Maximum Repetitive Reverse Voltage	V_{RRM}	1000	Volts																													
Maximum RMS Voltage	V_{RMS}	700	Volts																													
Maximum DC Blocking Voltage	V_{DC}	1000	Volts																													
Maximum average forward rectified current (see Fig. 1)	$I_{(AV)}$	12.0	Amps																													
Non-repetitive Peak Forward Surge Current 8.3 ms Single Half-Sine-Wave	I_{FSM}	450.0	Amps																													
Maximum Instantaneous Forward Voltage @ 12A (Note 1)	V_F	1	Volts																													
Leakage current-Sperrstrom	Ta = 25°C	10	uA																													
	Ta = 100°C	100																														
Typical Thermal Resistance (Note 2)	$R_{\theta JA}$	9	°C/W																													
Storage Temperature Range	T_{stg}	-65 to +175	°C																													
Operating Junction Temperature	T_J	-50 to +175	°C																													

- Notes: 1. Pulse test with PW=300 usec, 1% duty cycle.
2. Leads are kept at ambient temperature at a distance of 10 mm from case.

Typical Characteristics




Figure 1. Forward Current Derating Curve




Figure 2. Forward Voltage Characteristics




Figure 3. Non-Repetitive Surge Current



Power Semiconductor Technology

SiPower Inc. Legal Notice

Disclaimer - All data and specifications are subject to changes without notice

SiPower Inc, it's affiliates, agents, distributors and employees neither accept nor assume any responsibility or liability for errors or inaccuracies. All data and specifications are intended for information and provide a product description only. Electrical and mechanical parameters listed in SiPower data sheets and specifications will vary dependent upon application and environmental conditions. SiPower is not liable for any damages occurred or resulting from any circuit, product or end-use application for which it's products are used. SiPower products are not intended or designed for use in life saving or sustaining apparatus and purchase of any SiPower products automatically indemnifies SiPower against any claims or damages resulting from application malfunction.

<http://www.sipower-inc.com>

SiPower - The official marketing arm of Zhonghuan Semiconductor