

TECHNICAL DATA
Data Sheet 4098, Rev. D

Three-Phase IGBT BRIDGE, With Gate Driver and Optical Isolation

DESCRIPTION: A 600 VOLT, 80 AMP, THREE PHASE IGBT BRIDGE

ELECTRICAL CHARACTERISTICS PER IGBT DEVICE

(T_j=25°C UNLESS OTHERWISE SPECIFIED)

PARAMETER	SYMBOL	MIN	TYP	MAX	UNIT
IGBT SPECIFICATIONS					
Collector to Emitter Breakdown Voltage I _C = 250 μA, V _{GE} = 0V	BV _{CES}	600	-	-	V
Continuous Collector Current T _C = 25 °C T _C = 90 °C	I _C	-	-	80 70	A
Pulsed Collector Current, 1mS	I _{CM}	-	-	170	A
Gate to Emitter Voltage	V _{GE}	-	-	+/-20	V
Gate-Emitter Leakage Current , V _{GE} = +/-20V	I _{GES}	-	-	+/- 100	nA
Zero Gate Voltage Collector Current V _{CE} = 600 V, V _{GE} =0V T _i =25°C V _{CE} = 480 V, V _{GE} =0V T _i =125°C	I _{CES}	-	-	1 10	mA mA
Collector to Emitter Saturation Voltage, I _C = 60A, V _{GE} = 15V, T _C = 25 °C	V _{CE(SAT)}	-	1.7	2.0	V
Maximum Thermal Resistance	R _{θJC}	-	-	0.45	°C/W
Brake IGBT SPECIFICATIONS					
Continuous Collector Current T _C = 25 °C T _C = 90 °C	I _C	-	-	40 25	A
Pulsed Collector Current, 0.5mS	I _{CM}	-	-	120	A
Brake Resistor SPECIFICATIONS					
Maximum Continuous power dissipation	Pd			2	watt
Impulse Energy				80	Joules
Maximum operating Junction Temperature	T _{Jmax}	-40	-	150	°C
Maximum Storage Junction Temperature	T _{Jmax}	-55	-	150	°C

SENSITRON

TECHNICAL DATA

Data Sheet 4098, Rev. D

Over-Temperature Shutdown					
Over-Temperature Shutdown	Tsd	100	110	120	°C
Over-Temperature Output	Tso		10		10mV/°C
Over-Temperature Shutdown Hysteresis			20		°C

ULTRAFAST DIODES RATING AND CHARACTERISTICS					
Diode Peak Inverse Voltage	PIV	600	-	-	V
Continuous Forward Current, $T_C = 90\text{ }^\circ\text{C}$	I_F	-	-	60	A
Forward Surge Current, $t_p = 10\text{ msec}$	I_{FSM}	-	-	300	A
Diode Forward Voltage, $I_F = 60\text{A}$	V_F	-	1.4	1.7	V
Diode Reverse Recovery Time ($I_F = 60\text{A}$, $V_{RR} = 300\text{V}$, $di/dt = 200\text{ A}/\mu\text{s}$)	t_{rr}	-	90	160	nsec
Maximum Thermal Resistance	$R_{\theta JC}$	-	-	0.8	°C/W
Gate Driver					
Supply Voltage	VCC	10	15	20	V
Input On Current	HIN, LIN	2		5.0	mA
Opto-Isolator Logic High Input Threshold	I_{th}	-	1.6	-	mA
Input Reverse Breakdown Voltage	BV_{in}	5.0	-	-	V
Input Forward Voltage @ $I_{in} = 5\text{mA}$	V_F	-	1.5	1.7	V
Under Voltage Lockout	VCCUV	11.5	-	12.5	V
ITRIP Reference Voltage ⁽¹⁾	Itrip-ref	2.9	3.0	3.1	V
Input-to-Output Turn On Delay	t_{ond}	-		800	nsec
Output Turn On Rise Time	t_r	-		100	
Input-to-Output Turn Off Delay	t_{offd}	-			
Output Turn Off Fall Time	t_f			1000	
@ VCC=300V, IC=50A, $T_C = 25$				100	
Input-Output Isolation Voltage	-	1000	-	-	V

(1) ITRIP Cycle-by cycle current limit is internally set to 70A peak. The set point can be lowered by connecting a resistor between Itrip-ref and Gnd. The set point can be increased by connecting a resistor between Itrip-ref and +5V ref

SENSITRON**TECHNICAL DATA****Data Sheet 4098, Rev. D****Pin Description**


Pin Number	Function	Pin Number	Function
1	Isolated Input for Low-side IGBT of Phase A	17	+15V Rtn (Signal Ground)
2	Return for Input at 1	18	Fault Output ⁽³⁾
3	Isolated Input for High-side IGBT of Phase A	19	Fault Clear Input ⁽³⁾
4	Return for Input at 3	20	+5V Output
5	Isolated Input for Low -side IGBT of Phase B	21	Over-Current Trip Set point ⁽³⁾
6	Return for Input at 5	22	DC Bus Current Output with Total Gain of 0.0365 V/A
7	Isolated Input for High-side IGBT of Phase B	23	Case Temperature Output with a gain of 0.010 V/°C
8	Return for Input at 7	24	Brake IGBT Gate Input
9	Isolated Input for Low-side IGBT of Phase C	25	Brake IGBT Emitter Input. This input is internally connected to Signal Ground
10	Return for Input at 9	26 to 30	DC Bus return
11	Isolated Input for High-side IGBT of Phase C	31 , 32	Brake Resistor Terminal. Brake Resistor Shall be Connected Between These Terminals and +VDC
12	Return for Input at 11	33 to 37	DC Bus "+VDC" input
13	NC	38 to 42	Phase C output
14	NC	43 to 47	Phase B output
15	SD ⁽³⁾	48 to 52	Phase A output
16	+15V Input	Case	Isolated

SENSITRON


TECHNICAL DATA

Data Sheet 4098, Rev. D

Package Drawing Top View:



Package Drawing Side View:



SENSITRON**TECHNICAL DATA****Data Sheet 4098, Rev. D**

Application Notes:**a- Shutdown Feature:**

- 1- SD is a dual function input/output, active low input. It is internally pulled high. As a low input shuts down all IGBTs regardless of the Hin and Lin signals.
- 2- SD is also internally activated by the over-temperature shutdown, over-current limit, under-voltage shutdown, and desaturation protection.
- 3- Over-temperature shutdown, and over-current limit are not latching features.
- 4- Under-voltage shutdown is automatically reset after 300 msec once the VCC rises above the threshold limit.
- 5- Desaturation shutdown is a latching feature and internally reset after 300 msec.
- 6- When any of the internal protection features is activated, SD is pulled down.
- 7- SD can be used to shutdown all IGBTs except the brake IGBT by an external command. An open collector switch shall be used to pull down SD externally.
- 8- Also, SD can be used as a fault condition output. Low output at SD indicates a fault situation.

b- Fault Output Feature:

- 1- Pin 18 Flt is a dual function pin. It is internally pulled high. If pulled down, it will freeze the status of all the six IGBTs regardless of the Hin and Lin signals
- 2- Pin 18 as an output reports desaturation protection activation. When desaturation protection is activated a low output for about 9 μ sec is reported.
- 3- If any other protection feature is activated, it will not be reported by Pin 18.

c- Fault Clear Output:

- 1- Pin 19 is a fault clear input. It can be used to reset a latching fault condition, due to desaturation protection.
- 2- Pin 19 is internally pulled down. A latching fault due to desaturation can be cleared by pulling high this input.
- 3- An internal fault clear is activated after 300 msec delay. If desired to clear the fault earlier, this input can be used.

TECHNICAL DATA

DISCLAIMER:

- 1- The information given herein, including the specifications and dimensions, is subject to change without prior notice to improve product characteristics. Before ordering, purchasers are advised to contact the Sensitron Semiconductor sales department for the latest version of the datasheet(s).
- 2- In cases where extremely high reliability is required (such as use in nuclear power control, aerospace and aviation, traffic equipment, medical equipment, and safety equipment), safety should be ensured by using semiconductor devices that feature assured safety or by means of users' fail-safe precautions or other arrangement.
- 3- In no event shall Sensitron Semiconductor be liable for any damages that may result from an accident or any other cause during operation of the user's units according to the datasheet(s). Sensitron Semiconductor assumes no responsibility for any intellectual property claims or any other problems that may result from applications of information, products or circuits described in the datasheets.
- 4- In no event shall Sensitron Semiconductor be liable for any failure in a semiconductor device or any secondary damage resulting from use at a value exceeding the absolute maximum rating.
- 5- No license is granted by the datasheet(s) under any patents or other rights of any third party or Sensitron Semiconductor.
- 6- The datasheet(s) may not be reproduced or duplicated, in any form, in whole or part, without the expressed written permission of Sensitron Semiconductor.
- 7- The products (technologies) described in the datasheet(s) are not to be provided to any party whose purpose in their application will hinder maintenance of international peace and safety nor are they to be applied to that purpose by their direct purchasers or any third party. When exporting these products (technologies), the necessary procedures are to be taken in accordance with related laws and regulations.