



SPN1028

Dual N-Channel Enhancement Mode MOSFET

DESCRIPTION

The SPN1028 is the Dual N-Channel enhancement mode field effect transistors are produced using high cell density DMOS technology. These products have been designed to minimize on-state resistance while provide rugged, reliable, and fast switching performance. They can be used in most applications requiring up to 640mA DC and can deliver pulsed currents up to 950mA. These products are particularly suited for low voltage, low current applications such as small servo motor control, power MOSFET gate drivers, and other switching applications.



FEATURES

- ◆ 30V/0.95A , $R_{DS(ON)}=550m\Omega@V_{GS}=4.5V$
- ◆ 30V/0.75A , $R_{DS(ON)}=650m\Omega@V_{GS}=2.5V$
- ◆ 30V/0.65A , $R_{DS(ON)}=850m\Omega@V_{GS}=1.8V$
- ◆ Super high density cell design for extremely low $R_{DS(ON)}$
- ◆ Exceptional on-resistance and maximum DC current capability
- ◆ ESD protected
- ◆ SOT-563 (SC-89-6L) package design


APPLICATIONS

- Drivers: Relays, Solenoids, Lamps, Hammers, Display, Memories, Transistors, etc.
- High saturation current capability. Direct Logic-Level Interface: TTL/CMOS
- Battery Operated Systems
- Solid-State Relays

PIN CONFIGURATION (SOT-563 / SC-89-6L)



PART MARKING





SPN1028

Dual N-Channel Enhancement Mode MOSFET

PIN DESCRIPTION

Pin	Symbol	Description
1	S1	Source 1
2	G1	Gate 1
3	D2	Drain 2
4	S2	Source 2
5	G2	Gate 2
6	D1	Drain1

ORDERING INFORMATION

Part Number	Package	Part Marking
SPN1028S56RGB	SOT-563	28

※ Week Code : A ~ Z (1 ~ 26) ; a ~ z (27 ~ 52)

※ SPN1028S56RGB : Tape Reel ; Pb – Free ; Halogen –Free

ABSOLUTE MAXIMUM RATINGS

(TA=25°C Unless otherwise noted)

Parameter	Symbol	Typical	Unit
Drain-Source Voltage	V _{DSS}	30	V
Gate –Source Voltage - Continuous	V _{GSS}	±12	V
Continuous Drain Current(T _J =150°C)	I _D	0.64	A
TA=25°C			
Pulsed Drain Current (*)	I _{DM}	0.95	A
Power Dissipation	P _D	1.35	W
TA=25°C			
Operating Junction Temperature	T _J	-55 ~ 150	°C
Storage Temperature Range	T _{STG}	-55 ~ 150	°C
Thermal Resistance-Junction to Ambient	R _{θJA}	375	°C/W

(*) Pulse width limited by safe operating area



SPN1028

Dual N-Channel Enhancement Mode MOSFET

ELECTRICAL CHARACTERISTICS

(TA=25°C Unless otherwise noted)





Parameter	Symbol	Conditions	Min.	Typ	Max.	Unit
Static						
Drain-Source Breakdown Voltage	$V_{(BR)DSS}$	$V_{GS}=0V, I_D=250\mu A$	30			V
Gate Threshold Voltage	$V_{GS(th)}$	$V_{DS}=V_{GS}, I_D=250\mu A$	0.4		1.0	
Gate Leakage Current	I_{GSS}	$V_{DS}=0V, V_{GS}=\pm 12V$			± 10	μA
Zero Gate Voltage Drain Current	I_{DSS}	$V_{DS}=48V, V_{GS}=0V$ $T_J=25^\circ C$			1	μA
		$V_{DS}=48V, V_{GS}=0V$ $T_J=55^\circ C$			100	
On-State Drain Current	$I_{D(on)}$	$V_{DS}\geq 4.5V, V_{GS}=5V$	0.7			A
Drain-Source On-Resistance	$R_{DS(on)}$	$V_{GS}=4.5V, I_D=0.95A$		0.45	0.55	Ω
		$V_{GS}=2.5V, I_D=0.75A$		0.50	0.65	
		$V_{GS}=1.8V, I_D=0.65A$		0.70	0.85	
Forward Transconductance	G_{fs}	$V_{DS}=10V, I_D=0.4A$		1.0		S
Diode Forward Voltage	V_{SD}	$V_{GS}=0V, I_S=0.15A$		0.8	1.2	V
Dynamic						
Total Gate Charge	Q_g	$V_{DD}=10V, I_D=0.6A,$ $V_{GS}=4.5V$		1.2	1.5	nC
Gate-Source Charge	Q_{gs}			0.2		
Gate-Drain Charge	Q_{gd}			0.3		
Input Capacitance	C_{iss}	$V_{DS}=10V, f=1MHz,$ $V_{GS}=0V$		7.2		pF
Output Capacitance	C_{oss}			13.5		
Reverse Transfer Capacitance	C_{rss}			1.6		
Turn-On Time	$t_{d(on)}$	$V_{DD}=10V, I_D=0.5A$ $R_G=6\Omega, V_{GEN}=4.5V$ $R_L=10\Omega$		5	10	nS
	t_r			8	15	
Turn-Off Time	$t_{d(off)}$			10	18	
	t_f			1.2	2.8	



SPN1028

Dual N-Channel Enhancement Mode MOSFET

TYPICAL CHARACTERISTICS









SPN1028

Dual N-Channel Enhancement Mode MOSFET

TYPICAL CHARACTERISTICS







SPN1028

Dual N-Channel Enhancement Mode MOSFET


TYPICAL CHARACTERISTICS



Threshold Voltage Variance Over Temperature



Single Pulse Power, Junction-to-Ambient



Normalized Thermal Transient Impedance, Junction-to-Foot



SPN1028

Dual N-Channel Enhancement Mode MOSFET

Information provided is alleged to be exact and consistent. SYNC Power Corporation presumes no responsibility for the penalties of use of such information or for any violation of patents or other rights of third parties which may result from its use. No license is granted by allegation or otherwise under any patent or patent rights of SYNC Power Corporation. Conditions mentioned in this publication are subject to change without notice. This publication surpasses and replaces all information previously supplied. SYNC Power Corporation products are not authorized for use as critical components in life support devices or systems without express written approval of SYNC Power Corporation.

© The SYNC Power logo is a registered trademark of SYNC Power Corporation

© 2022 SYNC Power Corporation – Printed in Taiwan – All Rights Reserved

SYNC Power Corporation

7F-2, No.3-1, Park Street

NanKang District (NKSP), Taipei, Taiwan, 115, R.O.C

Phone: 886-2-2655-8178

Fax: 886-2-2655-8468

© <http://www.syncpower.com>