

## Type SQF Series

### Key Features

- Overheat fusing
- Various current ratings
- Up to 2.4 Watts continuous power
- 2 sizes
- Values up to 50K
- Suited to overloading and to overheating



As the Thermal fuses are incorporated, these cement filled resistors respond quickly to overloading as well as to external overheating. The SQF series also provides outstanding features against surges, and are therefore suitable for the preventing of inrush current for switching regulators. Obvious economic advantages can be achieved by not having to specify a separate thermal fuse.

### Characteristics - Electrical


Resistive Element:	SQF5 R10 - 150R SQF7 R10 - 430R	Wirewound
	SQF5 151R - 50K SQF7 431R - 50K	Metal Film
Tolerance:	—	J - +/-%
Temperature Coefficient of Resistance (TCR):	<1R0	+/-600PPM
	1R0 - 50K	+/-300PPM
Operating Temp Range:	—	-25 ~ 125 deg.C
Short Time Overload:	10 x Rated Power for 5 seconds	+/-2%
Voltage Withstand:	1,000V AC 1 Minute	No change
Insulation Resistance:	500V Megger	1000M Ohm
Temperature Cycle:	-25 ~ +125 deg. C for 5 cycles	+/-1%
Load Life:	25 Deg. C on off cycle for 1000 Hours	+/-5%
Moisture-Proof Load Life:	40 Deg. C. 90-95% humidity 500hours +24/-0	+/-5%
Incombustability:	16 X rated Wattage for 5 Minutes	No Flame

### Characteristics - Electrical

Type	Resistance Range	Tolerance	Fuse Type (°C) Rated		Rated Wattage (Continuous)	Maximum Wattage (Momentary)	Maximum Working Voltage	Working Current
			Rated Temp.	Cut Off Temp.				
SQF5	R10 - 50K	+/-5%	145	140 +/-2	1.6W	5W	250V	3A
SQF5			145	140 +/-2	1.6W	5W	250V	5A
SQF7			145	140 +/-2	2.2W	7W	250V	3A
SQF7			145	140 +/-2	2.2W	7W	250V	5A
SQF7			132	131+3/-4	2.2W	7W	250V	10A
SQF7			185	181 +/-2	2.4W	7W	250V	10A

## Type SQF Series

### Derating Curve



### Rated Power

Rated Power is the value of Max load voltage specified at the ambient temperature of 25°C, and shall meet the functions of electrical and mechanical performance. When the ambient temperature surpasses the above mentioned temperature, the value declines as per the Derating Curve.

### Rated Voltage


It is calculated through the following formula:

$$E = \sqrt{P \times R}$$

where E: rated voltage (V)  
P: rated power (W)  
R: total nominal resistance (Ω)

However, in case the voltage calculated exceeds the maximum load voltage, such the maximum load voltage shall be regarded as its rated voltage, means whichever less.

### Dimensions



Type	W ± 1	S ± 1	H ± 1.5	D1 ±0.1	D2 ±0.1
SQF5	13	9	25	0.8	3A:0.6 5A:1.0
SQF7	13	9	39	0.8	10A:1.0

### How to Order

SQF5	50R	J	145	5
Common Part	Resistance Value	Tolerance	Fuse Temperature	Max Working Current
SQF5 SQF7	0.1 Ohm = R10 1.0 Ohm = 1R0 1000 Ohms = 1K0 50,000Ohms = 50K	J = +/-5%	See table above	See Table Above 3 = 3A 5 = 5A 10 = 10A

TE Connectivity, TE connectivity (logo) and TE (logo) are trademarks.

Other logos, product and Company names mentioned herein may be trademarks of their respective owners.

While TE has made every reasonable effort to ensure the accuracy of the information in this datasheet, TE does not guarantee that it is error-free, nor does TE make any other representation, warranty or guarantee that the information is accurate, correct, reliable or current. TE reserves the right to make any adjustments to the information contained herein at any time without notice. TE expressly disclaims all implied warranties regarding the information contained herein, including but not limited to, any implied warranties of merchantability or fitness for a particular purpose. The dimensions in this datasheet are for reference purposes only and are subject to change without notice. Specifications are subject to change without notice. Consult TE for the latest dimensions and design specifications.